

<<ISO and IEC logos go here>>

**Draft 3, 2009-07-24**

# **Information technology — Document description and processing languages — Office Open XML File Formats —**

## **Part 1: Fundamentals and Markup Language Reference**

### **TECHNICAL CORRIGENDUM 1**

*Technologies de l'information — Description des documents et langages de traitement — Formats de fichier "Office Open XML" —  
Partie 1: Principes essentiels et référence de langage de balisage*

### **RECTIFICATIF TECHNIQUE 1**

Technical Corrigendum 1 to ISO/IEC 29500-1:2008 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology, Subcommittee SC 34, Document description and processing languages*.

It contains corrections that resolve various Defect Reports submitted against ISO/IEC 29500-1:2008.

A correction can involve changes to one or more clauses or subclauses; it can even apply to multiple Parts of ISO/IEC 29500. For changes to ISO/IEC 29500-1:2008, each such change has its own entry below.

Changes are presented in ascending clause, subclause, and page number order.

**ISO/IEC 29500-1:2008/Cor.1:2009(E)****Notational conventions**

The title of each change is the complete reference to the clause or subclause being corrected. In all cases, the title begins with the clause or subclause number, the clause or subclause name, and the page number. In those cases containing changes to a particular row of a table, the value in that row's first column is appended to the title. As the lines in each XML schema subclause are numbered starting at 1 and going to the end of a schema, corrections to schemas also contain the numbers of the lines being corrected.

A change can contain any one or more of the following kinds of edits:

1. Addition of text: New text is displayed in blue and is underlined, as demonstrated here.
2. Deletion of text: ~~Deleted text is displayed in red and is struck through, as demonstrated here.~~
3. Change of format of text: Text whose format (but not its content) has changed is displayed in green and is double-underlined, as demonstrated here.

Many changes involve edits to large paragraphs, tables, and/or XML fragments. In such cases, the changes contain only as much unchanged content as is necessary to establish the correct context of each change. Omitted content is identified via the use of ellipses (...).

Within a change, intent that cannot be represented visually as an edit is written as an instruction in italic and delimited by curly brackets; for example: *{In paragraph 2, item 4, and in paragraph 4, make the numbers in the text “17–23” hyperlinked forward references to Clauses 17 and 23.}*

## Contents

<b>Introduction (For WG4 use only; will be removed from the final COR) .....</b>	<b>1</b>
<b>Changes .....</b>	<b>2</b>
1. <b>§3, "Normative References", p. 8 .....</b>	<b>2</b>
2. <b>§3, "Normative References", p. 10 .....</b>	<b>2</b>
3. <b>§3, "Normative References", p. 10 .....</b>	<b>2</b>
4. <b>§3, "Normative References", p. 11 .....</b>	<b>2</b>
5. <b>§4, "Terms and Definitions", p. 12 .....</b>	<b>2</b>
6. <b>§4, "Terms and Definitions", p. 13 .....</b>	<b>2</b>
7. <b>§5, "Notational Conventions", p. 14.....</b>	<b>3</b>
8. <b>§7, "General Description", p. 16.....</b>	<b>3</b>
9. <b>§8.1, "Packages and Parts", p. 17 .....</b>	<b>3</b>
10. <b>§9.2, "Relationships in Office Open XML", p. 23.....</b>	<b>3</b>
11. <b>§10.1.2, "Office Open XML Native Extensibility Constructs", p. 28.....</b>	<b>3</b>
12. <b>§11.3.1, "Alternative Format Import Part", p. 32 .....</b>	<b>4</b>
13. <b>§11.3.11, "Numbering Definitions Part", p. 55 .....</b>	<b>4</b>
14. <b>§11.3.11, "Numbering Definitions Part", p. 55 .....</b>	<b>4</b>
15. <b>§11.3.11, "Numbering Definitions Part", p. 55 .....</b>	<b>4</b>
16. <b>§11.3.12, "Style Definitions Part", p. 55 .....</b>	<b>5</b>
17. <b>§11.3.12, "Style Definitions Part", p. 56 .....</b>	<b>5</b>
18. <b>§11.6, "Master Documents and Subdocuments", p. 59 .....</b>	<b>5</b>
19. <b>§12.3.7, "Dialogsheet Part", p. 76 .....</b>	<b>5</b>
20. <b>§12.3.7, "Dialogsheet Part", p. 76 .....</b>	<b>5</b>
21. <b>§12.3.9, "External Workbook References Part", p. 79 .....</b>	<b>5</b>
22. <b>§12.3.10, "Metadata Part", pp. 82–83.....</b>	<b>6</b>
23. <b>§12.3.12, "Pivot Table Cache Definition Part", p. 85.....</b>	<b>6</b>
24. <b>§12.3.20, "Styles Part", p. 94.....</b>	<b>6</b>
25. <b>§12.3.23, "Workbook Part", p. 98 .....</b>	<b>6</b>
26. <b>§12.3.24, "Worksheet Part", p. 101.....</b>	<b>6</b>
27. <b>§15.2.15, "Printer Settings Part", p. 162.....</b>	<b>7</b>
28. <b>§17.2.1, "background (Document Background)", p. 193, attribute color.....</b>	<b>7</b>
29. <b>§17.3.1.12, "ind (Paragraph Indentation)", p. 226.....</b>	<b>7</b>

30.	<b>§17.3.1.13, “jc (Paragraph Alignment)”, p. 231 .....</b>	7
31.	<b>§17.3.1.27, “pStyle (Referenced Paragraph Style)”, p. 253 .....</b>	7
32.	<b>§17.3.1.27, “pStyle (Referenced Paragraph Style)”, p. 253, attribute val.....</b>	8
33.	<b>§17.3.1.30, “rPr (Previous Run Properties for the Paragraph Mark)”, p. 258 .....</b>	8
34.	<b>§17.3.1.37, “tab (Custom Tab Stop)”, p. 269 .....</b>	8
35.	<b>§17.3.1.37, “tab (Custom Tab Stop)”, p. 270, attribute pos .....</b>	8
36.	<b>§17.3.1.37, “tab (Custom Tab Stop)”, p. 270, attribute val .....</b>	8
37.	<b>§17.3.1.38, “tabs (Set of Custom Tab Stops)”, p. 271 .....</b>	8
38.	<b>§17.3.1.39, “textAlignment (Vertical Character Alignment on Line)”, p. 272, attribute val.....</b>	9
39.	<b>§17.3.1.40, “textboxTightWrap (Allow Surrounding Paragraphs to Tight Wrap to Text Box Contents)”, p. 273.....</b>	9
40.	<b>§17.3.1.41, “textDirection (Paragraph Text Flow Direction)”, p. 275 .....</b>	9
41.	<b>§17.3.1.41, “textDirection (Paragraph Text Flow Direction)”, p. 275, attribute val.....</b>	9
42.	<b>§17.3.2.5, “caps (Display All Characters As Capital Letters)”, p. 285 .....</b>	10
43.	<b>§17.3.2.26, “rFonts (Run Fonts)”, p. 317, attribute cs.....</b>	10
44.	<b>§17.3.2.26, “rFonts (Run Fonts)”, p. 318, attribute cstheme.....</b>	10
45.	<b>§17.3.2.27, “rPr (Previous Run Properties)”, p. 321.....</b>	11
46.	<b>§17.3.2.28, “rPr (Run Properties)”, p. 323 .....</b>	11
47.	<b>§17.3.2.29, “rStyle (Referenced Character Style)”, p. 326, attribute val .....</b>	11
48.	<b>§17.3.2.33, “smallCaps (Small Caps)”, p. 330.....</b>	11
49.	<b>§17.3.3.18, “noBreakHyphen (Non Breaking Hyphen Character)”, pp. 363–364.....</b>	12
50.	<b>§17.3.3.20, “objectEmbed (Embedded Object Properties)”, p. 366, attribute fieldCodes .....</b>	13
51.	<b>§17.3.3.21, “objectLink (Linked Object Properties)”, p. 368, attribute fieldCodes .....</b>	14
52.	<b>§17.3.3.23, “ptab (Absolute Position Tab Character)”, p. 371.....</b>	14
53.	<b>§17.3.3.32, “tab (Tab Character)”, p. 383 .....</b>	15
54.	<b>§17.3.4, “Border Properties (CT_Border)”, p. 388, attribute themeShade .....</b>	15
55.	<b>§17.4, “Tables”, p. 399 .....</b>	15
56.	<b>§17.4.18, “header (Header Cell Reference)”, p. 431, attribute val .....</b>	15
57.	<b>§17.4.22, “hMerge (Horizontally Merged Cell)”, p. 436 .....</b>	16
58.	<b>§17.4.22, “hMerge (Horizontally Merged Cell)”, p. 436, attribute val.....</b>	16
59.	<b>§17.4.27, “jc (Table Alignment Exception)”, p. 441.....</b>	16
60.	<b>§17.4.28, “jc (Table Row Alignment)”, p. 442 .....</b>	16
61.	<b>§17.4.29, “jc (Table Alignment)”, p. 443 .....</b>	17

62.	§17.4.31, “shd (Table Shading Exception)”, p. 446 .....	17
63.	§17.4.38, “tbl (Table)”, p. 453 .....	17
64.	§17.4.39, “tblBorders (Table Borders)”, p. 455 .....	17
65.	§17.4.40, “tblBorders (Table Borders Exceptions)”, p. 457 .....	17
66.	§17.4.41, “tblCaption (Table Caption)”, p. 458, attribute val.....	18
67.	§17.4.42, “tblCellMar (Table Cell Margin Exceptions)”, p. 459 .....	18
68.	§17.4.43, “tblCellMar (Table Cell Margin Defaults)”, p. 460 .....	18
69.	§17.4.47, “tblDescription (Table Description)”, p. 465, attribute val .....	19
70.	§17.4.51, “tblInd (Table Indent from Leading Margin)”, p. 469 .....	19
71.	§17.4.59, “tblPr (Previous Table Properties)”, p. 483 .....	19
72.	§17.4.60, “tblPr (Table Properties)”, p. 485.....	20
73.	§17.4.61, “tblPrEx (Table-Level Property Exceptions)”, p. 487.....	20
74.	§17.4.62, “tblPrEx (Previous Table-Level Property Exceptions)”, p. 489 .....	20
75.	§17.4.63, “tblStyle (Referenced Table Style)”, p. 491, attribute val.....	21
76.	§17.4.65, “tblW (Preferred Table Width Exception)”, p. 493 .....	21
77.	§17.4.66, “tc (Table Cell)”, pp. 494–495 .....	21
78.	§17.4.67, “tcBorders (Table Cell Borders)”, p. 499.....	22
79.	§17.4.69, “tcMar (Single Table Cell Margins)”, p. 501.....	22
80.	§17.4.70, “tcPr (Table Cell Properties)”, p. 502 .....	22
81.	§17.4.73, “textDirection (Table Cell Text Flow Direction)”, p. 507 .....	23
82.	§17.4.73, “textDirection (Table Cell Text Flow Direction)”, p. 508, attribute val .....	23
83.	§17.4.79, “tr (Table Row)”, pp. 512–513 .....	24
84.	§17.4.85, “vMerge (Vertically Merged Cell)”, pp. 523–524.....	24
85.	§17.4.85, “vMerge (Vertically Merged Cell)”, pp. 523–524, attribute val .....	25
86.	§17.4.88, “Table Measurement (CT_TblWidth)”, p. 527 .....	25
87.	§17.5, “Custom Markup”, p. 528 .....	25
88.	§17.5.1, “Custom XML and Smart Tags”, p. 529.....	26
89.	§17.5.1, “Custom XML and Smart Tags”, p. 529.....	26
90.	§17.5.1, “Custom XML and Smart Tags”, p. 530.....	26
91.	§17.5.1.1, “attr (Custom XML Attribute)”, p. 531 .....	26
92.	§17.5.1.1, “attr (Custom XML Attribute)”, p. 531 .....	26
93.	§17.5.1.3, “customXml, Inline-Level Custom XML Element”, p. 534 .....	26

94.	§17.5.1.8, “placeholder (Custom XML Element Placeholder Text)”, p. 545–546, attribute val.....	27
95.	§17.5.1.9, “SmartTag, Inline-Level Smart Tag”, p. 547 .....	27
96.	§17.5.2.1, “alias (Friendly Name)”, p. 551, attribute val .....	27
97.	§17.5.2.5, “comboBox (Combo Box Structured Document Tag)”, p. 554 .....	28
98.	§17.5.2.5, “comboBox (Combo Box Structured Document Tag)”, pp. 555–556.....	28
99.	§17.5.2.8, “dateFormat (Date Display Mask)”, p. 562, attribute val .....	28
100.	§17.5.2.9, “docPart (Document Part Reference)”, p. 563, attribute val .....	29
101.	§17.5.2.10, “docPartCategory (Document Part Category Filter)”, p. 564–565, attribute val .....	29
102.	§17.5.2.11, “docPartGallery (Document Part Gallery Filter)”, p. 566, attribute val.....	30
103.	§17.5.2.15, “dropDownList (Drop-Down List Structured Document Tag)”, p. 570.....	30
104.	§17.5.2.31, “sdt, Inline-Level Structured Document Tag”, p. 590 .....	30
105.	§17.5.2.42, “tag (Programmatic Tag)”, p. 606, attribute val .....	31
106.	§17.6.1.11, “pgMar (Page Margins)”, p. 641.....	31
107.	§17.6.2, “bottom (Bottom Border)”, p. 617, attribute themeShade .....	31
108.	§17.6.7, “left (Left Border)”, p. 632, attribute themeShade.....	31
109.	§17.6.15, “right (Right Border)”, p. 655, attribute themeShade .....	31
110.	§17.6.20, “textDirection (Text Flow Direction)”, p. 667 .....	32
111.	§17.6.20, “textDirection (Text Flow Direction)”, p. 667, attribute val.....	32
112.	§17.6.21, “top (Top Border)”, p. 673, attribute themeShade.....	32
113.	§17.7.4, “General Style Properties”, p. 683 .....	32
114.	§17.7.4, “General Style Properties”, p. 683 .....	33
115.	§17.7.4.1, “aliases (Alternate Style Names)”, p. 684, attribute val .....	33
116.	§17.7.4.3, “basedOn (Parent Style ID)”, p. 688, attribute val.....	33
117.	§17.7.4.6, “link (Linked Style Reference)”, p. 694, attribute val .....	34
118.	§17.7.4.9, “name (Primary Style Name)”, p. 699, attribute val.....	34
119.	§17.7.4.10, “next (Style For Next Paragraph)”, p. 701, attribute val .....	34
120.	§17.7.4.17, “style (Style Definition)”, pp. 706–707.....	35
121.	§17.7.4.17, “style (Style Definition)”, p. 707.....	35
122.	§17.7.4.17, “style (Style Definition)”, p. 708.....	36
123.	§17.7.5, “Document Defaults”, p. 715 .....	36
124.	§17.7.5.1, “docDefaults (Document Default Paragraph and Run Properties)”, p. 716 .....	36
125.	§17.7.5.1, “docDefaults (Document Default Paragraph and Run Properties)”, p. 716 .....	36

126.	<b>§17.7.6, “Table Styles”, p. 724.....</b>	37
127.	<b>§17.7.6, “Table Styles”, p. 725.....</b>	37
128.	<b>§17.7.6.8, “tcPr (Table Style Conditional Formatting Table Cell Properties)”, p. 736 .....</b>	38
129.	<b>§17.7.8, “Paragraph Styles”, p. 742 .....</b>	38
130.	<b>§17.7.8.1, “Numbering in Paragraph Styles”, p. 744.....</b>	39
131.	<b>§17.7.9, “Run (Character) Styles”, p. 747.....</b>	39
132.	<b>§17.8.3.1, “altName (Alternate Names for Font)”, p. 752, attribute val .....</b>	39
133.	<b>§17.8.3.13, “panose1 (Panose-1 Typeface Classification Number)”, p. 766 .....</b>	39
134.	<b>§17.9, “Numbering”, p. 773.....</b>	40
135.	<b>§17.9, “Numbering”, p. 773.....</b>	40
136.	<b>§17.9.1, “abstractNum (Abstract Numbering Definition)”, p. 774 .....</b>	40
137.	<b>§17.9.1, “abstractNum (Abstract Numbering Definition)”, pp. 774–775.....</b>	40
138.	<b>§17.9.1, “abstractNum (Abstract Numbering Definition)”, p. 775, attribute abstractNumId .....</b>	41
139.	<b>§17.9.5, “legacy (Legacy Numbering Level Properties)”, p. 780 .....</b>	41
140.	<b>§17.9.5, “legacy (Legacy Numbering Level Properties)”, p. 780 .....</b>	41
141.	<b>§17.9.6, “lvl (Numbering Level Override Definition)”, p. 782.....</b>	41
142.	<b>§17.9.6, “lvl (Numbering Level Override Definition)”, pp. 782–783 .....</b>	41
143.	<b>§17.9.6, “lvl (Numbering Level Override Definition)”, p. 783.....</b>	42
144.	<b>§17.9.8, “lvlJc (Justification)”, p. 788.....</b>	42
145.	<b>§17.9.9, “lvlOverride (Numbering Level Definition Override)”, p. 790.....</b>	42
146.	<b>§17.9.9, “lvlOverride (Numbering Level Definition Override)”, pp. 790–791 .....</b>	43
147.	<b>§17.9.9, “lvlOverride (Numbering Level Definition Override)”, p. 791.....</b>	43
148.	<b>§17.9.9, “lvlOverride (Numbering Level Definition Override)”, pp. 791–792, attribute ilvl.....</b>	43
149.	<b>§17.9.11, “lvlRestart (Restart Numbering Level Symbol)”, pp. 793–794 .....</b>	43
150.	<b>§17.9.11, “lvlRestart (Restart Numbering Level Symbol)”, pp. 793–794 .....</b>	44
151.	<b>§17.9.14, “name (Abstract Numbering Definition Name)”, p. 799, attribute val .....</b>	44
152.	<b>§17.9.16, “num (Numbering Definition Instance)”, p. 802.....</b>	45
153.	<b>§17.9.18, “num (Numbering Definition Instance)”, p. 802.....</b>	45
154.	<b>§17.9.18, “numFmt (Numbering Format)”, p. 804 .....</b>	45
155.	<b>§17.9.18, “numFmt (Numbering Format)”, p. 804 .....</b>	45
156.	<b>§17.9.18, “numFmt (Numbering Format)”, p. 804 .....</b>	46
157.	<b>§17.9.22, “numStyleLink (Numbering Style Reference)”, p. 809, attribute val.....</b>	46

158.	<b>§17.9.23, “pPr (Numbering Level Associated Paragraph Properties)”, p. 810 .....</b>	46
159.	<b>§17.9.24, “pStyle (Paragraph Style's Associated Numbering Level)”, p. 812 .....</b>	46
160.	<b>§17.9.24, “pStyle (Paragraph Style's Associated Numbering Level)”, p. 813, attribute val.....</b>	47
161.	<b>§17.9.28, “styleLink (Numbering Style Definition)”, p. 819, attribute val .....</b>	47
162.	<b>§17.11.4, “endnotePr (Document-Wide Endnote Properties)”, p. 845.....</b>	47
163.	<b>§17.11.6, “endnoteRef (Endnote Reference Mark)”, p. 848.....</b>	48
164.	<b>§17.11.17, “numFmt (Endnote Numbering Format)”, p. 866 .....</b>	48
165.	<b>§17.11.18, “numFmt (Footnote Numbering Format)”, p. 867 .....</b>	48
166.	<b>§17.12.4, “description (Description for Entry)”, p. 881, attribute val.....</b>	48
167.	<b>§17.12.9, “gallery (Gallery Associated With Entry)”, p. 888 .....</b>	49
168.	<b>§17.12.12, “name (Category Associated With Entry)”, p. 891.....</b>	49
169.	<b>§17.12.12, “name (Category Associated With Entry)”, p. 891, attribute val .....</b>	49
170.	<b>§17.12.14, “style (Associated Paragraph Style Name)”, p. 894, attribute val.....</b>	50
171.	<b>§17.13.4.2, “comment (Comment Content)”, p. 905, attribute initials .....</b>	50
172.	<b>§17.13.4.2, “comment (Comment Content)”, p. 905, attribute initials .....</b>	50
173.	<b>§17.13.5.13, “del (Deleted Math Control Character)”, p. 949 .....</b>	50
174.	<b>§17.13.5.16, “ins (Inserted Math Control Character)”, p. 957.....</b>	50
175.	<b>§17.13.5.34, “tblPrChange (Revision Information for Table Properties)”, p. 1014 .....</b>	51
176.	<b>§17.13.5.36, “tcPrChange (Revision Information for Table Cell Properties)”, p. 1018.....</b>	51
177.	<b>§17.14.3, “addressFieldName (Column Containing E-mail Address)”, p. 1050, attribute val.....</b>	51
178.	<b>§17.14.8, “connectString (Data Source Connection String)”, p. 1056, attribute val .....</b>	52
179.	<b>§17.14.21, “mailSubject (Merged E-mail or Fax Subject Line)”, p. 1070, attribute val .....</b>	52
180.	<b>§17.14.23, “mappedName (Predefined Merge Field Name)”, p. 1072 .....</b>	52
181.	<b>§17.14.23, “mappedName (Predefined Merge Field Name)”, p. 1073, attribute val.....</b>	53
182.	<b>§17.14.24, “name (Data Source Name for Column)”, p. 1074, attribute val .....</b>	53
183.	<b>§17.14.26, “query (Query For Data Source Records To Merge)”, p. 1077, attribute val .....</b>	54
184.	<b>§17.14.31, “table (Data Source Table Name)”, p. 1084, attribute val .....</b>	54
185.	<b>§17.14.34, “udl (UDL Connection String)”, p. 1088, attribute val.....</b>	54
186.	<b>§17.15.1.1, “activeWritingStyle (Grammar Checking Settings)”, p. 1091 .....</b>	55
187.	<b>§17.15.1.5, “attachedSchema (Attached Custom XML Schema)”, p. 1096, attribute val.....</b>	55
188.	<b>§17.15.1.7, “autoCaption (Single Automatic Captioning Setting)”, p. 1098 .....</b>	55
189.	<b>§17.15.1.8, “autoCaptions (Automatic Captioning Settings)”, p. 1101.....</b>	56

190.	§17.15.1.11, “bookFoldPrinting (Book Fold Printing)”, p. 1104 .....	56
191.	§17.15.1.13, “bookFoldRevPrinting (Reverse Book Fold Printing)”, p. 1108 .....	56
192.	§17.15.1.16, “caption (Single Caption Type Definition)”, p. 1114, attribute chapNum .....	56
193.	§17.15.1.16, “caption (Single Caption Type Definition)”, p. 1115, attribute heading .....	56
194.	§17.15.1.18, “captions (Caption Settings)”, p. 1122 .....	57
195.	§17.15.1.19, “clickAndTypeStyle (Paragraph Style Applied to Automatically Generated Paragraphs)”, p. 1125, attribute val.....	57
196.	§17.15.1.23, “decimalSymbol (Radix Point for Field Code Evaluation)”, p. 1133, attribute val .....	57
197.	§17.15.1.24, “defaultTableStyle (Default Table Style for Newly Inserted Tables)”, p. 1134, attribute val.....	57
198.	§17.15.1.29, “documentProtection (Document Editing Restrictions)”, p. 1144 .....	58
199.	§17.15.1.44, “drawingGridHorizontalOrigin (Drawing Grid Horizontal Origin Point)”, p. 1158 .....	58
200.	§17.15.1.46, “drawingGridVerticalOrigin (Drawing Grid Vertical Origin Point)”, p. 1160.....	58
201.	§17.15.1.54, “ignoreMixedContent (Ignore Mixed Content When Validating Custom XML Markup)”, p. 1168 .....	59
202.	§17.15.1.56, “listSeparator (List Separator for Field Code Evaluation)”, p. 1169, attribute val .....	61
203.	§17.15.1.57, “mirrorMargins (Mirror Page Margins)”, p. 1170 .....	61
204.	§17.15.1.64, “printTwoOnOne (Print Two Pages Per Sheet)”, p. 1177 .....	61
205.	§17.15.1.74, “saveInvalidXml (Allow Saving Document As XML File When Custom XML Markup Is Invalid)”, p. 999 61	
206.	§17.15.1.77, “saveXmlDataOnly (Only Save Custom XML Markup)”, p. 1194 .....	61
207.	§17.15.1.77, “saveXmlDataOnly (Only Save Custom XML Markup)”, p. 1194 .....	62
208.	§17.15.1.93, “writeProtection (Write Protection)”, p. 1213 .....	62
209.	§17.15.2, “Web Page Settings”, p. 1219 .....	63
210.	§17.15.2.13, “doNotUseLongFileNames”, p. 1237 .....	63
211.	§17.15.2.14, “encoding (Output Encoding When Saving as Web Page)”, p. 1239, attribute val .....	63
212.	§17.15.2.17, “frameLayout (Frameset Layout)”, p. 1244, attribute val.....	64
213.	§17.15.2.30, “name (Frame Name)”, p. 1265, attribute val .....	64
214.	§17.15.2.40, “sz (Frame Size)”, p. 1280, attribute val .....	64
215.	§17.15.2.41, “sz (Nested Frameset Size)”, p. 1281, attribute val .....	65
216.	§17.15.2.43, “title (Frame or Frameset Title)”, p. 1284, attribute val .....	65
217.	§17.15.2.46, “webSettings (Web Page Settings)”, p. 1288 .....	65
218.	§17.16.1, “Syntax”, p. 1301 .....	66
219.	§17.16.1, “Syntax”, p. 1303 .....	66
220.	§17.16.1, “Syntax”, p. 1304 .....	66

221.	§17.16.5, “Field definitions”, p. 1341, category User Information .....	66
222.	§17.16.5.1, “ADDRESSBLOCK”, p. 1342, switch \d .....	66
223.	§17.16.5.1, “ADDRESSBLOCK”, p. 1342, switch \f.....	67
224.	§17.16.5.1, “ADDRESSBLOCK”, p. 1343, switch \l .....	67
225.	§17.16.5.13, “DATE”, p. 1353, switch \l.....	67
226.	§17.16.5.18, “FILESIZE”, p. 1358 .....	67
227.	§17.16.5.33, “LISTNUM”, p. 1369 .....	67
228.	§17.16.5.49, “QUOTE”, p. 1382 .....	67
229.	§17.16.10, “default (Default Text Box Form Field String)”, p. 1406, attribute val .....	67
230.	§17.16.17, “ffData (Form Field Properties)”, p. 1413.....	68
231.	§17.16.18, “fldChar (Complex Field Character)”, p. 1415.....	68
232.	§17.16.18, “fldChar (Complex Field Character)”, p. 1416, attribute dirty.....	68
233.	§17.16.18, “fldChar (Complex Field Character)”, p. 1417, attribute fldLock.....	69
234.	§17.16.19, “fldSimple, Simple Field”, p. 1418.....	69
235.	§17.16.20, “format (Text Box Form Field Formatting)”, p. 1421, attribute val .....	69
236.	§17.16.22, “hyperlink, Hyperlink”, p. 1424.....	69
237.	§17.16.25, “listEntry (Drop-Down List Entry)”, p. 1432, attribute val .....	70
238.	§17.18.3, “ST_BrClear (Line Break Text Wrapping Restart Location)”, pp. 1508–1509.....	70
239.	§17.18.3, “ST_BrClear (Line Break Text Wrapping Restart Location)”, p. 1509 .....	71
240.	§17.18.16, “ST_DocPartGallery (Entry Gallery Types)”, p. 1523 .....	71
241.	§17.18.25, “ST_FFFHelpTextVal”, p. 1534 .....	72
242.	§17.18.26, ST_FFName, p. 1535.....	72
243.	§17.18.44, “ST_Jc (Horizontal Alignment Type)”, p. 1554 .....	72
244.	§17.18.51, “ST_MacroName”, p. 1563.....	72
245.	§17.18.57, “ST_Merge (Merged Cell Type)”, pp. 1569–1570.....	72
246.	§17.18.59, “ST_NumberFormat (Numbering Format)”, p. 1574, enumeration value arabicAlpha .....	73
247.	§17.18.59, “ST_NumberFormat (Numbering Format)”, p. 1584, enumeration value decimalFullWidth2 .....	73
248.	§17.18.59, “ST_NumberFormat (Numbering Format)”, p. 1587, enumeration value hebrew1 .....	74
249.	§17.18.59, “ST_NumberFormat (Numbering Format)”, p. 1590, enumeration value hindiConsonants.....	74
250.	§17.18.59, “ST_NumberFormat (Numbering Format)”, p. 1591, enumeration value hindiNumbers.....	74
251.	§17.18.59, “ST_NumberFormat (Numbering Format)”, p. 1592, enumeration value hindiVowels.....	74
252.	§17.18.59, “ST_NumberFormat (Numbering Format)”, p. 1613, enumeration value thaiLetters .....	75

253.	§17.18.78, “ <b>ST_Shd (Shading Patterns)</b> ”, p. 1633 .....	75
254.	§17.18.84, “ <b>ST_TabJc (Custom Tab Stop Type)</b> ”, p. 1651 .....	75
255.	§17.18.93, “ <b>ST_TextDirection (Text Flow Direction)</b> ”, p. 1665 .....	75
256.	§17.18.93, “ <b>ST_TextDirection (Text Flow Direction)</b> ”, p. 1665 .....	75
257.	§17.18.93, “ <b>ST_TextDirection (Text Flow Direction)</b> ”, p. 1666 .....	76
258.	§17.18.98, “ <b>ST_UcharHexNumber (Two Digit Hexadecimal Value)</b> ”, p. 1672.....	76
259.	§18.2.3, “ <b>customWorkbookView (Custom Workbook View)</b> ”, p. 1709–1710, attribute <b>autoUpdate</b> .....	76
260.	§18.2.5, “ <b>definedName (Defined Name)</b> ”, p. 1719, new attribute .....	76
261.	§18.2.20, “ <b>sheets (Sheets)</b> ”, p. 1733.....	76
262.	§18.2.24, “ <b>webPublishing</b> ”, p. 1736.....	77
263.	§18.2.27, “ <b>workbook (Workbook)</b> ”, p. 1739 .....	77
264.	§18.3.1.2, “ <b>autoFilter (AutoFilter Settings)</b> ”, p. 1758.....	77
265.	§18.3.1.3, “ <b>brk (Break)</b> ”, p. 1759, attribute <b>man</b> .....	77
266.	§18.3.1.10, “ <b>cfRule (Conditional Formatting Rule)</b> ”, pp. 1765–1766, various attributes .....	78
267.	§18.3.1.11, “ <b>cfvo (Conditional Format Value Object)</b> ”, p. 1768, attribute <b>gte</b> .....	78
268.	§18.3.1.25, “ <b>customSheetView (Custom Sheet View)</b> ”, p. 1786 .....	78
269.	§18.3.1.29, “ <b>dataConsolidate (Data Consolidate)</b> ”, p. 1790, new attribute .....	79
270.	§18.3.1.32, “ <b>dataValidation (Data Validation)</b> ”, p. 1791, attribute <b>allowBlank</b> .....	79
271.	§18.3.1.38, “ <b>evenFooter (Even Page Footer)</b> ”, p. 1802, new attribute.....	79
272.	§18.3.1.39, “ <b>evenHeader</b> ”, p. 1804 .....	79
273.	§18.3.1.40, “ <b>f (Formula)</b> ”, p. 1806, attribute <b>aca</b> .....	80
274.	§18.3.1.40, “ <b>f (Formula)</b> ”, p. 1807, attribute <b>r2</b> .....	80
275.	§18.3.1.40, “ <b>f (Formula)</b> ”, p. 1808, new attribute.....	80
276.	§18.3.1.41, “ <b>firstFooter (First Page Footer)</b> ”, p. 1808 .....	80
277.	§18.3.1.41, “ <b>firstFooter (First Page Footer)</b> ”, p. 1808, new attribute.....	80
278.	§18.3.1.42, “ <b>firstHeader (First Page Header)</b> ”, p. 1808 .....	81
279.	§18.3.1.42, “ <b>firstHeader (First Page Header)</b> ”, p. 1809, new attribute.....	81
280.	§18.3.1.43, “ <b>formula (Formula)</b> ”, p. 1809, new attribute .....	81
281.	§18.3.1.44, “ <b>formula1 (Formula 1)</b> ”, p. 1809, new attribute.....	81
282.	§18.3.1.45, “ <b>formula2 (Formula 2)</b> ”, p. 1810, new attribute.....	82
283.	§18.3.1.49, “ <b>iconSet (Icon Set)</b> ”, p. 1813, attribute <b>reverse</b> .....	82
284.	§18.3.1.57, “ <b>oddFooter (Odd Page Footer)</b> ”, p. 1823, new attribute .....	82

285.	<b>§18.3.1.58, “oddHeader (Odd Header)”, p. 1823, new attribute .....</b>	82
286.	<b>§18.3.1.63, “pageSetup (Page Setup Settings)”, p. 1827.....</b>	83
287.	<b>§18.3.1.63, “pageSetup (Page Setup Settings)”, p. 1830.....</b>	83
288.	<b>§18.3.1.63, “pageSetup (Page Setup Settings)”, p. 1830, attribute paperSize.....</b>	83
289.	<b>§18.3.1.64, “pageSetup (Chart Sheet Page Setup)”, p. 1832.....</b>	85
290.	<b>§18.3.1.64, “pageSetup (Chart Sheet Page Setup)”, p. 1834 .....</b>	86
291.	<b>§18.3.1.73, “row (Row)”, p. 1848, various attributes .....</b>	86
292.	<b>§18.3.1.75, “scenario (Scenario)”, p. 1854.....</b>	86
293.	<b>§18.3.1.85, “sheetProtection (Sheet Protection Options)”, p. 1870, attribute scenarios .....</b>	86
294.	<b>§18.3.1.96, “v (Cell Value)”, p. 1884, new attribute .....</b>	87
295.	<b>§18.3.2.1, “colorFilter (Color Filter Criteria)”, p. 1888, attribute cellColor .....</b>	87
296.	<b>§18.3.2.2, “customFilter (Custom Filter Criteria)”, p. 1888 .....</b>	87
297.	<b>§18.3.2.3, “customFilters (Custom Filters)”, p. 1889, attribute and .....</b>	87
298.	<b>§18.3.2.5, “dynamicFilter (Dynamic Filter)”, pp. 1891–1892, attribute various .....</b>	87
299.	<b>§18.4.12 , “t (Text)”, p. 1906, new attribute.....</b>	88
300.	<b>§18.5.1.1, “calculatedColumnFormula (Calculated Column Formula)”, p. 1909, new attribute .....</b>	88
301.	<b>§18.7.1, “author (Author)”, p. 1929, new attribute .....</b>	88
302.	<b>§18.8.1, “alignment (Alignment)”, p. 1936, attribute indent .....</b>	89
303.	<b>§18.8.29, “name (Font Name)”, p. 1965 .....</b>	89
304.	<b>§18.8.31, “numFmts (Number Formats)”, p. 1974.....</b>	89
305.	<b>§18.10.1.10, “calculatedMember (Calculated Member)”, p. 2030 .....</b>	89
306.	<b>§18.10.1.45, “item (PivotTable Field Item)”, p. 2071 .....</b>	90
307.	<b>§18.10.1.46, “items (Field Items)”, p. 2072.....</b>	90
308.	<b>§18.10.1.67, “pivotCacheDefinition (PivotCache Definiton)”, pp. 2093–2094.....</b>	90
309.	<b>§18.10.1.67, “pivotCacheDefinition (PivotCache Definiton)”, p. 2096, attribute refreshedDateIso .....</b>	90
310.	<b>§18.10.1.73, “pivotTableDefinition (PivotTable Definition)”, p. 2142, attribute printDrill.....</b>	91
311.	<b>§18.10.1.73, “pivotTableDefinition (PivotTable Definition)”, p. 2146, attribute useAutoFormatting .....</b>	91
312.	<b>§18.10.1.90, “sharedItems (Shared Items)”, p. 2167 .....</b>	91
313.	<b>§18.14.11, “oleLink (Generic Object Link Connection)”, p. 2251, attribute progId.....</b>	91
314.	<b>§18.17.2.1, “Constants”, p. 2276 .....</b>	91
315.	<b>§18.17.2.1, “Constants”, p. 2276 .....</b>	92
316.	<b>§18.17.2.1, “Constants”, p. 2277 .....</b>	92

317.	§18.17.2.3, “Cell References”, p. 2281.....	92
318.	§18.17.2.3.1, “A1-Style Cell References”, p. 2285.....	92
319.	§18.17.3, “Error values”, p. 2292.....	92
320.	§18.17.5.2, “Precision”, p. 2296 .....	93
321.	§18.17.5.4, “Interpretation”, p. 2297 .....	93
322.	§18.17.6.5, “Name Representation”, p. 2300 .....	93
323.	§18.17.7.2, “ACCRINT”, p. 2306, value 0 or omitted .....	93
324.	§18.17.7.2, “ACCRINT”, p. 2307, value 4.....	93
325.	§18.17.7.28, “BETAINV”, p. 2333.....	94
326.	§18.17.7.37, “CHIINV”, p. 2347.....	94
327.	§18.17.7.49, “CORREL”, p. 2360 .....	94
328.	§18.17.7.63, “COVAR”, p. 2382 .....	94
329.	§18.17.7.66, “CUBEMEMBER”, p. 2385, name member-expression.....	94
330.	§18.17.7.74, “DATE”, p. 2393, name year.....	95
331.	§18.17.7.76, “DATEVALUE”, pp. 2396–2397 .....	95
332.	§18.17.7.76, “DATEVALUE”, p. 2397, name date-time-string.....	95
333.	§18.17.7.89, “DEVSQ”, p. 2410.....	95
334.	§18.17.7.110, “ERROR.TYPE”, p. 2429 .....	95
335.	§18.17.7.121, “FINV”, p. 2438 .....	95
336.	§18.17.7.126, “FORECAST”, p. 2442 .....	96
337.	§18.17.7.132, “GAMMAINV”, p. 2447 .....	96
338.	§18.17.7.170, “INTERCEPT”, p. 2482.....	96
339.	§18.17.7.173, “IRR”, p. 2487 .....	96
340.	§18.17.7.195, “LINEST”, p. 2500 .....	97
341.	§18.17.7.230, “NORMINV”, p. 2534 .....	97
342.	§18.17.7.232, “NORMSINV”, p. 2535.....	97
343.	§18.17.7.247, “PEARSON”, p. 2557.....	97
344.	§18.17.7.283, “RSQ”, p. 2593 .....	98
345.	§18.17.7.292, “SKEW”, p. 2600.....	98
346.	§18.17.7.294, “STDEVA”, p. 2602 .....	98
347.	§18.17.7.298, “STANDARDIZE”, p. 2605, name mean .....	98
348.	§18.17.7.298, “STANDARDIZE”, p. 2605, name standard-dev .....	98

349.	<b>§18.17.7.299, “STDEV”, p. 2605.....</b>	98
350.	<b>§18.17.7.300, “STDEVA”, p. 2606 .....</b>	98
351.	<b>§18.17.7.301, “STDEVP”, p. 2607.....</b>	99
352.	<b>§18.17.7.302, “STDEVPA”, p. 2608 .....</b>	99
353.	<b>§18.17.7.303, “STEYX”, p. 2609 .....</b>	99
354.	<b>§18.17.7.324, “TIMEVALUE”, p. 2627 .....</b>	99
355.	<b>§18.17.7.338, “VAR”, p. 2636 .....</b>	99
356.	<b>§18.17.7.339, “VARA”, p. 2637.....</b>	100
357.	<b>§18.17.7.340, “VARP”, p. 2638 .....</b>	100
358.	<b>§18.17.7.341, “VARPA”, p. 2639.....</b>	100
359.	<b>§18.17.7.356, “ZTEST”, p. 2663.....</b>	100
360.	<b>§18.18.26, “ST_DynamicFilterType (Dynamic Filter)”, p. 2682–2683, enumeration values.....</b>	100
361.	<b>§19.2.1.13, “font (Embedded Font Name)”, p. 2769.....</b>	101
362.	<b>§19.2.1.19, “modifyVerifier (Modification Verifier)”, p. 2774.....</b>	101
363.	<b>§19.3.1.21, “graphicFrame (Graphic Frame)”, p. 2829, attribute bwMode .....</b>	101
364.	<b>§19.3.2.4, “oleObj (Global Element for Embedded objects and Controls)”, p. 2859.....</b>	102
365.	<b>§19.5.9, “audio (Audio)”, p. 2882 .....</b>	102
366.	<b>§19.5.44, “from (From)”, p. 2919 .....</b>	102
367.	<b>§19.5.46, “hsl (HSL)”, p. 2921, attributes l and s.....</b>	102
368.	<b>§19.5.46, “hsl (HSL)”, p. 2921, attribute l .....</b>	103
369.	<b>§19.5.46, “hsl (HSL)”, p. 2921, attribute s.....</b>	103
370.	<b>§19.5.62, “rCtr (Rotation Center)”, p. 2935 .....</b>	103
371.	<b>§19.5.63, “rgb (RGB)”, pp. 2936–2937, attributes b, g, and r .....</b>	103
372.	<b>§19.5.63, “rgb (RGB)”, p. 2936, attribute b.....</b>	104
373.	<b>§19.5.63, “rgb (RGB)”, p. 2937, attribute g .....</b>	104
374.	<b>§19.5.63, “rgb (RGB)”, p. 2937, attribute r .....</b>	104
375.	<b>§19.5.68, “snd (Sound)”, p. 2941 .....</b>	104
376.	<b>§19.5.68, “snd (Sound)”, p. 2942, attribute embed .....</b>	104
377.	<b>§19.5.69, “sndAc (Sound Action)”, p. 2942 .....</b>	104
378.	<b>§19.5.70, “sndTgt (Sound Target)”, p. 2943, attribute embed .....</b>	105
379.	<b>§19.5.76, “stSnd (Start Sound Action)”, p. 2949 .....</b>	105
380.	<b>§19.5.79, “tav (Time Animate Value)”, p. 2952 .....</b>	105

381.	§19.5.79, “tav (Time Animate Value)”, p. 2955, attribute fmla.....	105
382.	§19.5.80, “tavLst (Time Animated Value List)”, p. 2956.....	105
383.	§19.5.83, “tmPct (Time Percentage)”, p. 2958.....	106
384.	§19.5.88, “to (To)”, p. 2962 .....	106
385.	§19.5.88, “to (To)”, p. 2962 .....	106
386.	§19.5.90, “to (To)”, p. 2964 .....	107
387.	§19.5.92, “tavLst val (Value)”, p. 2965–2966 .....	107
388.	§19.7.53, “ST_TransitionSideDirectionType (Transition Slide Direction Type)”, p. 3004, enumeration value r ....	107
389.	§20.1.2.2.32, “snd (Hyperlink Sound)”, p. 3044, attribute embed .....	107
390.	§20.1.2.3.3, “alphaOff (Alpha Offset)”, p. 3053, attribute val.....	107
391.	§20.1.2.3.5, “blueMod (Blue Modification Modulation)”, p. 3055, attribute val .....	108
392.	§20.1.2.3.6, “blueOff (Blue Offset)”, pp. 3055–3056, attribute val .....	108
393.	§20.1.2.3.10, “green (Green)”, p. 3057, attribute val .....	109
394.	§20.1.2.3.11, “greenMod (Green Modification Modulation)”, p. 3058, attribute val.....	109
395.	§20.1.2.3.12, “greenOff (Green Offset)”, p. 3059, attribute val .....	109
396.	§20.1.2.3.19, “lum (Luminance)”, p. 3065, attribute val .....	110
397.	§20.1.2.3.20, “lumMod (Luminance Modulation)”, p. 3065, attribute val .....	110
398.	§20.1.2.3.21, “lumOff (Luminance Offset)”, p. 3066, attribute val .....	111
399.	§20.1.2.3.23, “red (Red)”, p. 3068, attribute val.....	111
400.	§20.1.2.3.24, “redMod (Red Modulation)”, p. 3069, attribute val .....	112
401.	§20.1.2.3.25, “redOff (Red Offset)”, p. 3070, attribute val .....	112
402.	§20.1.2.3.26, “sat (Saturation)”, p. 3071, attribute val .....	113
403.	§20.1.2.3.27, “satMod (Saturation Modulation)”, pp. 3071–3072, attribute val .....	113
404.	§20.1.2.3.28, “satOff (Saturation Offset)”, p. 3072, attribute val .....	114
405.	§20.1.2.3.31, “shade (Shade)”, pp. 3076–3077, attribute val.....	114
406.	§20.1.2.3.34, “tint (Tint)”, p. 3081, attribute val .....	115
407.	§20.1.3.7, “wavAudioFile (Audio from WAV File)”, p. 3089, attribute embed .....	115
408.	§20.1.5.5, “camera (Camera)”, p. 3153.....	115
409.	§20.1.10.46, “ST_PositivePercentage (Positive Percentage Value with Sign)”, p. 3300.....	116
410.	§20.4.2.3, “anchor (Anchor for Floating DrawingML Object)”, p. 3462–3467 .....	116
411.	§21.1.2.2.2, “defPPr (Default Paragraph Style)”, p. 3569–3570, attribute rtl.....	116
412.	§21.1.2.2.7, “pPr (Text Paragraph Properties)”, p. 3587–3570, attribute rtl .....	117

413.	<b>§21.1.2.3.1, “cs (Complex Script Font)”, pp. 3598–3599 .....</b>	117
414.	<b>§21.1.2.3.3, “ea (East Asian Font)”, pp. 3606–3607 .....</b>	117
415.	<b>§21.1.2.3.7, “latin (Latin Font)”, pp. 3614–3615 .....</b>	118
416.	<b>§21.1.2.3.10, “sym (Symbol Font)”, pp. 3623–3624.....</b>	118
417.	<b>§21.1.2.4.6, “buFont (Specified)”, p. 3638–3639 .....</b>	119
418.	<b>§21.1.2.4.9, “buSzPct (Bullet Size Percentage)”, pp. 3640–3641.....</b>	119
419.	<b>§21.1.2.4.13, “lvl1pPr (List Level 1 Text Style)”, p. 3651–3652, attribute rtl .....</b>	120
420.	<b>§21.1.2.4.14, “lvl2pPr (List Level 2 Text Style)”, p. 3660–3661, attribute rtl .....</b>	120
421.	<b>§21.1.2.4.15, “lvl3pPr (List Level 3 Text Style)”, p. 3669, attribute rtl.....</b>	120
422.	<b>§21.1.2.4.16, “lvl4pPr (List Level 4 Text Style)”, p. 3677–3678, attribute rtl .....</b>	120
423.	<b>§21.1.2.4.17, “lvl5pPr (List Level 5 Text Style)”, p. 3686, attribute rtl.....</b>	121
424.	<b>§21.1.2.4.18, “lvl6pPr (List Level 6 Text Style)”, p. 3694–3695, attribute rtl .....</b>	121
425.	<b>§21.1.2.4.19, “lvl7pPr (List Level 7 Text Style)”, p. 3703, attribute rtl.....</b>	121
426.	<b>§21.1.2.4.20, “lvl8pPr (List Level 8 Text Style)”, p. 3711–3712, attribute rtl .....</b>	121
427.	<b>§21.1.2.4.21, “lvl9pPr (List Level 9 Text Style)”, p. 3720, attribute rtl.....</b>	121
428.	<b>§21.2.2.12, “backward (Backward)”, p. 3763.....</b>	122
429.	<b>§21.2.2.59, “evenFooter (Even Footer)”, p. 3789, new attribute .....</b>	122
430.	<b>§21.2.2.60, “evenHeader (Even Header)”, p. 3789, new attribute .....</b>	122
431.	<b>§21.2.2.63, “externalData (External Data Relationship)”, p. 3790 .....</b>	122
432.	<b>§21.2.2.66, “firstFooter (First Footer)”, p. 3792, new attribute .....</b>	123
433.	<b>§21.2.2.67, “firstHeader (First Header)”, p. 3792, new attribute .....</b>	123
434.	<b>§21.2.2.73, “forward (Forward)”, p. 3795.....</b>	123
435.	<b>§21.2.2.124, “oddFooter (Odd Footer)”, p. 3818, new attribute.....</b>	124
436.	<b>§21.2.2.125, “oddHeader (Odd Header)”, p. 3818, new attribute .....</b>	124
437.	<b>§21.2.2.134, “pageSetup (Page Setup)”, p. 3822 .....</b>	124
438.	<b>§21.2.2.134, “pageSetup (Page Setup)”, p. 3823, attribute paperSize .....</b>	124
439.	<b>§21.2.2.134, “pageSetup (Page Setup)”, p. 3825 .....</b>	124
440.	<b>§21.2.2.220, “userShapes (User Shapes)”, p. 3867 .....</b>	125
441.	<b>§21.2.3.18, “ST_HoleSize (Hole Size)”, p. 3884 .....</b>	125
442.	<b>§21.2.3.33, “ST_Period (Period)”, p. 3892 .....</b>	125
443.	<b>§21.2.3.33, “ST_Period (Period)”, p. 3892, enumeration value auto .....</b>	125
444.	<b>§21.2.3.34, “ST_Perspective (Perspective)”, p. 3892 .....</b>	125

445.	§21.2.3.44, “ST_Skip (Skip)”, p. 3897 .....	126
446.	§22.1.2.3, “aln (Alignment)”, p. 4074 .....	126
447.	§22.1.2.5, “argPr (Argument Properties)”, p. 4078 .....	126
448.	§22.1.2.18, “cGp (Matrix Column Gap)”, p. 4094 .....	126
449.	§22.1.2.19, “cGpRule (Matrix Column Gap Rule)”, p. 4095 and many others .....	126
450.	§22.1.2.22, “cSp (Minimum Matrix Column Width)”, p. 4099 .....	126
451.	§22.1.2.22, “cSp (Minimum Matrix Column Width)”, p. 4100 .....	126
452.	§22.1.2.26, “deg (Degree)”, pp. 4104–4107 .....	127
453.	§22.1.2.28, “den (Denominator)”, pp. 4108–4110 .....	127
454.	§22.1.2.32, “e (Element (Argument))”, p. 4114 .....	127
455.	§22.1.2.32, “e (Element)”, pp. 4115–4117 .....	127
456.	§22.1.2.37, “fName (Function Name)”, p. 4122 .....	127
457.	§22.1.2.37, “fName (Function Name)”, pp. 4123–4125 .....	128
458.	§22.1.2.39, “func (Function Apply Object)”, p. 4126 .....	128
459.	§22.1.2.52, “lim (Limit)”, pp. 4138–4139 .....	128
460.	§22.1.2.75, “num (Numerator)”, pp. 4171–4172 .....	128
461.	§22.1.2.77, “oMath (Office Math)”, pp. 4174–4176 .....	129
462.	§22.1.2.83, “plcHide (Hide Placeholders (Matrix))”, p. 4181 .....	129
463.	§22.1.2.95, “sepChr (Delimiter Separator Character)”, p. 4193 .....	129
464.	§22.1.2.105, “sSup (Superscript Object)”, p. 4202 .....	129
465.	§22.1.2.112, “sub (Subscript (Pre-Sub-Superscript))”, pp. 4209–4210 .....	129
466.	§22.1.2.114, “sup (Superscript (Superscript object))”, pp. 4212–4213 .....	130
467.	§22.5.2.2, “schemaRef (Associated XML Schema)”, p. 4262, attribute uri .....	130
468.	§22.6.2.5, “Author (Author)”, p. 4269, new attribute .....	130
469.	§22.9.2.1, “ST_CalendarType (Calendar Types)”, p. 4319, attribute hebrew .....	131
470.	§22.9.2.13, “ST_String (String)”, p. 4329 .....	131
471.	§22.9.2.13, “ST_String (String)”, p. 4329 .....	131
472.	§22.9.2.15, “ST_UniversalMeasure (Universal Measurement)”, p. 4332 .....	132
473.	§A.1, “WordprocessingML”, p. 4345 .....	132
474.	§A.1, “WordprocessingML”, p. 4378, lines 1780–1786 .....	132
475.	§A.1, “WordprocessingML”, new type .....	133
476.	§A.2, “SpreadsheetML”, p. 4410 .....	134

477.	§A.2, “SpreadsheetML”, p. 4411, lines 84–88.....	134
478.	§A.2, “SpreadsheetML”, p. 4482, lines 3822–3829 .....	134
479.	§A.3, “PresentationML”, p. 3394.....	135
480.	§A.3, “PresentationML”, p. 4518, lines 1278–1286.....	135
481.	§A.4.1, “DrawingML – Main”, p. 4525 .....	135
482.	§A.4.1, “DrawingML – Main”, p. 4525, lines 17–18.....	135
483.	§A.4.1, “DrawingML - Main”, p. 4546, lines 1103–1110.....	135
484.	§A.4.2, “DrawingML – Picture”, p. 4582 .....	136
485.	§A.4.3, “DrawingML - Locked Canvas”, p. 4583 .....	136
486.	§A.4.4, “DrawingML - WordprocessingML Drawing”, p. 4583.....	136
487.	§A.4.5, “DrawingML - SpreadsheetML Drawing”, p. 4586 .....	136
488.	§A.5.1, “DrawingML – Charts”, p. 4590 .....	136
489.	§A.5.1, “DrawingML - Charts”, p. 4596, lines 309–317.....	136
490.	§A.5.1, “Drawing ML - Charts”, p. 4598, lines 424–438.....	137
491.	§A.5.1, “Drawing ML - Charts”, p. 4599, lines 493–498.....	137
492.	§A.5.1, “Drawing ML - Charts”, p. 4609, lines 1024–1028.....	137
493.	§A.5.2, “DrawingML - Chart Drawing”, p. 4617 .....	137
494.	§A.5.3, “DrawingML – Diagrams”, p. 4620.....	138
495.	§A.6.1, “Math”, p. 4641 .....	138
496.	§A.6.1, “Math”, p. 4650, lines 488–493 .....	138
497.	§A.6.2, “Extended Properties”, p. 4652 .....	138
498.	§A.6.3, “Custom Properties”, p. 4653.....	138
499.	§A.6.4, “Variant Types”, p. 4654 .....	138
500.	§A.6.5, “Custom XML Data Properties”, p. 4658.....	138
501.	§A.6.6, “Bibliography”, p. 4658 .....	139
502.	§A.6.7, “Additional Characteristics”, p. 4661.....	139
503.	§A.6.8, “Office Document Relationships”, p. 4662 .....	139
504.	§A.6.9, “Shared Simple Types”, p. 4662.....	139
505.	§A.7, “Custom XML Schema References”, p. 4665.....	139
506.	§B.1, “WordprocessingML”, p. 4667 .....	139
507.	§B.1, “WordprocessingML”, p. 4688, lines 1134–1137 .....	139
508.	§B.1, “WordprocessingML”, p. 4688, lines 1134–1137 .....	139

509.	§B.1, “WordprocessingML”, new type.....	140
510.	§B.1.1.1, “Comments Part”, p. 4708.....	140
511.	§B.1.1.2, “Document Settings Part”, p. 4708 .....	140
512.	§B.1.1.3, “Endnotes Part”, p. 4708 .....	140
513.	§B.1.1.4, “Font Table Part”, p. 4709 .....	140
514.	§B.1.1.5, “Footer Part”, p. 4709 .....	140
515.	§B.1.1.6, “Footnotes Part”, p. 4709.....	140
516.	§B.1.1.7, “Glossary Document Part”, p. 4710 .....	140
517.	§B.1.1.8, “Header Part”, p. 4710 .....	141
518.	§B.1.1.9, “Mail Merge Recipient Data Part”, p. 4710.....	141
519.	§B.1.1.10, “Main Document Part”, p. 4711.....	141
520.	§B.1.1.11, “Numbering Definitions Part”, p. 4711 .....	141
521.	§B.1.1.12, “Style Definitions Part”, p. 4711 .....	141
522.	§B.1.1.13, “Web Settings Part”, p. 4712.....	141
523.	§B.2, “SpreadsheetML”, p. 4712.....	141
524.	§B.2, “SpreadsheetML”, p. 4714, lines 78–81.....	141
525.	§B.2, “SpreadsheetML”, p. 4789, lines 4056–4060 .....	142
526.	§B.2.1.1, “Calculation Chain Part”, p. 4800.....	142
527.	§B.2.1.2, “Chartsheet Part”, p. 4800.....	142
528.	§B.2.1.3, “Comments Part”, p. 4800 .....	142
529.	§B.2.1.4, “Connections Part”, p. 4801 .....	142
530.	§B.2.1.5, “Custom XML Mappings Part”, p. 4801.....	142
531.	§B.2.1.6, “Dialogsheet Part”, p. 4801 .....	142
532.	§B.2.1.7, “Drawing Part”, p. 4801.....	143
533.	§B.2.1.8, “External Workbook References Part”, p. 4802 .....	143
534.	§B.2.1.9, “Metadata Part”, p. 4802 .....	143
535.	§B.2.1.10, “Pivot Table Part”, p. 4802 .....	143
536.	§B.2.1.11, “Pivot Table Cache Definition Part”, p. 4803.....	143
537.	§B.2.1.12, “Pivot Table Cache Records Part”, p. 4803.....	143
538.	§B.2.1.13, “Query Table Part”, p. 4803 .....	143
539.	§B.2.1.14, “Shared String Table Part”, p. 4803 .....	143
540.	§B.2.1.15, “Shared Workbook Revision Headers Part”, p. 4804.....	144

541.	§B.2.1.16, "Shared Workbook Revision Log Part", p. 4804 .....	144
542.	§B.2.1.17, "Shared Workbook User Data Part", p. 4804 .....	144
543.	§B.2.1.18, "Single Cell Table Definitions Part", p. 4804 .....	144
544.	§B.2.1.19, "Styles Part", p. 4805.....	144
545.	§B.2.1.20, "Table Definitions Part", p. 4805 .....	144
546.	§B.2.1.21, "Volatile Dependencies Part", p. 4805.....	144
547.	§B.2.1.22, "Workbook Part", p. 4806 .....	144
548.	§B.2.1.23, "Worksheet Part", p. 4806.....	145
549.	§B.3, "PresentationML", p. 4828 .....	145
550.	§B.3, "PresentationML", p. 4818, line 606.....	145
551.	§B.3, "PresentationML", pp. 4822–4823, lines 864–868 .....	145
552.	§B.3.1.1, "Comment Authors Part", p. 4828 .....	145
553.	§B.3.1.2, "Comments Part", p. 4828.....	145
554.	§B.3.1.3, "Handout Master Part", p. 4828 .....	145
555.	§B.3.1.4, "Notes Master Part", p. 4828 .....	146
556.	§B.3.1.5, "Notes Slide Part", p. 4829 .....	146
557.	§B.3.1.6, "Presentation Part", p. 4829.....	146
558.	§B.3.1.7, "Presentation Properties Part", p. 4829 .....	146
559.	§B.3.1.8, "Slide Part", p. 4829 .....	146
560.	§B.3.1.9, "Slide Layout Part", p. 4830.....	146
561.	§B.3.1.10, "Slide Master Part", p. 4830 .....	146
562.	§B.3.1.11, "Slide Synchronization Data Part", p. 4830 .....	146
563.	§B.3.1.12, "User Defined Tags Part", p. 4831.....	147
564.	§B.3.1.13, "View Properties Part", p. 4831.....	147
565.	§B.4.1, "DrawingML - Main", p. 4831 .....	147
566.	§B.4.1.1.1, "Table Styles Part", p. 4874 .....	147
567.	§B.4.1.1.2, "Theme Part", p. 4875 .....	147
568.	§B.4.1.1.3, "Theme Override Part", p. 4875 .....	147
569.	§B.4.1.1.3, "Theme Override Part", p. 4875, line 10 .....	147
570.	§B.4.2, "DrawingML - Picture", p. 4875 .....	147
571.	§B.4.3, "DrawingML - Locked Canvas", p. 4876 .....	148
572.	§B.4.4, "DrawingML - WordprocessingML Drawing", p. 4876.....	148

573.	§B.4.5, “DrawingML - SpreadsheetML Drawing”, p. 4878.....	148
574.	§B.5.1, “DrawingML - Charts”, p. 4880 .....	148
575.	§B.5.1, “Drawing ML - Charts”, p. 4884, lines 192–193.....	148
576.	§B.5.1, “Drawing ML - Charts”, pp. 4885–4886, lines 261–272 .....	148
577.	§B.5.1, “Drawing ML - Charts”, p. 4886, lines 311–312.....	148
578.	§B.5.1, “Drawing ML - Charts”, p. 4892, lines 652 .....	149
579.	§B.5.1.1.1, “Chart Part”, p. 4898 .....	149
580.	§B.5.1.1.2, “Chart Drawing Part”, p. 4898 .....	149
581.	§B.5.2, “DrawingML - Chart Drawing”, p. 4898.....	149
582.	§B.5.3, “DrawingML - Diagrams”, p. 4900 .....	149
583.	§B.5.3.1.1, “Diagram Colors Part”, p. 4915.....	149
584.	§B.5.3.1.2, “Diagram Data Part”, p. 4915 .....	149
585.	§B.5.3.1.3, “Diagram Layout Definitions Part”, p. 4915 .....	149
586.	§B.5.3.1.4, “Diagram Style Part”, p. 4915 .....	150
587.	§B.6.1, “Math”, p. 4916.....	150
588.	§B.6.1, “Math”, p. 4920, line 240 .....	150
589.	§B.6.2, “Extended Properties”, p. 4921 .....	150
590.	§B.6.2.1.1, “Extended File Properties Part”, p. 4922 .....	150
591.	§B.6.3, “Custom Properties”, p. 4922 .....	150
592.	§B.6.3.1.1, “Custom File Properties Part”, p. 4923 .....	150
593.	§B.6.4, “Variant Types”, p. 4923.....	150
594.	§B.6.5, “Custom XML Data Properties”, p. 4927.....	151
595.	§B.6.5.1.1, “Custom XML Data Properties Part”, p. 4927.....	151
596.	§B.6.6, “Bibliography”, p. 4927 .....	151
597.	§B.6.6.1.1, “Bibliography Part”, p. 4929 .....	151
598.	§B.6.7, “Additional Characteristics”, p. 4929 .....	151
599.	§B.6.7.1.1, “Additional Characteristics Part”, p. 4930.....	151
600.	§B.6.8, “Office Document Relationships”, p. 4930 .....	151
601.	§B.6.9, “Shared Simple Types”, p. 4930.....	151
602.	§B.7, “Custom XML Schema References”, p. 4932.....	152
603.	§B.8.1, “Any”, p. 4932 .....	152
604.	§B.8.2, “XML”, p. 4932 .....	152

605.	§E, “Processing Bitfields with XSLT”, pp. 4937–4939 .....	152
606.	§F, “WordprocessingML Custom XML Data Extraction”, p. 4940–4941.....	152
607.	§F, “WordprocessingML Custom XML Data Extraction”, p. 4941 .....	154
608.	§K.5.8.1, “Using Captions and Long Descriptions in WordprocessingML Tables”, pp. 5061–5062.....	154
609.	§M.1.5.9, “Vertically Merged Cells”, p. 5085 .....	155
610.	§M.1.5.9, “Vertically Merged Cells”, pp. 5086–5087 .....	155
611.	§M.1.8.2, “Style Definitions”, p. 5097 .....	155
612.	§M.1.8.3, “Paragraph Styles”, p. 5098.....	155
613.	§M.1.8.4, “Character Styles”, p. 5099.....	156
614.	§M.1.8.5, “Linked Styles”, p. 5100.....	156
615.	§M.1.8.5, “Linked Styles”, p. 5100.....	156
616.	§M.1.8.7, “Table Styles”, p. 5105 .....	156
617.	§M.1.8.7, “Table Styles”, p. 5106 .....	156
618.	§M.1.8.11, “Latent Styles”, p. 5109 .....	157
619.	§M.1.10.3, “Abstract Numbering Definitions”, p. 5116 .....	157
620.	§M.1.10.4, “Numbering Definition Instances”, p. 5118 .....	158
621.	§M.1.10.6, “The Complete Story”, p. 5122 .....	158
622.	§M.1.10.8, “Referencing Numbering Styles”, p. 5125.....	158
623.	§M.1.10.8, “Referencing Numbering Styles”, p. 5126.....	158
624.	§M.2.8.3.2.2, “Metadata Behaviors”, p. 5225 .....	159
625.	§M.2.9.3.2, “XML - pivotCacheDefinition part”, p. 5239.....	159
626.	§M.2.9.3.2, “XML - pivotCacheDefinition part”, p. 5242.....	159
627.	§M.2.9.3.4.5, “Row Items”, pp. 5251–5252 .....	159
628.	§M.2.9.3.4.7, “Column Items”, p. 5254 .....	159
629.	§M.2.12.3, “Pivot XML fragment”, p. 5269.....	160
630.	§M.4.6.2.2, “Camera”, p. 5374 .....	160
631.	§M.6.1, “Math”, p. 5507 .....	160
632.	§N.1, “WordprocessingML”, p. 5554 .....	160

## **Introduction (For WG4 use only; will be removed from the final COR)**

This Technical Corrigendum contains corrections that resolve various Defect Reports submitted against ISO/IEC 29500-1:2008.

A correction can involve changes to one or more clause or subclauses; it can even apply to multiple Parts of ISO/IEC 29500. For changes to Part 1, each such change has its own entry below, and the number of the Defect Report that lead to any particular change is written immediately following that change's title, in the form “[DR 99-9999]”. (This information is for the use of committee ISO/IEC SC 34/WG4 only, and will be removed from the final COR. However, a committee-private version containing the DR numbers will be made available for tracking purposes.)

Changes are presented in ascending clause, subclause, and page number order.

## Changes

### 1. §3, “Normative References”, p. 8

[DR 09-0031]

ISO/IEC 10646:~~2003~~, *Information technology — Universal Multiple-Octet Coded Character Set (UCS)*.

### 2. §3, “Normative References”, p. 10

[DR 09-0031]

The Unicode Consortium. *The Unicode Standard, Version 5.0, defined by The Unicode Standard, Version xx5.0 (Reading, MA, Addison-Wesley, 2006. ISBN 0-321-48091-0)*, <http://www.unicode.org/unicode/standard>.

### 3. §3, “Normative References”, p. 10

[DR 09-0169]

~~XML, Tim Bray, Eve Maler, Jean Paoli, C. M. Sperberg McQueen, John Cowan, and François Yergeau (editors). Extensible Markup Language (XML) 1.1, Third Edition. World Wide Web Consortium. 2004. <http://www.w3.org/TR/2004/REC-xml11-20040204/> XML, Tim Bray, Jean Paoli, Eve Maler, C. M. Sperberg McQueen, Eve Maler, and François Yergeau (editors). Extensible Markup Language (XML) 1.0, Fourth Edition.<sup>1</sup> World Wide Web Consortium. 2006. <http://www.w3.org/TR/2006/REC-xml-20060816/>~~

<sup>1</sup> In the future, this reference may be replaced by the 5<sup>th</sup> edition once that has received broad acceptance.

### 4. §3, “Normative References”, p. 11

[DR 09-0170]

XML Namespaces, Bray, Tim, Dave Hollander, Andrew Layman, and Richard Tobin (editors). *Namespaces in XML 1.0*. World Wide Web Consortium. 2006. <http://www.w3.org/TR/2004/REC-xml-names11-20040204/> <http://www.w3.org/TR/2006/REC-xml-names-20060816>

### 5. §4, “Terms and Definitions”, p. 12

[DR 09-0076]

[Note: This part uses OPC-related terms, which are defined in ISO/IEC 29500-2. end note]

### 6. §4, “Terms and Definitions”, p. 13

[DR 09-0267]

OLE – OLE in this context does not refer to any specific technology; instead, it refers to the generalized abstraction of embedding and linking objects within a document.

## 7. §5, “Notational Conventions”, p. 14

[DR 09-0082]

The following typographical conventions are used in ISO/IEC 29500:

- The first occurrence of a new term is written in italics,~~as in "normative"~~. [Example: The text in ISO/IEC 29500 is divided into normative and informative categories. end example]
- In each definition of a term in §4 (Terms and Definitions), the term is written in bold,~~as in "behavior"~~. [Example: behavior — External appearance or action. end example]
- The tag name of an XML element is written using an Element style,~~as in "document"~~. [Example: The bookmarkStart and bookmarkEnd elements specify ... end example]
- The name of an XML attribute is written using an Attribute style,~~as in "id"~~. [Example: The dropCap attribute specifies ... end example]
- The value of an XML attribute is written using a constant-width style,~~as in "CommentReference"~~. [Example: The attribute value of auto specifies ... end example]
- The qualified or unqualified name of a simple type, complex type, or base datatype is written using a Type style,~~as in "xsd:anyURI"~~. [Example: The possible values for this attribute are defined by the ST\_HexColor simple type. end example]

## 8. §7, “General Description”, p. 16

[DR 09-0076]

{Numbered list item 4: The numbers in “clauses 17–23” are not actual hyperlinked forward references, and should be.}

## 9. §8.1, “Packages and Parts”, p. 17

[DR 09-0076]

(Packages are discussed further in ISO/IEC 29500-2.)

## 10. §9.2, “Relationships in Office Open XML”, p. 23

[DR 09-0076]

All other relationships are implicit. [Note: ... end note].

## 11. §10.1.2, “Office Open XML Native Extensibility Constructs”, p. 28

[DR 09-0076]

See the reference material in §17–23 ...

## 12. §11.3.1, “Alternative Format Import Part”, p. 32

[DR 09-0035]

Content Type:	One of the following formats: <ul style="list-style-type: none"> <li>• Text = <del>application/</del>text/plain</li> <li>• HTML = <del>application/</del>text/html</li> <li>• WordprocessingML =              application/vnd.openxmlformats-officedocument.wordprocessingml.document</li> <li>• XHTML = application/xhtml+xml</li> </ul>
---------------	---

## 13. §11.3.11, “Numbering Definitions Part”, p. 55

[DR 09-0108]

```
<w:lvl w:ilvl="0" w:tplc="151C4798">
  ...
  <w:lvlJc w:val="startLeft"/>
  ...
</w:lvl>
```

## 14. §11.3.11, “Numbering Definitions Part”, p. 55

[DR 09-0123]

```
<w:pPr>
  <w:tabs>
    <w:tab w:val="list" w:pos="720"/>
  </w:tabs>
  <w:ind w:startLeft="720" w:hanging="360"/>
</w:pPr>
```

## 15. §11.3.11, “Numbering Definitions Part”, p. 55

[DR 09-0138]

```
<w:pPr>
  <w:tabs>
    <w:tab w:val="numList" w:pos="720"/>
  </w:tabs>
  <w:ind w:left="720" w:hanging="360"/>
</w:pPr>
```

**16. §11.3.12, “Style Definitions Part”, p. 55**

[DR 09-0190]

```
<w:styles xmlns:w="..." ... xml:space="preserve">
  ...
</w:styles>
```

**17. §11.3.12, “Style Definitions Part”, p. 56**

[DR 09-0123]

```
<w:pPr>
  <w:pStyle w:val="ListBullet"/>
  ...
  <w:ind w:startLeft="648"/>
</w:pPr>
```

**18. §11.6, “Master Documents and Subdocuments”, p. 59**

[DR 09-0190]

```
<w:document xmlns:r="..." xmlns:w="..." ...>
  ...
</w:document>
```

**19. §12.3.7, “Dialogsheet Part”, p. 76**

[DR 09-0135]

```
<sheets>
  ...
  <sheet name="Dialog1" tabId="4" type="dialog" r:id="rId2"/>
</sheets>
```

**20. §12.3.7, “Dialogsheet Part”, p. 76**

[DR 09-0124]

```
<sheets>
  ...
  <sheet name="Dialog1" tabSheetId="4" type="dialog" r:id="rId2"/>
</sheets>
```

**21. §12.3.9, “External Workbook References Part”, p. 79**

[DR 09-0124]

```
<sheets>
  <sheet name="Sheet1" tabSheetId="1" r:id="rId1"/>
  <sheet name="Sheet2" tabSheetId="2" r:id="rId2"/>
  <sheet name="Sheet3" tabSheetId="3" r:id="rId3"/>
</sheets>
```

## 22. §12.3.10, “Metadata Part”, pp. 82–83

[DR 09-0087]

```
<pivotCacheDefinition ... saveData="0" refreshedBy="..."
  refreshedDateIso="2005-11-28T16:55:44" backgroundQuery="1" createdVersion="3"
  refreshedVersion="3" recordCount="0">
  ...
</pivotCacheDefinition>
```

## 23. §12.3.12, “Pivot Table Cache Definition Part”, p. 85

[DR 09-0087]

```
<pivotCacheDefinition ... r:id="rId1" refreshedBy="John Jones"
  refreshedDateIso="2005-11-18T16:47:49" createdVersion="3"
  refreshedVersion="3" recordCount="11">
  ...
</pivotCacheDefinition>
```

## 24. §12.3.20, “Styles Part”, p. 94

[DR 09-0025]

Root Namespace:	http://schemas.openxmlformats.org/spreadsheetml/2006/main
-----------------	---

## 25. §12.3.23, “Workbook Part”, p. 98

[DR 09-0124]

```
<sheets>
  <sheet name="January" tabSheetId="1" r:id="rId1"/>
  <sheet name="February" tabSheetId="2" r:id="rId2"/>
  <sheet name="March" tabSheetId="3" r:id="rId3"/>
</sheets>
```

## 26. §12.3.24, “Worksheet Part”, p. 101

[DR 09-0024]

A Worksheet part is permitted to have implicit relationships to the following parts defined by ISO/IEC 29500:

- Comments (§12.3.3)
- Pivot Table Definitions (§12.3.11)
- Printer Settings (§15.2.15)
- [Query Table Part \(§12.3.14\)](#)
- Single Cell Table Definitions (§12.3.19)
- Table Definition (§12.3.21)

## 27. §15.2.15, “Printer Settings Part”, p. 162

[DR 09-0081]

*[Example: ... here: http://... end example]*

## 28. §17.2.1, “background (Document Background)”, p. 193, attribute color

[DR 09-0080]

Change “... *end example*]. RGB ...” to “... *end example*]. RGB ...”

## 29. §17.3.1.12, “ind (Paragraph Indentation)”, p. 226

[DR 09-0123]

```
<w:pPr>
  <w:ind w:startLeft="1440" w:endRight="1440" w:hanging="1080" />
</w:pPr>
```

## 30. §17.3.1.13, “jc (Paragraph Alignment)”, p. 231

[DR 09-0108]

```
<w:pPr>
  <w:jc w:val="endRight" />
</w:pPr>
```

## 31. §17.3.1.27, “pStyle (Referenced Paragraph Style)”, p. 253

[DR 09-0123]

*[Example: Consider the following WordprocessingML fragment:*

```
<w:pPr>
  <w:pStyle w:val="TestParagraphStyle" />
  <w:ind w:startLeft="1440" />
</w:pPr>
```

This paragraph specifies that it inherits all of the paragraph properties specified by the paragraph style with a styleId of TestParagraphStyle, which then has any indentation properties overridden with a startleft indentation of 1440 twentieths of a point, and no indentation for any other value. *end example]*

### 32. §17.3.1.27, “pStyle (Referenced Paragraph Style)”, p. 253, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

### 33. §17.3.1.30, “rPr (Previous Run Properties for the Paragraph Mark)”, p. 258

[DR 09-0090]

```
<w:lang w:val="en-CAea" />
```

### 34. §17.3.1.37, “tab (Custom Tab Stop)”, p. 269

[DR 09-0108]

```
<w:tab w:val="startleft" w:pos="2160" />
```

### 35. §17.3.1.37, “tab (Custom Tab Stop)”, p. 270, attribute pos

[DR 09-0108]

```
<w:tab w:val="startleft" w:pos="2160" />
```

### 36. §17.3.1.37, “tab (Custom Tab Stop)”, p. 270, attribute val

[DR 09-0108]

```
<w:tab w:val="startleft" w:pos="2160" />
```

### 37. §17.3.1.38, “tabs (Set of Custom Tab Stops)”, p. 271

[DR 09-0108]

```
<w:pPr>
  <w:tabs>
    <w:tab w:val="startLeft" w:pos="2160" />
    <w:tab w:val="startLeft" w:pos="5040" />
  </w:tabs>
</w:pPr>
```

### 38. §17.3.1.39, “textAlignment (Vertical Character Alignment on Line)”, p. 272, attribute val

[DR 09-0119]

```
<w:pPr>
  <w:textAlignment w:val="baseLine" />
</w:pPr>
```

### 39. §17.3.1.40, “textboxTightWrap (Allow Surrounding Paragraphs to Tight Wrap to Text Box Contents)”, p. 273

[DR 09-0110]

```
<w:pPr>
  <w:textboxTightWrap w:val="allLines" />
</w:pPr>
```

### 40. §17.3.1.41, “textDirection (Paragraph Text Flow Direction)”, p. 275

[DR 09-0111]

*[Example:* Consider a document with a paragraph in which text must be oriented vertically, flowing from left to right horizontally on the page. ~~should flow bottom to top vertically, and left to right horizontally.~~ This setting would be specified with the following WordprocessingML:

```
<w:pPr>
  <w:textDirection w:val="ltrbtLr" />
</w:pPr>
```

The textDirection element specifies via the ltrbtLr value in the val attribute that the text flow must be oriented vertically, with subsequent lines stacked from left to right. ~~should go bottom to top, and left to right.~~ *[end example]*

### 41. §17.3.1.41, “textDirection (Paragraph Text Flow Direction)”, p. 275, attribute val

[DR 09-0111]

[Example: Consider a document with a section in which text must be oriented vertically, flowing from left to right horizontally on the page.~~should flow bottom to top vertically, and left to right horizontally.~~ This setting requires the following WordprocessingML:

```
<w:sectPr>
  ...
  <w:textDirection w:val="1rbtLr" />
</w:sectPr>
```

The textDirection element specifies via the 1rbtLr value in the val attribute that the text flow must be oriented vertically, with subsequent lines stacked from left to right.~~should go bottom to top, and left to right.~~ *end example]*

## 42. §17.3.2.5, “caps (Display All Characters As Capital Letters)”, p. 285

[DR 09-0084]

[Example: Consider the words Hello, World, which must be displayed in all capital letters in a document. This constraint is specified as follows in the WordprocessingML:

```
<w:r>
  <w:rPr>
    <w:caps w:val="true" />
  </w:rPr>
  <w:t>Hello, World</w:t>
</w:r>
```

This run displays as HELLO, WORLD, even though the lowercase characters are used in the run contents due to the use of the caps element. If this property is removed, the original character forms is displayed (they are not lost). *end example]*

## 43. §17.3.2.26, “rFonts (Run Fonts)”, p. 317, attribute cs

[DR 09-0125]

If the csTtheme attribute is also specified, then this attribute shall be ignored and that value shall be used instead.

## 44. §17.3.2.26, “rFonts (Run Fonts)”, p. 318, attribute cstheme

[DR 09-0125]

[Example: Consider a run of Arabic text that~~which~~ must be displayed using the majorBidi theme font. This requirement would be specified as follows in the resulting WordprocessingML:

```
<w:rPr>
  <w:rFonts w:csTtheme="majorBidi" />
```

</w:rPr>

The `csT` attribute specifies that the run must use the `majorBidi` theme font as defined in the document's themes part for all text in a complex script range. *end example]*

## 45. §17.3.2.27, “rPr (Previous Run Properties)”, p. 321

[DR 09-0090]

<w:lang w:val="en-CAea" />

## 46. §17.3.2.28, “rPr (Run Properties)”, p. 323

[DR 09-0090]

<w:lang w:val="en-CAea" />

## 47. §17.3.2.29, “rStyle (Referenced Character Style)”, p. 326, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p><i>[Example:</i> Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 48. §17.3.2.33, “smallCaps (Small Caps)”, p. 330

[DR 09-0084]

*[Example:* Consider the words Hello, World, which must be displayed in small capital letters in a document. This constraint is specified as follows in the WordprocessingML:

```
<w:r>
  <w:rPr>
    <w:smallCaps w:val="true" />
    <w:sz w:val="24" />
  </w:rPr>
  <w:t>Hello, World</w:t>
</w:r>
```

*... end example]*

## 49. §17.3.3.18, “noBreakHyphen (Non Breaking Hyphen Character)”, pp. 363–364

[DR 09-0114]

This element specifies that a non-breaking hyphen character shall be placed at the current location in the run content. ~~A non-breaking hyphen is the equivalent of Unicode character 002D (the hyphen-minus); however, it shall not be used as a line breaking character for the current line of text when displaying this WordprocessingML content.~~

The behavior of a non-breaking hyphen in run content shall be to display using the same glyph as the hyphen-minus character ([U+002D](#)), however, without [that hyphen](#) being a line breaking position (unlike the hyphen-minus character, which does allow line breaking).

[Example: Consider the following sentence in a WordprocessingML document: ‘Each citizen has a unique Social Security Number of the form “999-99-9999”, where each 9 represents a decimal digit.’ The fragment of this sentence involving the string literal might be represented in WordprocessingML, as follows:

```
<w:r>
  <w:t>Number of the form “999-99-9999”, where</w:t>
</w:r>
```

However, consider the case in which, on rendering, the right margin was such that the quoted string is broken across multiple lines with the hyphens being used as possible line breaking points; for example:

Each citizen has a unique Social Security Number of the form “999-99-9999”, where ...

If such line breaks are undesirable, those hyphens can be marked as non-breaking, as follows:

```
<w:r>
  <w:t>Number of the form “999</w:t>
</w:r>
<w:r>
  <w:noBreakHyphen />
  <w:t>99</w:t>
</w:r>
<w:r>
  <w:noBreakHyphen />
  <w:t>9999”, where</w:t>
</w:r>
```

in which case, for the same margin settings, the rendered result might be like the following:

Each citizen has a unique Social Security Number of the form “999-99-9999”, where ...

end example]

[~~Example: Consider the following sentence in a WordprocessingML document:~~

~~This makes a very very very wordy and deliberately overcomplicated sentence.~~

~~Normally, just as shown above, this sentence not would be displayed on a single line as it is long enough to require line breaking (given the width of the current page). However, if a hyphen minus were inserted after the letter s in sentence, as follows:~~

```
<w:r>
  <w:t>This makes a very very very wordy and deliberately overcomplicated s-
  entence.</w:t>
</w:r>
```

~~This would allow a break at that position, and break the word after that character:~~

~~This makes a very very very wordy and deliberately overcomplicated s-entence.~~

~~If this was not desired, the non breaking hyphen character could be specified as follows:~~

```
<w:r>
  <w:t>This makes a very very very wordy and deliberately overcomplicated
  s</w:t>
  <w:nonBreakHyphen/>
  <w:t>entence.</w:t>
</w:r>
```

~~This would display a hyphen character, but would not allow the text to break at that location:~~

~~This makes a very very very wordy and deliberately overcomplicated s-entence.~~

end example]

## 50. §17.3.3.20, “objectEmbed (Embedded Object Properties)”, p. 366, attribute fieldCodes

[DR 09-0175]

<u>Attributes</u>	<u>Description</u>
-------------------	--------------------

<u>Attributes</u>	<u>Description</u>
fieldCodes (Field Switches)	<p>This element specifies the WordprocessingML field switches which shall be stored with an embedded object, using the set of field switches defined by the LINK field, as specified in §17.16.<a href="#">5.32</a>. This element shall specify the exact field switches for the field which represents the object.</p> <p>...</p> <p>[Example:</p> <pre>&lt;w:objectEmbed ... fieldCodes="\f 0"/&gt;</pre> <p>This embedded object specifies additional LINK field code values of \f 0, which specifies that the embedded object must retain its source formatting (as defined in §17.16.<a href="#">5.32</a>).</p> <p><i>end example</i>]</p> <p>...</p>

## 51. §17.3.3.21, “objectLink (Linked Object Properties)”, p. 368, attribute fieldCodes

[DR 09-0175]

<u>Attributes</u>	<u>Description</u>
fieldCodes (Field Switches)	<p>This element specifies the WordprocessingML field switches which shall be stored with an embedded object, using the set of field switches defined by the LINK field, as specified in §17.16.<a href="#">5.32</a>. This element shall specify the exact field switches for the field which represents the object.</p> <p>...</p> <p>[Example:</p> <pre>&lt;w:objectEmbed ... fieldCodes="\f 0"/&gt;</pre> <p>This embedded object specifies additional LINK field code values of \f 0, which specifies that the embedded object must retain its source formatting (as defined in §17.16.<a href="#">5.32</a>).</p> <p><i>end example</i>]</p> <p>...</p>

## 52. §17.3.3.23, “ptab (Absolute Position Tab Character)”, p. 371

[DR 09-0108]

```
<w:pPr>
  <w:tabs>
    <w:tab w:val="startLeft" w:pos="2160" />
    <w:tab w:val="startLeft" w:pos="5040" />
  </w:tabs>
```

</w:pPr>

### 53. §17.3.3.32, “tab (Tab Character)”, p. 383

[DR 09-0108]

```
<w:pPr>
  <w:tabs>
    <w:tab w:val="startLeft" w:pos="2160" />
    <w:tab w:val="startLeft" w:pos="5040" />
  </w:tabs>
</w:pPr>
```

### 54. §17.3.4, “Border Properties (CT\_Border)”, p. 388, attribute themeShade

[DR 09-0080]

Change “... instance. If the ...” to “... instance. If the ...”

### 55. §17.4, “Tables”, p. 399

[DR 09-0122]

```
<w:tblBorders>
  ...
  <w:startLeft w:val="single" w:sz="4" w:space="0" w:color="auto"/>
  ...
  <w:endRight w:val="single" w:sz="4" w:space="0" w:color="auto"/>
</w:tblBorders>
```

### 56. §17.4.18, “header (Header Cell Reference)”, p. 431, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p><i>[Example:</i> Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 57. §17.4.22, “hMerge (Horizontally Merged Cell)”, p. 436

[DR 09-0115]

```
<w:tc>
  <w:tcPr>
    <w:hMerge w:val="restart"/>
  </w:tcPr>
  ...
</w:tc>
<w:tc>
  <w:tcPr>
    <w:hMerge/>
  </w:tcPr>
  ...
</w:tc>
...

```

The hMerge element defines the cells thatwhich are horizontally merged, and how each group is merged together. *end example*

## 58. §17.4.22, “hMerge (Horizontally Merged Cell)”, p. 436, attribute val

[DR 09-0115]

```
<w:tcPr>
  <w:hMerge w:val="restart"/>
</w:tcPr>
```

## 59. §17.4.27, “jc (Table Alignment Exception)”, p. 441

[DR 09-0108]

```
<w:tblPrEx>
  <w:jc w:val="startleft"/>
</w:tblPrEx>
```

## 60. §17.4.28, “jc (Table Row Alignment)”, p. 442

[DR 09-0108]

```
<w:trPr>
  <w:jc w:val="startleft"/>
</w:trPr>
```

**61. §17.4.29, “jc (Table Alignment)”, p. 443**

[DR 09-0108]

```
<w:tblPr>
  <w:jc w:val="endright" />
</w:tblPr>
```

**62. §17.4.31, “shd (Table Shading Exception)”, p. 446**

[DR 09-0108]

```
<w:tblPrEx>
  <w:jc w:val="startleft" />
  <w:shd w:val="clear" w:color="auto" w:fill="EEECE1" w:themeFill="background2"
    />
</w:tblPrEx>
```

**63. §17.4.38, “tbl (Table)”, p. 453**

[DR 09-0122]

```
<w:tblBorders>
  ...
  <w:startleft w:val="single" w:sz="4" w:space="0" w:color="auto"/>
  ...
  <w:endright w:val="single" w:sz="4" w:space="0" w:color="auto"/>
</w:tblBorders>
```

**64. §17.4.39, “tblBorders (Table Borders)”, p. 455**

[DR 09-0122]

```
<w:tblBorders>
  ...
  <w:startleft w:val="single" w:sz="4" w:space="0" w:color="000000"
    w:themeColor="text1"/>
  ...
  <w:endright w:val="single" w:sz="4" w:space="0" w:color="000000"
    w:themeColor="text1"/>
  ...
<w:tblBorders>
```

**65. §17.4.40, “tblBorders (Table Borders Exceptions)”, p. 457**

[DR 09-0122]

```

<w:tblBorders>
...
<w:startLeft w:val="single" w:sz="24" w:space="0" w:color="000000"
  w:themeColor="text1"/>
...
<w:endRight w:val="single" w:sz="24" w:space="0" w:color="000000"
  w:themeColor="text1"/>
...
</w:tblBorders>

```

## 66. §17.4.41, “tblCaption (Table Caption)”, p. 458, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre> &lt;w:pPr&gt;   &lt;w:pStyle w:val="<u>Heading1</u><del>heading1</del>" /&gt; &lt;/w:pPr&gt; ... </pre>

## 67. §17.4.42, “tblCellMar (Table Cell Margin Exceptions)”, p. 459

[DR 09-0122]

```

<w:tblCellMar>
...
<w:startLeft w:w="144" w:type="dxa"/>
...
<w:endRight w:w="144" w:type="dxa"/>
</w:tblCellMar>

```

## 68. §17.4.43, “tblCellMar (Table Cell Margin Defaults)”, p. 460

[DR 09-0122]

```

<w:tblCellMar>
...
<w:startLeft w:w="144" w:type="dxa"/>
...
<w:endRight w:w="144" w:type="dxa"/>
</w:tblCellMar>

```

## 69. §17.4.47, “tblDescription (Table Description)”, p. 465, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 70. §17.4.51, “tblInd (Table Indent from Leading Margin)”, p. 469

[DR 09-0108]

```
<w:tblPr>
  <w:jc w:val="startleft"/>
  <w:tblInd w:w="1440" w:type="dxa"/>
</w:tblPr>
```

...

```
<w:tblPr>
  <w:jc w:val="endright"/>
  <w:tblInd w:w="1440" w:type="dxa"/>
</w:tblPr>
```

## 71. §17.4.59, “tblPr (Previous Table Properties)”, p. 483

[DR 08-0010]

```
<w:tblPr>
  ...
  <w:tblLook w:val="04A0" w:firstRow="true" w:firstColumn="true"
    w:noVBand="true" />
  <w:tblPrChange w:id="0" ... >
    <w:tblPr>
      ...
      <w:tblLook w:val="04A0" w:firstRow="true" w:firstColumn="true"
        w:noVBand="true" />
    </w:tblPr>
  </w:tblPrChange>
```

</w:tblPr>

## 72. §17.4.60, “tblPr (Table Properties)”, p. 485

[DR 09-0122]

```
<w:tblBorders>
...
<w:startLeft w:val="single" w:sz="4" w:space="0" w:color="auto"/>
...
<w:endRight w:val="single" w:sz="4" w:space="0" w:color="auto"/>
...
</w:tblBorders>
```

## 73. §17.4.61, “tblPrEx (Table-Level Property Exceptions)”, p. 487

[DR 09-0122]

```
<w:tblBorders>
...
<w:startLeft w:val="thinThickThinMediumGap" w:sz="24" w:space="0"
  w:color="auto"/>
...
<w:endRight w:val="thinThickThinMediumGap" w:sz="24" w:space="0"
  w:color="auto"/>
...
</w:tblBorders>
```

## 74. §17.4.62, “tblPrEx (Previous Table-Level Property Exceptions)”, p. 489

[DR 09-0122]

```
<w:tr>
  <w:tblPrEx>
    <w:tblBorders>
      ...
      <w:startLeft w:val="thinThickThinMediumGap" w:sz="24" w:space="0"
        w:color="auto"/>
      ...
      <w:endRight w:val="thinThickThinMediumGap" w:sz="24" w:space="0"
        w:color="auto"/>
      ...
    </w:tblBorders>
    <w:tblPrExChange w:id="9" ... >
      <w:tblPrEx>
```

```

<w:tblBorders>
  ...
  <w:startLeft w:val="thinThickThinSmallGap" w:sz="24" w:space="0"
    w:color="FF0000"/>
  ...
  <w:endRight w:val="thinThickThinSmallGap" w:sz="24" w:space="0"
    w:color="FF0000"/>
  ...
</w:tblBorders>
...
</w:tr>

```

## 75. §17.4.63, “tblStyle (Referenced Table Style)”, p. 491, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p><i>[Example:</i> Consider the following WordprocessingML fragment:</p> <pre> &lt;w:pPr&gt;   &lt;w:pStyle w:val="<u>Heading1</u><u>heading1</u>" /&gt; &lt;/w:pPr&gt; ... </pre>

## 76. §17.4.65, “tblW (Preferred Table Width Exception)”, p. 493

[DR 09-0139]

```

<w:tblPrEx>
  <w:tblW w:type="autofixed" w:w="1440"/>
</w:tblPrEx>

```

## 77. §17.4.66, “tc (Table Cell)”, pp. 494–495

[DR 09-0084]

*[Example:* Consider a table consisting of a single table cell, which contains the text Hello, World:

Hello, <u>W</u> orld
----------------------

This table cell's content is represented by the following WordprocessingML:

```

<w:tc>
  <w:tcPr>
    <w:tcW w:w="0" w:type="auto"/>
  </w:tcPr>
  <w:p>
    <w:r>
      <w:t>Hello, World</w:t>
    </w:r>
  </w:p>
</w:tc>

```

... end example]

## 78. §17.4.67, “tcBorders (Table Cell Borders)”, p. 499

[DR 09-0122]

```

<w:tcPr>
  <w:tcBorders>
    ...
    <w:startLeft w:val="double" w:sz="24" w:space="0" w:color="FF0000"/>
    ...
    <w:endRight w:val="double" w:sz="24" w:space="0" w:color="FF0000"/>
  </w:tcBorders>
</w:tcPr>

```

## 79. §17.4.69, “tcMar (Single Table Cell Margins)”, p. 501

[DR 09-0122]

```

<w:tcMar>
  <w:top w:w="720" w:type="dxa"/>
  <w:startLeft w:w="720" w:type="dxa"/>
  <w:bottom w:w="720" w:type="dxa"/>
  <w:endRight w:w="720" w:type="dxa"/>
</w:tcMar>

```

## 80. §17.4.70, “tcPr (Table Cell Properties)”, p. 502

[DR 09-0122]

```

<w:tbl>
  <w:tblPr>
    <w:tblCellMar>
      <w:startLeft w:w="0" w:type="dxa"/>
    </w:tblCellMar>

```

```

</w:tblPr>
...
<w:tr>
  <w:tc>
    <w:tcPr>
      <w:tcMar>
        <w:startLeft w:w="720" w:type="dxa"/>
      </w:tcMar>
    </w:tcPr>
    ...
  </w:tc>
</w:tr>
</w:tbl>

```

## 81. §17.4.73, “textDirection (Table Cell Text Flow Direction)”, p. 507

[DR 09-0111]

*[Example:* Consider a table with one cell in which all the table cell's text flow is oriented vertically, flowing from right to left horizontally within that celltop to bottom—right to left:

	Text in	this	table	cell
--	---------	------	-------	------

This table cell would specify this text flow using the following WordprocessingML:

```

<w:tc>
  <w:tcPr>
    ...
    <w:textDirection w:val="r1tbR1" />
  </w:tcPr>
  ...
</w:tc>

```

The textDirection element specifies via the r1tbR1 value in the val attribute that the text flow is to be oriented vertically, with subsequent lines stacked from right to left, should go top to bottom, then right to left. end example

## 82. §17.4.73, “textDirection (Table Cell Text Flow Direction)”, p. 508, attribute val

[DR 09-0111]

[*Example:* Consider a document with a section in which text must be oriented vertically, flowing from left to right horizontally on the page.~~should flow bottom to top vertically, and left to right horizontally.~~ This setting requires the following WordprocessingML:

```
<w:sectPr>
  ...
  <w:textDirection w:val="lrbtr" />
</w:sectPr>
```

The textDirection element specifies via the `lrbtr` value in the val attribute that the text flow must be oriented vertically, with subsequent lines stacked from left to right.~~go bottom to top, and left to right.~~ *end example]*

### 83. §17.4.79, “tr (Table Row)”, pp. 512–513

[DR 09-0084]

[*Example:* Consider a table consisting of a single table cell, which contains the text Hello, World:

Hello World
-------------

This table row's content is represented by the following WordprocessingML:

```
<w:tr>
  <w:tc>
    <w:tcPr>
      <w:tcW w:w="0" w:type="auto"/>
    </w:tcPr>
    <w:p>
      <w:r>
        <w:t>Hello, World</w:t>
      </w:r>
    </w:p>
  </w:tc>
</w:tr>
```

*... end example]*

### 84. §17.4.85, “vMerge (Vertically Merged Cell)”, pp. 523–524

[DR 09-0115]

```
<w:tc>
  <w:tcPr>
    <w:vMerge w:val="restart"/>
  </w:tcPr>
```

```

...
</w:tc>
...
<w:tc>
  <w:tcPr>
    <w:vMerge w:val="continue"/>
  </w:tcPr>
  ...
</w:tc>
...
<w:tc>
  <w:tcPr>
    <w:vMerge w:val="continue"/>
  </w:tcPr>
  ...
</w:tc>
...

```

The vMerge element defines the cells thatwhich are vertically merged, and how each cell is merged together.  
*[Example: ... end example]*

## 85. §17.4.85, “vMerge (Vertically Merged Cell)”, pp. 523–524, attribute val

[DR 09-0115]

```

<w:tcPr>
  <w:vMerge w:val="restart"/>
</w:tcPr>

```

## 86. §17.4.88, “Table Measurement (CT\_TblWidth)”, p. 527

[DR 09-0247]

Attributes	Description
type (Table Width Type)	<p>...</p> <p><i>[Example: ... end example]</i></p> <p>If the value of the type attribute and the actual measurement specified by the w attribute are contradictory, the type specified by the type attribute shall be ignored.</p> <p>The possible values for this attribute are defined by the ST_TblWidth simple type (§xx).</p>

## 87. §17.5, “Custom Markup”, p. 528

[DR 09-0205]

For these scenarios, multiple facilities are provided for the ~~insertion and round-tripping~~inclusion of customer-defined semantics within a WordprocessingML document.

## 88. §17.5.1, “Custom XML and Smart Tags”, p. 529

[DR 09-0214]

The next ~~form~~example of customer-defined semantics ~~that~~which can be embedded in a WordprocessingML document is custom XML markup.

## 89. §17.5.1, “Custom XML and Smart Tags”, p. 529

[DR 09-0215]

Custom XML markup allows the application of the XML elements defined in any schema syntax (XML Schema, NVDL, etc.) to be applied to the contents of a WordprocessingML document in ~~one of~~two types of locations:

## 90. §17.5.1, “Custom XML and Smart Tags”, p. 530

[DR 09-0217]

~~Similar to the smart tag example above, a~~A custom XML element in a document has two required attributes:

### 91. §17.5.1.1, “attr (Custom XML Attribute)”, p. 531

[DR 09-0218]

The attributes on this element shall be used to specify ~~the contents~~the Namespace URI, name, and content of the custom XML attribute.

### 92. §17.5.1.1, “attr (Custom XML Attribute)”, p. 531

[DR 09-0220]

This ~~property bag~~set of custom XML properties specifies that the parent custom XML element must have two attributes associated with it, the first with a name of companyName, and the second with a name of companySymbol. *end example*

### 93. §17.5.1.3, “customXml, Inline-Level Custom XML Element”, p. 534

[DR 09-0011]

<b>Parent Elements</b>
------------------------

Parent Elements
bdo (\$xx); customXml (\$xx); <a href="#">deg (\$22.1.2.26)</a> ; del (\$xx); <a href="#">den (\$22.1.2.28)</a> ; dir (\$xx); <a href="#">e (\$22.1.2.32)</a> ; fldSimple (\$xx); <a href="#">fName (\$22.1.2.37)</a> ; hyperlink (\$xx); ins (\$xx); <a href="#">lim (\$22.1.2.52)</a> ; moveFrom (\$xx); moveTo (\$xx); <a href="#">num (\$22.1.2.75)</a> ; oMath (\$22.1.2.77); p (\$xx); sdtContent (\$xx); smartTag (\$xx); <a href="#">sub (\$22.1.2.112)</a> ; <a href="#">sup (\$22.1.2.114)</a>

#### 94. §17.5.1.8, “placeholder (Custom XML Element Placeholder Text)”, p. 545–546, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p><i>[Example:</i> Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="<a href="#">Heading1</a><a href="#">heading1</a>" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

#### 95. §17.5.1.9, “SmartTag, Inline-Level Smart Tag”, p. 547

[DR 09-0011]

Parent Elements
bdo (\$xx); customXml (\$xx); <a href="#">deg (\$22.1.2.26)</a> ; del (\$xx); <a href="#">den (\$22.1.2.28)</a> ; dir (\$xx); <a href="#">e (\$22.1.2.32)</a> ; fldSimple (\$xx); <a href="#">fName (\$22.1.2.37)</a> ; hyperlink (\$xx); ins (\$xx); <a href="#">lim (\$22.1.2.52)</a> ; moveFrom (\$xx); moveTo (\$xx); <a href="#">num (\$22.1.2.75)</a> ; oMath (\$22.1.2.77); p (\$xx); sdtContent (\$xx); smartTag (\$xx); <a href="#">sub (\$22.1.2.112)</a> ; <a href="#">sup (\$22.1.2.114)</a>

#### 96. §17.5.2.1, “alias (Friendly Name)”, p. 551, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p><i>[Example:</i> Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="<a href="#">Heading1</a><a href="#">heading1</a>" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 97. §17.5.2.5, “**comboBox** (Combo Box Structured Document Tag)”, p. 554

[DR 09-0224]

- The child elements of this element specify choices which shall be presented to the user displayed in a standard drop-down list format

## 98. §17.5.2.5, “**comboBox** (Combo Box Structured Document Tag)”, pp. 555-556

[DR 09-0084]

*[Example:* Consider a combo box structured document tag defined as follows:

```
<w:sdt>
  <w:sdtPr>
    <w:dataBinding ... />
    <w:comboBox w:lastValue="2"/>
  </w:sdtPr>
  <w:sdtContent>
    <w:r>
      <w:t>Hello, world</w:t>
    </w:r>
  </w:sdtContent>
</w:sdt>
```

The current run content of the structured document tag reads Hello, world. When this document is opened, if the current value of the associated custom XML data is 2, the matching lastValue attribute specifies that the contents of the combo box must continue to be the current display text of the combo box even though there is no listItem whose value is 2 (and normally, the content of the structured document tag would be set to 2). Essentially, this attribute specifies a listItem whose value is 2 and whose displayText is Hello, world (the current structured document tag contents). *end example]*

## 99. §17.5.2.8, “**dateFormat** (Date Display Mask)”, p. 562, attribute val

[DR 09-0227]

Attributes	Description
------------	-------------

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 100. §17.5.2.9, “docPart (Document Part Reference)”, p. 563, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 101. §17.5.2.10, “docPartCategory (Document Part Category Filter)”, p. 564–565, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 102. §17.5.2.11, “**docPartGallery (Document Part Gallery Filter)**”, p. 566, attribute **val**

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p><i>[Example:</i> Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 103. §17.5.2.15, “**dropDownList (Drop-Down List Structured Document Tag)**”, p. 570

[DR 09-0084]

*[Example:* Consider a drop-down list structured document tag defined as follows:

```
<w:sdt>
  <w:sdtPr>
    <w:dataBinding ... />
    <w:dropDownList w:lastValue="2"/>
  </w:sdtPr>
  <w:sdtContent>
    <w:r>
      <w:t>Hello, world</w:t>
    </w:r>
  </w:sdtContent>
</w:sdt>
```

The current run content of the structured document tag reads Hello, world. When this document is opened, if the current value of the associated custom XML data is 2, the matching lastValue attribute specifies that the contents of the combo box must continue to be the current display text of the combo box even though there is no listItem whose value is 2 (and normally, the content of the structured document tag would be set to 2). Essentially, this attribute specifies a listItem whose value is 2 and whose displayText is Hello, world (the current structured document tag contents). *end example]*

## 104. §17.5.2.31, “**sdt, Inline-Level Structured Document Tag**”, p. 590

[DR 09-0011]

Parent Elements
bdo (\$xx); customXml (\$xx); <a href="#">deg (\$22.1.2.26)</a> ; del (\$xx); <a href="#">den (\$22.1.2.28)</a> ; dir (\$xx); <a href="#">e (\$22.1.2.32)</a> ; fldSimple (\$xx); <a href="#">fName (\$22.1.2.37)</a> ; hyperlink (\$xx); ins (\$xx); <a href="#">lim (\$22.1.2.52)</a> ; moveFrom (\$xx); moveTo (\$xx); <a href="#">num (\$22.1.2.75)</a> ; oMath (\$22.1.2.77); p (\$xx); sdtContent (\$xx); smartTag (\$xx); <a href="#">sub (\$22.1.2.112)</a> ; <a href="#">sup (\$22.1.2.114)</a>

## 105. §17.5.2.42, “tag (Programmatic Tag)”, p. 606, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p><i>[Example:</i> Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 106. §17.6.1.11, “pgMar (Page Margins)”, p. 641

[DR 09-0133]

```
<w:sectPr>
  <w:pgMar w:header="720" w:bottom="1440" w:top="1440" w:right="1440"
    w:left="1440" w:footer="720" w:gutter="0" />
  ...
</w:sectPr>
```

## 107. §17.6.2, “bottom (Bottom Border)”, p. 617, attribute themeShade

[DR 09-0080]

Change “... instance. If the ...” to “... instance. If the ...”

## 108. §17.6.7, “left (Left Border)”, p. 632, attribute themeShade

[DR 09-0080]

Change “... instance. If the ...” to “... instance. If the ...”

## 109. §17.6.15, “right (Right Border)”, p. 655, attribute themeShade

[DR 09-0080]

Change “... instance. If the ...” to “... instance. If the ...”

## 110. §17.6.20, “textDirection (Text Flow Direction)”, p. 667

[DR 09-0111]

[*Example: Consider a document with a section in which text must be oriented vertically, flowing from left to right horizontally on the page. should flow bottom to top vertically, and left to right horizontally.* This setting requires the following WordprocessingML:

```
<w:sectPr>
  ...
  <w:textDirection w:val="1rbtLr" />
</w:sectPr>
```

The textDirection element specifies via the 1rbtLr value in the val attribute that the text flow must be oriented vertically, with subsequent lines stacked from left to right. go bottom to top, and left to right. *end example]*

## 111. §17.6.20, “textDirection (Text Flow Direction)”, p. 667, attribute val

[DR 09-0111]

[*Example: Consider a document with a section in which text must be oriented vertically, flowing from left to right horizontally on the page. should flow bottom to top vertically, and left to right horizontally.* This setting requires the following WordprocessingML:

```
<w:sectPr>
  ...
  <w:textDirection w:val="1rbtLr" />
</w:sectPr>
```

The textDirection element specifies via the 1rbtLr value in the val attribute that the text flow must be oriented vertically, with subsequent lines stacked from left to right. go bottom to top, and left to right. *end example]*

## 112. §17.6.21, “top (Top Border)”, p. 673, attribute themeShade

[DR 09-0080]

Change “... instance. If the ...” to “... instance. If the ...”

## 113. §17.7.4, “General Style Properties”, p. 683

[DR 09-0085]

[*Example: Consider a style called Heading 1 in a document as follows:*

```

<w:style w:type="paragraph" w:styleId="Heading1">
  <w:name w:val="Heading 1"/>
  <w:basedOn w:val="Normal"/>
  <w:next w:val="Normal"/>
  <w:link w:val="Heading1Char"/>
  <w:uiPriority w:val="1"/>
  <w:qformat/>
  <w:rsid w:val="00F303CE"/>
  ...
</w:style>

```

## 114. §17.7.4, “General Style Properties”, p. 683

[DR 09-0121]

```

<w:style w:type="paragraph" w:styleId="Heading1">
  ...
  <w:qFormat/>
  ...
</w:style>

```

## 115. §17.7.4.1, “aliases (Alternate Style Names)”, p. 684, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre> &lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;   ... </pre>

## 116. §17.7.4.3, “basedOn (Parent Style ID)”, p. 688, attribute val

[DR 09-0227]

Attributes	Description
------------	-------------

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 117. §17.7.4.6, “link (Linked Style Reference)”, p. 694, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 118. §17.7.4.9, “name (Primary Style Name)”, p. 699, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 119. §17.7.4.10, “next (Style For Next Paragraph)”, p. 701, attribute val

[DR 09-0227]

Attributes	Description

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 120. §17.7.4.17, “style (Style Definition)”, pp. 706–707

[DR 09-0085]

[Example: Consider a style called Heading 1 in a document as follows:

```
<w:style w:type="paragraph" w:styleId="Heading1">
  <w:name w:val="Heading 1"/>
  <w:basedOn w:val="Normal"/>
  <w:next w:val="Normal"/>
  <w:link w:val="Heading1Char"/>
  <w:uiPriority w:val="1"/>
  <w:qformat/>
  <w:rsid w:val="00F303CE"/>
  ...
</w:style>
```

## 121. §17.7.4.17, “style (Style Definition)”, p. 707

[DR 09-0121]

```
<w:style w:type="paragraph" w:styleId="Heading1">
  ...
  <w:qFormat/>
  ...
</w:style>

<w:style w:type="paragraph" w:styleId="Heading1">
  ...
  <w:qFormat/>
  ...
</w:style>
```

**122. §17.7.4.17, “style (Style Definition)”, p. 708**

[DR 09-0122]

```
<w:tblCellMar>
...
<w:startLeft w:w="108" w:type="dxa"/>
...
<w:endRight w:w="108" w:type="dxa"/>
</w:tblCellMar>
```

**123. §17.7.5, “Document Defaults”, p. 715**

[DR 09-0084]

[Example: Consider the following fragment from the main document part of a WordprocessingML document:

```
<w:body>
  <w:p>
    <w:r>
      <w:t>Hello, world!L</w:t>
    </w:r>
  </w:p>
</w:body>
```

*... end example]*

**124. §17.7.5.1, “docDefaults (Document Default Paragraph and Run Properties)”, p. 716**

[DR 09-0084]

```
<w:body>
  <w:p>
    <w:r>
      <w:t> Hello, world!L</w:t>
    </w:r>
  </w:p>
</w:body>
```

**125. §17.7.5.1, “docDefaults (Document Default Paragraph and Run Properties)”, p. 716**

[DR 09-0126]

```

<w:docDefaults>
  <w:rPrDefault>
    <w:rPr>
      <w:b/>
    </w:rPr>
  </w:rPrDefault>
  <w:pPrDefault>
    <w:pPr>
      <w:jc w:val="center"/>
    </w:pPr>
  </w:pPrDefault>
  <w:rPrDefault>
    <w:rPr>
    <w:b/>
    </w:rPr>
  </w:rPrDefault>
</w:docDefaults>

```

## 126. §17.7.6, “Table Styles”, p. 724

[DR 09-0122]

```

<w:tblPr>
  <w:tblBorders>
    ...
    <w:startLeft w:val="single" w:sz="4" w:space="0" w:color="auto"/>
    ...
    <w:endRight w:val="single" w:sz="4" w:space="0" w:color="auto"/>
    ...
  </w:tblBorders>
  <w:tblCellMar>
    ...
    <w:startLeft w:w="108" w:type="dxa"/>
    ...
    <w:endRight w:w="108" w:type="dxa"/>
  </w:tblCellMar>
</w:tblPr>

```

## 127. §17.7.6, “Table Styles”, p. 725

[DR 08-0010]

The use or omission conditional formats shall be specified using the `tblLook` element, which contains a bitmask representing a number of attributes that indicate which properties are applied and omitted.

```

...
<w:tbl>
  <w:tblPr>
    ...
    <w:tblLook w:val="0660" w:firstRow="true" w:lastRow="true"
      w:noHBand="true" w:noVBand="true"/>
  </w:tblPr>
  ...
</w:tbl>
...
<w:tbl>
  <w:tblPr>
    ...
    <w:tblLook w:val="0460" w:firstRow="true" w:lastRow="true"
      w:noVBand="true"/>
  </w:tblPr>
  ...
</w:tbl>

```

## 128. §17.7.6.8, “tcPr (Table Style Conditional Formatting Table Cell Properties)”, p. 736

[DR 09-0122]

```

<w:tcBorders>
  ...
  <w:startLeft w:val="nil" />
  ...
  <w:endRight w:val="nil" />
  ...
</w:tcBorders>

```

## 129. §17.7.8, “Paragraph Styles”, p. 742

[DR 09-0121]

```

<w:style w:type="paragraph" w:styleId="TestParagraphStyle">
  ...
  <w:qFormat/>
  ...
</w:style>

```

## 130. §17.7.8.1, “Numbering in Paragraph Styles”, p. 744

[DR 09-0123]

```
<w:pPr>
  <w:tabs>
    <w:tab w:val="num" w:pos="720" />
  </w:tabs>
  <w:ind w:startLeft="720" w:hanging="360" />
</w:pPr>
```

## 131. §17.7.9, “Run (Character) Styles”, p. 747

[DR 09-0121]

```
<w:style w:type="character" w:styleId="TestCharacterStyle">
  ...
  <w:qFormat/>
  ...
</w:style>
```

## 132. §17.8.3.1, “altName (Alternate Names for Font)”, p. 752, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p><i>[Example:</i> Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 133. §17.8.3.13, “panose1 (Panose-1 Typeface Classification Number)”, p. 766

[DR 09-0048]

This element specifies the Panose-1 classification number ~~for the current font using the mechanism defined shown in §4.2.7.17 of ISO/IEC 14496-22:2007~~. This information can be used as defined in font substitution logic to locate an appropriate substitute font when this font is not available. This information is determined by querying the font when present and shall not be modified when the font is not available.

**134. §17.9, “Numbering”, p. 773**

[DR 09-0108]

```
<w:lvl w:ilvl="0">
  <w:start w:val="1" />
  <w:lvlText w:val="%1." />
  <w:lvlJc w:val="startLeft" />
  ...
</w:lvl>
```

**135. §17.9, “Numbering”, p. 773**

[DR 09-0123]

```
<w:pPr>
  <w:tabs>
    <w:tab w:val="num" w:pos="720" />
  </w:tabs>
  <w:ind w:startLeft="720" w:hanging="360" />
</w:pPr>
```

**136. §17.9.1, “abstractNum (Abstract Numbering Definition)”, p. 774**

[DR 09-0123]

```
<w:pPr>
  <w:tabs>
    <w:tab w:val="num" w:pos="720" />
  </w:tabs>
  <w:ind w:startLeft="720" w:hanging="360" />
</w:pPr>
```

**137. §17.9.1, “abstractNum (Abstract Numbering Definition)”, pp. 774–775**

[DR 09-0108]

```
<w:lvl w:ilvl="0">
  <w:start w:val="1" />
  <w:lvlText w:val="%1." />
  <w:lvlJc w:val="startLeft" />
  ...
</w:lvl>
```

## 138. §17.9.1, “abstractNum (Abstract Numbering Definition)”, p. 775, attribute abstractNumId

[DR 09-0123]

```
<w:pPr>
  <w:tabs>
    <w:tab w:val="num" w:pos="720" />
  </w:tabs>
  <w:ind w:startLeft="720"/>
</w:pPr>
```

## 139. §17.9.5, “legacy (Legacy Numbering Level Properties)”, p. 780

[DR 09-0108]

```
<w:lvl w:ilvl="0">
  ...
  <w:legacy w:legacySpace="820" w:legacyIndent="960" />
  <w:lvlJc w:val="startLeft" />
  ...
</w:lvl>
```

## 140. §17.9.5, “legacy (Legacy Numbering Level Properties)”, p. 780

[DR 09-0123]

```
<w:pPr>
  <w:ind w:startLeft="360" w:hanging="360" />
</w:pPr>
```

## 141. §17.9.6, “lvl (Numbering Level Override Definition)”, p. 782

[DR 09-0108]

```
<w:lvl w:ilvl="0">
  <w:start w:val="4" />
  <w:lvlText w:val="%1)" />
  <w:lvlJc w:val="startLeft" />
  ...
</w:lvl>
```

## 142. §17.9.6, “lvl (Numbering Level Override Definition)”, pp. 782–783

[DR 09-0123]

```

<w:pPr>
  <w:ind w:startLeft="360" w:hanging="360" />
</w:pPr>

<w:pPr>
  <w:ind w:startLeft="360" w:hanging="360" />
</w:pPr>

```

## 143. §17.9.6, “**lvl (Numbering Level Override Definition)**”, p. 783

[DR 09-0108]

```

<w:lvl w:ilvl="0">
  <w:start w:val="4" />
  <w:lvlText w:val="%1)" />
  <w:lvlJc w:val="startLeft" />
  ...
</w:lvl>

```

## 144. §17.9.8, “**lvlJc (Justification)**”, p. 788

[DR 09-0108]

```

<w:lvl w:ilvl="8" w:tplc="756C1446" w:tentative="1">
  <w:start w:val="1" />
  <w:numFmt w:val="bullet" />
  <w:lvlText w:val="•" />
  <w:lvlJc w:val="startLeft" />
  ...
</w:lvl>

```

## 145. §17.9.9, “**lvlOverride (Numbering Level Definition Override)**”, p. 790

[DR 09-0108]

```

<w:lvl w:ilvl="0">
  <w:start w:val="4" />
  <w:lvlText w:val="%1)" />
  <w:lvlJc w:val="startLeft" />
  ...
</w:lvl>
...
<w:lvl w:ilvl="1">
  <w:start w:val="5" />
  <w:lvlText w:val="%Test)" />

```

```

<w:lvlJc w:val="startleft" />
...
</w:lvl>
```

## 146. §17.9.9, “**lvlOverride (Numbering Level Definition Override)**”, pp. 790–791

[DR 09-0123]

```

<w:pPr>
  <w:ind w:startleft="360" w:hanging="360" />
</w:pPr>
...
<w:pPr>
  <w:ind w:startleft="360" w:hanging="360" />
</w:pPr>

<w:pPr>
  <w:ind w:startleft="360" w:hanging="360" />
</w:pPr>
```

## 147. §17.9.9, “**lvlOverride (Numbering Level Definition Override)**”, p. 791

[DR 09-0108]

```

<w:lvl w:ilvl="0">
  <w:start w:val="4" />
  <w:lvlText w:val="%1)" />
  <w:lvlJc w:val="startleft" />
  ...
</w:lvl>
```

## 148. §17.9.9, “**lvlOverride (Numbering Level Definition Override)**”, pp. 791–792, attribute **ilvl**

[DR 09-0123]

```

<w:pPr>
  <w:ind w:startleft="360" />
</w:pPr>
```

## 149. §17.9.11, “**lvlRestart (Restart Numbering Level Symbol)**”, pp. 793–794

[DR 09-0108]

```
<w:lvl w:ilvl="0">
```

```

<w:start w:val="1" />
<w:lvlText w:val="%1)" />
<w:lvlJc w:val="startLeft" />
...
</w:lvl>
<w:lvl w:ilvl="1">
  <w:start w:val="1" />
  <w:numFmt w:val="upperLetter" />
  <w:lvlText w:val="%2)" />
  <w:lvlJc w:val="startLeft" />
</w:lvl>
<w:lvl w:ilvl="2">
  <w:start w:val="1" />
  <w:numFmt w:val="lowerRoman" />
  <w:lvlRestart w:val="0">
    <w:lvlText w:val="%3)" />
    <w:lvlJc w:val="startLeft" />
  ...
</w:lvl>

```

## 150. §17.9.11, “lvlRestart (Restart Numbering Level Symbol)”, pp. 793–794

[DR 09-0123]

```

<w:pPr>
  <w:ind w:startLeft="360" w:hanging="360" />
</w:pPr>
...
<w:pPr>
  <w:ind w:startLeft="720" w:hanging="360" />
</w:pPr>
...
<w:pPr>
  <w:ind w:startLeft="1080" w:hanging="360" />
</w:pPr>

```

## 151. §17.9.14, “name (Abstract Numbering Definition Name)”, p. 799, attribute val

[DR 09-0227]

Attributes	Description
------------	-------------

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 152. §17.9.16, “num (Numbering Definition Instance)”, p. 802

[DR 09-0123]

```
<w:pPr>
  <w:ind w:startLeft="360" w:hanging="360" />
</w:pPr>
```

## 153. §17.9.18, “num (Numbering Definition Instance)”, p. 802

[DR 09-0108]

```
<w:lvl w:ilvl="0">
  <w:start w:val="4" />
  <w:lvlText w:val="%1)" />
  <w:lvlJc w:val="startLeft" />
  ...
</w:lvl>
```

## 154. §17.9.18, “numFmt (Numbering Format)”, p. 804

[DR 09-0123]

```
<w:pPr>
  <w:ind w:startLeft="1080" w:hanging="360" />
</w:pPr>
```

## 155. §17.9.18, “numFmt (Numbering Format)”, p. 804

[DR 09-0108]

```
<w:lvl w:ilvl="2">
  <w:start w:val="1" />
  <w:numFmt w:val="lowerRoman" />
  <w:lvlRestart w:val="0" />
  <w:lvlText w:val="%3)" />
```

```

<w:lvlJc w:val="startleft" />
...
</w:lvl>

```

## 156. §17.9.18, “numFmt (Numbering Format)”, p. 804

[DR 09-0091]

Attributes	Description
format (Custom Defined Number Format)	Specifies a custom number format using the syntax defined by the XSLT <del>1.0</del> -format attribute. This format shall be used for all numbering in the parent object. ...

## 157. §17.9.22, “numStyleLink (Numbering Style Reference)”, p. 809, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	... <i>[Example:</i> Consider the following WordprocessingML fragment: <w:pPr> <w:pStyle w:val="Heading1heading1" /> </w:pPr> ...

## 158. §17.9.23, “pPr (Numbering Level Associated Paragraph Properties)”, p. 810

[DR 09-0123]

```

<w:pPr>
  <w:tabs>
    <w:tab w:val="num" w:pos="720" />
  </w:tabs>
  <w:ind w:startleft="720" w:hanging="360" />
</w:pPr>

```

## 159. §17.9.24, “pStyle (Paragraph Style's Associated Numbering Level)”, p. 812

[DR 09-0123]

```

<w:pPr>
  <w:tabs>
    <w:tab w:val="num" w:pos="720" />
  </w:tabs>
  <w:ind w:startLeft= "720" w:hanging="360" />
</w:pPr>

```

## 160. §17.9.24, “pStyle (Paragraph Style's Associated Numbering Level)”, p. 813, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p><i>[Example:</i> Consider the following WordprocessingML fragment:</p> <pre> &lt;w:pPr&gt;   &lt;w:pStyle w:val="<u>Heading1</u><del>heading1</del>" /&gt; &lt;/w:pPr&gt; ... </pre>

## 161. §17.9.28, “styleLink (Numbering Style Definition)”, p. 819, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p><i>[Example:</i> Consider the following WordprocessingML fragment:</p> <pre> &lt;w:pPr&gt;   &lt;w:pStyle w:val="<u>Heading1</u><del>heading1</del>" /&gt; &lt;/w:pPr&gt; ... </pre>

## 162. §17.11.4, “endnotePr (Document-Wide Endnote Properties)”, p. 845

[DR 09-0127]

```

<w:endnotePr>
  <w:pos w:val="sectEnd"/>
  <w:numFmt w:val="lowerRoman" />
  <w:pos w:val="sectEnd"/>
</w:endnotePr>

```

### 163. §17.11.6, “endnoteRef (Endnote Reference Mark)”, p. 848

[DR 09-0137]

```

<w:r>
  <w:rPr>
    <w:rStyle w:val="EndnoteReference" />
  </w:rPr>
  <w:endnoteRef />
</w:r>

```

### 164. §17.11.17, “numFmt (Endnote Numbering Format)”, p. 866

[DR 09-0091]

Attributes	Description
format (Custom Defined Number Format)	Specifies a custom number format using the syntax defined by the XSLT <del>1.0</del> -format attribute. This format shall be used for all numbering in the parent object. ...

### 165. §17.11.18, “numFmt (Footnote Numbering Format)”, p. 867

[DR 09-0091]

Attributes	Description
format (Custom Defined Number Format)	Specifies a custom number format using the syntax defined by the XSLT <del>1.0</del> -format attribute. This format shall be used for all numbering in the parent object. ...

### 166. §17.12.4, “description (Description for Entry)”, p. 881, attribute val

[DR 09-0227]

Attributes	Description
------------	-------------

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 167. §17.12.9, “gallery (Gallery Associated With Entry)”, p. 888

[DR 09-0128]

```
<w:category>
  <w:name w:val="Internal Memo Covers" />
  <w:gallery w:val="coverPg" />
  <w:name w:val="Internal Memo Covers" />
</w:category>
```

## 168. §17.12.12, “name (Category Associated With Entry)”, p. 891

[DR 09-0128]

```
<w:category>
  <w:name w:val="Internal Memo Covers" />
  <w:gallery w:val="coverPg" />
  <w:name w:val="Internal Memo Covers" />
</w:category>
```

## 169. §17.12.12, “name (Category Associated With Entry)”, p. 891, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 170. §17.12.14, “style (Associated Paragraph Style Name)”, p. 894, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 171. §17.13.4.2, “comment (Comment Content)”, p. 905, attribute initials

[DR 09-0080]

Change “... application.If there ...” to “... application. If there ...”

## 172. §17.13.4.2, “comment (Comment Content)”, p. 905, attribute initials

[DR 09-0129]

[Example: Consider a comment represented using the following WordprocessingML fragment:

```
<w:comment w:id="1" w:initials="KB" w:authorname="Krista Bendig">
  ...
</w:comment>
```

The initials attribute specifies that the initials of the author of the current comment are KB, which can be used as desired. *end example*]

## 173. §17.13.5.13, “del (Deleted Math Control Character)”, p. 949

[DR 09-0018]

[Note: The W3C XML Schema definition of this element’s content model ([CT\\_MathCtrlDel](#)~~CT\_RPrChange~~) is located in §A.1. *end note*]

## 174. §17.13.5.16, “ins (Inserted Math Control Character)”, p. 957

[DR 09-0017]

[Note: The W3C XML Schema definition of this element’s content model ([CT\\_MathCtrlIns](#)~~CT\_RPrChange~~) is located in §A.1. *end note*]

**175. §17.13.5.34, “tblPrChange (Revision Information for Table Properties)”, p. 1014**

[DR 08-0010]

```
<w:tblPr>
...
<w:tblLook w:val="04A0" w:firstRow="true" w:firstColumn="true"
w:noVBand="true"/>
<w:tblPrChange w:id="0" w:author="Tristan Davis" w:date="2006-06-
01T13:39:00Z">
<w:tblPr>
...
<w:tblLook w:val="04A0" w:firstRow="true" w:firstColumn="true"
w:noVBand="true"/>
</w:tblPr>
</w:tblPrChange>
</w:tblPr>
```

**176. §17.13.5.36, “tcPrChange (Revision Information for Table Cell Properties)”, p. 1018**

[DR 08-0011]

```
<w:tcPr>
<w:cndStyle w:val="001000000000" w:firstColumn="true"/>
<w:tcW w:w="3192" w:type="dxa"/>
<w:tcPrChange w:id="8" w:author="Tristan Davis" w:date="2006-06-01T13:39:00Z">
<w:tcPr>
<w:tcW w:w="3192" w:type="dxa"/>
</w:tcPr>
</w:tcPrChange>
</w:tcPr>
```

**177. §17.14.3, “addressFieldName (Column Containing E-mail Address)”, p. 1050, attribute val**

[DR 09-0227]

Attributes	Description
------------	-------------

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 178. §17.14.8, “connectString (Data Source Connection String)”, p. 1056, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 179. §17.14.21, “mailSubject (Merged E-mail or Fax Subject Line)”, p. 1070, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 180. §17.14.23, “mappedName (Predefined Merge Field Name)”, p. 1072

[DR 09-0116]

```

<w:fieldMapData>
  <w:column w:val="0" />
    <w:name w:val="Column Name A" />
    <w:mappedName w:val="First Name" />
    <w:column w:val="0" />
  ...
</w:fieldMapData>
<w:fieldMapData>
  <w:column w:val="1" />
    <w:name w:val="Column Name B" />
    <w:mappedName w:val="Last Name" />
    <w:column w:val="1" />
  ...
</w:fieldMapData>

```

## 181. §17.14.23, “mappedName (Predefined Merge Field Name)”, p. 1073, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre> &lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;   ... </pre>

## 182. §17.14.24, “name (Data Source Name for Column)”, p. 1074, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre> &lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;   ... </pre>

## 183. §17.14.26, “query (Query For Data Source Records To Merge)”, p. 1077, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 184. §17.14.31, “table (Data Source Table Name)”, p. 1084, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 185. §17.14.34, “udl (UDL Connection String)”, p. 1088, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 186. §17.15.1.1, “activeWritingStyle (Grammar Checking Settings)”, p. 1091

[DR 09-0117]

[Example: Consider the following WordprocessingML fragment from the document settings:

```
<w:activeWritingStyle w:lang="en-CA" w:vendorID="64" w:dllVersion="131078"
w:nlCheck="1" w:checkStyle="0" w:appName="testApp" />
```

The activeWritingStyle element's lang attribute specifies that the English (Canada) language setting for grammatical and stylistic checks must be applied; the vendorID attribute specifies information about the vendor associated with the DLL used to perform the grammatical and stylistic checks; the dllVersion attribute specifies the version of this DLL; the nlCheck attribute specifies if natural language checks were performed or not; **and** the checkStyle attribute specifies that the hosting application should allow its grammar engine to check both the grammar and style of the given WordprocessingML document, if that functionality is available; **and the appName attribute indicates that an application called testApp specified the grammar checking rules of the given WordprocessingML. end example**

## 187. §17.15.1.5, “attachedSchema (Attached Custom XML Schema)”, p. 1096, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="<u>Heading1</u><b>heading1</b>" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 188. §17.15.1.7, “autoCaption (Single Automatic Captioning Setting)”, p. 1098

[DR 09-0109]

```
<w:captions>
  <w:caption w:name="Table" w:pos="below" w:chapNum="1" w:heading="2"
    w:numFmt="upperLetter" w:sep="hyphen8212" />
  <w:autoCaptions>
    <w:autoCaption w:name="wfwTable" w:caption="Table" />
  </w:autoCaptions>
</w:captions>
```

**189. §17.15.1.8, “autoCaptions (Automatic Captioning Settings)”, p. 1101**

[DR 09-0109]

```
<w:captions>
  <w:caption w:name="Table" w:pos="below" w:chapNum="1" w:heading="2"
    w:numFmt="upperLetter" w:sep="hyphen8212" />
  <w:autoCaptions>
    <w:autoCaption w:name="wfwTable" w:caption="Table" />
  </w:autoCaptions>
</w:captions>
```

**190. §17.15.1.11, “bookFoldPrinting (Book Fold Printing)”, p. 1104**

[DR 09-0133]

```
<w:pgMar w:header="0" w:top="1440" w:right="1440" w:bottom="1440" w:left="2160"
  w:footer="720" w:gutter="0" />
```

**191. §17.15.1.13, “bookFoldRevPrinting (Reverse Book Fold Printing)”, p. 1108**

[DR 09-0133]

```
<w:pgMar w:header="0" w:top="1440" w:right="1440" w:bottom="1440" w:left="2160"
  w:footer="720" w:gutter="0" />
```

**192. §17.15.1.16, “caption (Single Caption Type Definition)”, p. 1114, attribute chapNum**

[DR 09-0109]

```
<w:caption w:name="Table" w:pos="below" w:chapNum="true"
  w:heading="2" w:numFmt="upperLetter" w:sep="hyphen8212" />
```

**193. §17.15.1.16, “caption (Single Caption Type Definition)”, p. 1115, attribute heading**

[DR 09-0109]

```
<w:caption w:name="Table" w:pos="below" w:chapNum="1"
  w:heading="2" w:numFmt="upperLetter" w:sep="hyphen8212" />
```

In other words, the WordprocessingML above can be used to label tables inserted in a given WordprocessingML document generated by an application with a caption consisting of: the string Table followed by a decimal number corresponding with the chapter number in which the table is present, a hyphendash as defined in the

sep attribute, and a capital English letter defined by the numFmt attribute corresponding with the given table's ordering within the current chapter. *end example]*

#### 194. §17.15.1.18, “captions (Caption Settings)”, p. 1122

[DR 09-0109]

```
<w:caption w:name="Table" w:pos="below" w:chapNum="1" w:heading="2"
w:numFmt="upperLetter" w:sep="hyphen8212" />
```

#### 195. §17.15.1.19, “clickAndTypeStyle (Paragraph Style Applied to Automatically Generated Paragraphs)”, p. 1125, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p><i>[Example:</i> Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1<u>heading1</u>" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

#### 196. §17.15.1.23, “decimalSymbol (Radix Point for Field Code Evaluation)”, p. 1133, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p><i>[Example:</i> Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1<u>heading1</u>" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

#### 197. §17.15.1.24, “defaultTableStyle (Default Table Style for Newly Inserted Tables)”, p. 1134, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 198. §17.15.1.29, “documentProtection (Document Editing Restrictions)”, p. 1144

[DR 09-0085]

```
<w:style w:type="paragraph" w:styleId="Heading1">
  <w:name w:val="Heading 1" />
  <w:locked w:val="1" />
  ...
</w:style>
```

## 199. §17.15.1.44, “drawingGridHorizontalOrigin (Drawing Grid Horizontal Origin Point)”, p. 1158

[DR 09-0112]

```
<w:settings>
  ...
  <w:doNotUseMarginsForDrawingGridOrigin w:val="true" />
  <w:drawingGridHorizontalOrigin w:val="4320" />
  ...
</w:settings>
```

The drawingGridHorizontalOrigin element's val attribute is equal to 4320 specifying that the horizontal edge of the document's drawing grid must begin three inches (4320 twentieths of a point) from the left edge of the page, since the doNotUseMarginsForDrawingGridOrigin element's val attribute is equal to true. *end example]*

## 200. §17.15.1.46, “drawingGridVerticalOrigin (Drawing Grid Vertical Origin Point)”, p. 1160

[DR 09-0112]

[*Example:* Consider a WordprocessingML document whose drawing grid must begin one inch (1440 twentieths of a point) before the top edge of the page. This requirement would be specified using the following WordprocessingML markup in the document settings:

```
<w:settings>
  ...
  <w:doNotUseMarginsForDrawingGridOrigin w:val="true" />
  <w:drawingGridVerticalOrigin w:val="1440" />
  ...
</w:settings>
```

The drawingGridVerticalOrigin element's val attribute is equal to 1440 specifying that the vertical edge of the document's drawing grid must begin one inch (1440 twentieths of a point) from the top edge of the page, since the doNotUseMarginsForDrawingGridOrigin element's val attribute is equal to true. *end example]*

## **201. §17.15.1.54, “ignoreMixedContent (Ignore Mixed Content When Validating Custom XML Markup)”, p. 1168**

[DR 09-0155]

[*Example:* Consider a WordprocessingML document which should not have its custom XML content validated even by applications which support this operation. This requirement is specified using the following WordprocessingML in the document settings:

```
<w:doNotValidateAgainstSchema w:val="true" />
```

The doNotValidateAgainstSchema element's val attribute has a value of true specifying that the custom XML markup in this document must not be validated. *end example]*

[*Example:* Consider a WordprocessingML document that contains the following markup:

```

<w:customXml w:element="invoice" w:uri="http://www.example.com/invoice">
  <w:p>
    <w:r>
      <w:t>Invoice #:</w:t>
    </w:r>
    <w:customXml w:element="id" w:uri="http://www.example.com/invoice">
      <w:r>
        <w:t>012345</w:t>
      </w:r>
    </w:customXml>
  </w:p>
  <w:p>
    <w:r>
      <w:t>Invoice Date:</w:t>
    </w:r>
    <w:customXml w:element="date" w:uri="http://www.example.com/invoice">
      <w:r>
        <w:t>01/29/2009</w:t>
      </w:r>
    </w:customXml>
  </w:p>
</w:customXml>

```

If all the custom markup is extracted from the document, that markup would include all content in the document, i.e.:

```

<invoice xmlns="http://www.example.com/invoice">
  Invoice #:
  <id>012345</id>
  Invoice Date
  <date>01/29/2009</date>
</invoice>

```

However, if the ignoreMixedContent element is present with a val attribute value of true (or equivalent) then an application should ignore all text nodes in elements with mixed content, i.e.:

```

<invoice xmlns="http://www.example.com/invoice">
  <id>012345</id>
  <date>01/29/2009</date>
</invoice>

```

*end example]*

## 202. §17.15.1.56, “listSeparator (List Separator for Field Code Evaluation)”, p. 1169, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p><i>[Example:</i> Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 203. §17.15.1.57, “mirrorMargins (Mirror Page Margins)”, p. 1170

[DR 09-0200]

This element specifies that the left and right margins defined in the section properties shall be swapped on facing pages. [\[Note: Page numbering can be set arbitrarily, so the flip might not always be on the even-numbered pages. end note\]](#)

## 204. §17.15.1.64, “printTwoOnOne (Print Two Pages Per Sheet)”, p. 1177

[DR 09-0133]

```
<w:pgMar w:header="0" w:top="2160" w:right="1440" w:bottom="1440" w:left="1440"
  w:footer="720" w:gutter="0" />
```

## 205. §17.15.1.74, “saveInvalidXml (Allow Saving Document As XML File When Custom XML Markup Is Invalid)”, p. 999

[DR 09-0198]

This element specifies that this document should be capable of being saved into a format consisting of a single XML file (not defined by ISO/IEC 29500) [even](#) when its contents are invalid based XML schema validation of the custom XML markup contained in the document.

## 206. §17.15.1.77, “saveXmlDataOnly (Only Save Custom XML Markup)”, p. 1194

[DR 09-0084]

*[Example: ...]*

```

<w:body>
  <w:p>
    <w:customXml w:element="root" w:namespaceuri="urn:example">
      <w:r>
        <w:t>Hello, world</w:t>
      </w:r>
    </w:customXml>
  </w:p>
</w:body>

```

The presence of this element specifies that the resulting document only contains the custom XML markup, resulting in the following:

```
<ns0:root xmlns:ns0="urn:example">Hello, world</ns0:root>
```

*end example]*

## 207. §17.15.1.77, “**saveXmlDataOnly (Only Save Custom XML Markup)**”, p. 1194

[DR 09-0136]

```

<w:customXml w:element="root" w:namespaceuri="urn:example">
  <w:r>
    <w:t>Hello world</w:t>
  </w:r>
</w:customXml>

```

## 208. §17.15.1.93, “**writeProtection (Write Protection)**”, p. 1213

[DR 09-0113]

*[Example: Consider a WordprocessingML document that can be opened but only in a write protected state unless a password is provided, in which case the file would be opened in an editable state. This requirement would be specified using the following WordprocessingML in the document settings:*

```
<w:writeProtection w:hashValue="9oN7nWkCAyEZib1RomSJTjmPpCY=" />
```

*If the attributes specified in the password attribute group AG\_Password (\$xx) are present, then the application shall require a password to exit write protection. If the supplied password does not match the hash value in the attribute hashValue, then write protection shall be enabled. The writeProtection element is present which specifies that write protection must be turned on for this document. Since the password attribute is equal to 9oN7nWkCAyEZib1RomSJTjmPpCY= the given WordprocessingML document can only be opened in a write protected state unless a password which matches the hash value 9oN7nWkCAyEZib1RomSJTjmPpCY= is provided; in which case the file would be opened in an editable state. end example]*

## 209. §17.15.2, “Web Page Settings”, p. 1219

[DR 09-0062]

[*Example:* Consider the following WordprocessingML fragment for the web page settings in a WordprocessingML document:

...

The webSettings element contains all of the web page settings for this document. In this case, the web page settings specified for this document are: a frameset defined using the frameset element (§xx); and a setting specifying that when this file is saved as a web page, all resulting files must not exceed 8.3 ~~characters~~octets in length using the doNotUseLongFileNames element (§xx). *end example*]

## 210. §17.15.2.13, “doNotUseLongFileNames”, p. 1237

[DR 09-0062]

This element specifies that applications shall ensure that the file names for all files generated when saving this document as a web page do not exceed eight ~~characters~~octets with a three ~~character~~octet extension. This includes all supporting files (images which are part of this HTML web page, etc.). The file names generated are not case-sensitive.

[*Example:* Consider a WordprocessingML document which contains the following content within the web settings part:

...

The doNotUseLongFileNames element specifies that applications should ensure that all file names generated when this document is subsequently saved as a web page do not exceed the 8.3 ~~character~~octet file name limitation. *end example*]

## 211. §17.15.2.14, “encoding (Output Encoding When Saving as Web Page)”, p. 1239, attribute val

[DR 09-0227]

Attributes	Description
------------	-------------

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 212. §17.15.2.17, “frameLayout (Frameset Layout)”, p. 1244, attribute val

[DR 09-0130]

```
<w:frameset>
  <w:frameLayout w:val="cols" />
  ...
</w:frameset>
```

## 213. §17.15.2.30, “name (Frame Name)”, p. 1265, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 214. §17.15.2.40, “sz (Frame Size)”, p. 1280, attribute val

[DR 09-0227]

Attributes	Description

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 215. §17.15.2.41, “sz (Nested Frameset Size)”, p. 1281, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 216. §17.15.2.43, “title (Frame or Frameset Title)”, p. 1284, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 217. §17.15.2.46, “webSettings (Web Page Settings)”, p. 1288

[DR 09-0062]

[Example: Consider the following WordprocessingML fragment for the web page settings in a WordprocessingML document:

...

The webSettings element contains all of the web page settings for this document. In this case, the web page settings specified for this document are: a frameset defined using the frameset element (§xx); and a setting specifying that when this file is saved as a web page, all resulting files must not exceed 8.3 ~~characters~~octets in length using the doNotUseLongFileNames element (§xx). *end example]*

## 218. §17.16.1, “Syntax”, p. 1301

[DR 09-0076]

numbering=<blank line>"LISTNUM", [field-argument] | ...

## 219. §17.16.1, “Syntax”, p. 1303

[DR 09-0171]

```
double-quote=
'-' ; (* one double-quote character *)
```

## 220. §17.16.1, “Syntax”, p. 1304

[DR 09-0101]

```
letter=
"a"|"b"|"c"|"d"|"e"|"f"|"g"|"h"|"i"|"j"|"k"|"l"|"m"|
"n"|"o"|"p"|"q"|"r"|"s"|"t"|"u"|"v"|"w"|"x"|"y"|"z"|
"a"|"b"|"c"|"d"|"e"|"f"|"g"|"h"|"i"|"j"|"k"|"l"|"m"|
"A"|"B"|"C"|"D"|"E"|"F"|"G"|"H"|"I"|"J"|"K"|"L"|"M"|
"n"|"o"|"p"|"q"|"r"|"s"|"t"|"u"|"v"|"w"|"x"|"y"|"z" ;
"N"|"O"|"P"|"Q"|"R"|"S"|"T"|"U"|"V"|"W"|"X"|"Y"|"Z" ;
```

## 221. §17.16.5, “Field definitions”, p. 1341, category User Information

[DR 09-0080]

Change “... a user account under which the document is manipulated. [Note: These ...” to a user account under which the document is manipulated. [Note: These ...”

## 222. §17.16.5.1, “ADDRESSBLOCK”, p. 1342, switch \d

[DR 09-0080]

Change “... the recipient as defined ...” to “... the recipient as defined ...”

**223. §17.16.5.1, “ADDRESSBLOCK”, p. 1342, switch \f**

[DR 09-0080]

Change “... placeholders in the ...” to “... placeholders in the ...”

**224. §17.16.5.1, “ADDRESSBLOCK”, p. 1343, switch \l**

[DR 09-0080]

Change “... document. This language ...” to “... document. This language ...”

**225. §17.16.5.13, “DATE”, p. 1353, switch \l**

[DR 09-0089]

\l	When a field update is performed, if no <u>date-and-time-formatting-switch</u> is used, this switch is an instruction specifying that the field shall use the <u>date-and-time-formatting-switch</u> last used by the hosting application when inserting a new DATE field. If there is no last-used date format available, then the <u>date-and-time-formatting-switch</u> used is implementation-defined.
----	--

**226. §17.16.5.18, “FILESIZE”, p. 1358**

[DR 08-0009]

\k	Round to the nearest thousand bytes <u>kilobyte</u> .
\m	Round to the nearest million bytes <u>megabyte</u> .

**227. §17.16.5.33, “LISTNUM”, p. 1369**

[DR 09-0081]

**Description:** ... specific\_level ...

**228. §17.16.5.49, “QUOTE”, p. 1382**

[DR 09-0087]

**Description:** Retrieves the text specified by *text* in *field-argument*. This text can include any other fields except ~~AUTONUM, AUTONUMLGL, AUTONUMOUT, and SYMBOL~~.

**229. §17.16.10, “default (Default Text Box Form Field String)”, p. 1406, attribute val**

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p>[Example: Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 230. §17.16.17, “ffData (Form Field Properties)”, p. 1413

[DR 09-0063]

[Example: Consider the following WordprocessingML fragment for a text box form field:

...

The ffData element specifies the set of properties for this text box form field; in this example, a form field name of TestTextBox via the name element (§17.16.27), a disabled state via the enabled element (§17.16.14), and a maximum character length of 10 [Unicode scalar values](#)~~characters~~ via the maxLength element (§17.16.26). *end example*]

## 231. §17.16.18, “fldChar (Complex Field Character)”, p. 1415

[DR 09-0134]

```
<w:body>
  <w:p>
    <w:r>
      <w:fldChar w:fldCharType="beginstart" />
    </w:r>
  ...
</w:body>
```

## 232. §17.16.18, “fldChar (Complex Field Character)”, p. 1416, attribute dirty

[DR 09-0134]

```
<w:r>
  <w:fldChar w:fldCharType="beginstart" w:dirty="true"/>
</w:r>
```

## 233. §17.16.18, “fldChar (Complex Field Character)”, p. 1417, attribute fldLock

[DR 09-0134]

```
<w:r>
  <w:fldChar w:fldCharType="beginstart" w:fldLock="true"/>
</w:r>
```

## 234. §17.16.19, “fldSimple, Simple Field”, p. 1418

[DR 09-0011]

Parent Elements
bdo (\$xx); customXml (\$xx); <a href="#">deg (§22.1.2.26)</a> ; <a href="#">den (§22.1.2.28)</a> ; dir (\$xx); <a href="#">e (§22.1.2.32)</a> ; fldSimple (\$xx); <a href="#">fName (§22.1.2.37)</a> ; hyperlink (\$xx); <a href="#">lim (§22.1.2.52)</a> ; num (\$xx); <a href="#">oMath (§22.1.2.77)</a> ; p (\$xx); sdtContent (\$xx); smartTag (\$xx); <a href="#">sub (§22.1.2.112)</a> ; <a href="#">sup (§22.1.2.114)</a>

## 235. §17.16.20, “format (Text Box Form Field Formatting)”, p. 1421, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p><i>[Example:</i> Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 236. §17.16.22, “hyperlink, Hyperlink”, p. 1424

[DR 09-0011]

Parent Elements
bdo (\$xx); customXml (\$xx); <a href="#">deg (§22.1.2.26)</a> ; <a href="#">den (§22.1.2.28)</a> ; dir (\$xx); <a href="#">e (§22.1.2.32)</a> ; fldSimple (\$xx); <a href="#">fName (§22.1.2.37)</a> ; hyperlink (\$xx); <a href="#">lim (§22.1.2.52)</a> ; num (\$xx); <a href="#">oMath (§22.1.2.77)</a> ; p (\$xx); sdtContent (\$xx); smartTag (\$xx); <a href="#">sub (§22.1.2.112)</a> ; <a href="#">sup (§22.1.2.114)</a>

## 237. §17.16.25, “listEntry (Drop-Down List Entry)”, p. 1432, attribute val

[DR 09-0227]

Attributes	Description
val (String Value)	<p>...</p> <p><i>[Example:</i> Consider the following WordprocessingML fragment:</p> <pre>&lt;w:pPr&gt;   &lt;w:pStyle w:val="Heading1heading1" /&gt; &lt;/w:pPr&gt;</pre> <p>...</p>

## 238. §17.18.3, “ST\_BrClear (Line Break Text Wrapping Restart Location)”, pp. 1508–1509

[DR 09-0072]

Enumeration Value	Description
left (Restart In Next Text Region Left to Right)	<p>Specifies that the text wrapping break shall behave as follows when this line intersects a floating object:</p> <p>If the parent paragraph is left-to-right:</p> <ul style="list-style-type: none"> <li>• ...</li> <li>• Otherwise, treat this as a text wrapping break of <a href="#">styleType</a> none.</li> </ul> <p>If the parent paragraph is right to left:</p> <ul style="list-style-type: none"> <li>• If the object occurs to the left of the break, treat this as a break of <a href="#">styleType</a> all.</li> <li>• Otherwise, treat this as a text wrapping break of type none.</li> </ul> <p>In either case, if this line does not intersect a floating object, then treat this break as a text wrapping break of <a href="#">styleType</a> none.</p>

Enumeration Value	Description
right (Restart In Next Text Region Right to Left)	<p>Specifies that the text wrapping break shall behave as follows when this line intersects a floating object:</p> <p>If the parent paragraph is left-to-right:</p> <ul style="list-style-type: none"> <li>• If the object occurs to the right of the break, treat this as a break of <b>styletype all</b>.</li> <li>• Otherwise, treat this as a text wrapping break of <b>styletype none</b>.</li> </ul> <p>If the parent paragraph is right to left:</p> <ul style="list-style-type: none"> <li>• If this is the rightmost region of text flow currently on this line, <ul style="list-style-type: none"> <li>• If a floating object occurs to the right of the break, treat this as a break of <b>styletype all</b>.</li> <li>• Otherwise, advance the text to the next position on the line where text can be displayed</li> </ul> </li> <li>• Otherwise, treat this as a text wrapping break of <b>styletype none</b>.</li> </ul> <p>In either case, if this line does not intersect a floating object, then treat this break as a text wrapping break of <b>styletype none</b>.</p> <p>If the parent paragraph is right to left, then these behaviors are also reversed.</p> <p>...</p>

### 239. §17.18.3, “ST\_BrClear (Line Break Text Wrapping Restart Location)”, p. 1509

[DR 09-0073]

Enumeration Value	Description
right (Restart In Next Text Region Right to Left)	<p>...</p> <p>In either case, if this line does not intersect a floating object, then treat this break as a text wrapping break of <b>style none</b>.</p> <p>If the parent paragraph is right to left, then these behaviors are also reversed.</p> <p>[Note: This break type is used to control the text wrapping on the right side of a floating image without preventing text from appearing on the opposite side. end note]</p>

### 240. §17.18.16, “ST\_DocPartGallery (Entry Gallery Types)”, p. 1523

[DR 09-0128]

```

<w:category>
  <w:name w:val="Internal Memo Covers" />
  <w:gallery w:val="coverPg" />
  <w:name w:val="Internal Memo Covers" />
</w:category>
```

**241. §17.18.25, “ST\_FFHelpTextVal”, p. 1534**

[DR 09-0064]

This simple type also specifies the following restrictions:

- This simple type's contents have a maximum length of 256 [Unicode scalar values](#)~~characters~~.

**242. §17.18.26, ST\_FFName, p. 1535**

[DR 09-0065]

This simple type also specifies the following restrictions:

- This simple type's contents have a maximum length of 65 [Unicode scalar values](#)~~characters~~.

**243. §17.18.44, “ST\_Jc (Horizontal Alignment Type)”, p. 1554**

[DR 09-0201]

[*Example: ... The val attribute's value of ~~right~~[end](#) specifies that the content must be right-aligned on the page for a left-to-right paragraph, [and](#) left-justified for a right-to-left paragraph. end example*]

**244. §17.18.51, “ST\_MacroName”, p. 1563**

[DR 09-0066]

This simple type also specifies the following restrictions:

- This simple type's contents have a maximum length of 33 [Unicode scalar values](#)~~characters~~.

**245. §17.18.57, “ST\_Merge (Merged Cell Type)”, pp. 1569–1570**

[DR 09-0115]

```

<w:tc>
  <w:tcPr>
    <w:vMerge w:val="restart"/>
  </w:tcPr>
  ...
</w:tc>
...
<w:tc>
  <w:tcPr>
    <w:vMerge w:val="continue"/>
  </w:tcPr>
  ...
</w:tc>
...
<w:tc>
  <w:tcPr>
    <w:vMerge w:val="continue"/>
  </w:tcPr>
  ...
</w:tc>

```

The val attribute of type ST\_Merge on the vMerge element defines the cells thatwhich are vertically merged, and how each cell is merged together. *end example]*

## 246. §17.18.59, “ST\_NumberFormat (Numbering Format)”, p. 1574, enumeration value arabicAlpha

[DR 09-0080]

Change “... alphabet \_ from the ...” to “... alphabet from the ...”

## 247. §17.18.59, “ST\_NumberFormat (Numbering Format)”, p. 1584, enumeration value decimalFullWidth2

[DR 09-0092]

Enumeration Value	Description
-------------------	-------------

Enumeration Value	Description
<code>decimalFullWidth2 (Full Width Arabic Numerals Alternate)</code>	<p>Specifies that the sequence shall consist of a set of full-width Arabic numbering.</p> <p>To determine the text that is displayed for any value, this sequence specifies a set of characters that represent positions 1–9 and then those same characters are combined with each other and 0 (represents the number zero) to construct the remaining values.</p> <p>The set of characters used by this numbering format for values 0–9 is U+FF10–U+FF19, respectively.</p> <p>For values greater than the size of the set, the number is constructed by following these steps:</p> <ol style="list-style-type: none"> <li>1. Divide the value by 10 and write the symbol which represents the remainder.</li> <li>2. Divide the quotient of the previous division by 10 and write the symbol, which represents the remainder, to the left of the existing position.</li> <li>3. Repeat step 2 until the remaining value is equal to zero.</li> </ol> <p>[Example: The numbering for the items should be represented by the following pattern: 1, 2, 3, ..., 8, 9, 10, 11, 12, ..., 18, 19, 20, 21, ... end example]</p>

## 248. §17.18.59, “ST\_NumberFormat (Numbering Format)”, p. 1587, enumeration value hebrew1

[DR 09-0080]

Change “To determine ...” to “To determine ...”

## 249. §17.18.59, “ST\_NumberFormat (Numbering Format)”, p. 1590, enumeration value hindiConsonants

[DR 09-0080]

Change “... consonantfrom ...” to “... consonant from ...”

## 250. §17.18.59, “ST\_NumberFormat (Numbering Format)”, p. 1591, enumeration value hindiNumbers

[DR 09-0080]

Change “... numberfrom ...” to “... number from ...”

## 251. §17.18.59, “ST\_NumberFormat (Numbering Format)”, p. 1592, enumeration value hindiVowels

[DR 09-0080]

Change “... vowelfrom ...” to “... vowel from ...”

252. §17.18.59, “ST\_NumberFormat (Numbering Format)”, p. 1613,  
enumeration value thaiLetters

[DR 09-0080]

Change “... letter from ...” to “... letter from ...”

### 253. §17.18.78, "ST\_Shd (Shading Patterns)", p. 1633

[DR 09-0094]

This simple type specifies the pattern that~~which~~ shall be used to lay the pattern color over the background color for ~~a~~-shading.

This pattern consists of a mask [that which](#) is applied over the background shading color to get the locations where the pattern color should be shown. Each of these possible masks [are is](#) shown in the enumeration values [located](#) below. In each example, [an 8 pixel by 8 pixel mask is displayed where](#) black has been used as the fill color ([the parent element's fill attribute](#)), and white has been used as the pattern [color \(the parent element's color attribute\)](#). [When the shading is applied, the mask is tiled as necessary to match the size of the shaded area.](#)

254. §17.18.84, "ST\_TabJc (Custom Tab Stop Type)", p. 1651

[DR 09-0108]

```
<w:tab w:val="startleft" w:pos="2160" />
```

## 255. §17.18.93, "ST\_TextDirection (Text Flow Direction)", p. 1665

[DR 09-0111]

[Example: Consider an object in which text must be oriented vertically, flowing from left to right horizontally on the page. flow bottom to top vertically, and left to right horizontally. This is achieved by using an `lrbtLr` value in an element of type `ST_TextDirection` specifies that the text flow must go bottom to top, and left to right. end example]

## 256. §17.18.93, "ST\_TextDirection (Text Flow Direction)", p. 1665

[DR 09-0074]

Attributes	Description
IrV (Lines Flow From Left to Right Rotated)	<p>Specifies that text in the parent object shall be oriented vertically, flowing from left to right horizontally on the page.</p> <p>This means that vertical lines are filled before the text expands horizontally.</p> <p>This flow is also rotated <a href="#">clockwise</a> such that text which is not in an East Asian script is rotated 90 degrees when displayed on a page.</p>

**257. §17.18.93, “ST\_TextDirection (Text Flow Direction)”, p. 1666**

[DR 09-0075]

<b>Attributes</b>	<b>Description</b>
rlV (Lines Flow From Right to Left Rotated)	Specifies that text in the parent object shall be oriented vertically, flowing from right to left horizontally on the page. This means that vertical lines are filled before the text expands horizontally. This flow is also rotated such that text which is <u>not</u> in an East Asian script is rotated 90 degrees <b>counter</b> -clockwise when displayed on a page.

**258. §17.18.98, “ST\_UcharHexNumber (Two Digit Hexadecimal Value)”, p. 1672**

[DR 09-0093]

[Example: Consider the following value for a node of type ST\_UcharLongHexNumber: BE. ... end example]**259. §18.2.3, “customWorkbookView (Custom Workbook View)”, p. 1709-1710, attribute autoUpdate**

[DR 09-0080]

Change “... that if the ...” to “... that if the ...”Change “... the spreadsheet ...” to “... the spreadsheet ...”**260. §18.2.5, “definedName (Defined Name)”, p. 1719, new attribute**

[DR 09-0026]

<b>Attributes</b>	<b>Description</b>
<u>xml:space (Content Contains Significant Whitespace)</u>  <u>Namespace:</u> <u><a href="http://www.w3.org/XML/1998/namespace">http://www.w3.org/XML/1998/namespace</a></u>	<u>Specifies how white space should be handled for the contents of this element using the W3C space preservation rules.</u>  <u>The possible values for this attribute are defined by §2.10 of the XML 1.0 specification.</u>

**261. §18.2.20, “sheets (Sheets)”, p. 1733**

[DR 09-0135]

```

<sheets>
  <sheet name="Sheet1" sheetId="1" r:id="rId1"/>
  <sheet name="Sheet2" sheetId="2" r:id="rId2"/>
  <sheet name="Sheet5" sheetId="3" r:id="rId3"/>
  <sheet name="Chart1" sheetId="4" type="chartsheet" r:id="rId4"/>
</sheets>

```

## 262. §18.2.24, “webPublishing”, p. 1736

[DR 09-0067]

Attributes	Description
longFileNames (Enable Long File Names)	<p>Specifies a boolean value that indicates whether the application allows file names longer than 8 <del>characters</del><u>octets</u> for Web pages. <a href="#">File names are not case-sensitive.</a></p> <p>The possible values for this attribute are defined by the W3C XML Schema boolean datatype.</p>

## 263. §18.2.27, “workbook (Workbook)”, p. 1739

[DR 09-0135]

```

<sheets>
  <sheet name="Sheet1" sheetId="1" r:id="rId1"/>
  <sheet name="Sheet2" sheetId="2" r:id="rId2"/>
  <sheet name="Sheet5" sheetId="3" r:id="rId3"/>
  <sheet name="Chart1" sheetId="4" type="chartsheet" r:id="rId4"/>
</sheets>

```

## 264. §18.3.1.2, “autoFilter (AutoFilter Settings)”, p. 1758

[DR 09-0150]

[Example: ... The filter is being applied to the range B3:E8, and the criteria is being applied to values in the column whose ~~colId='1'~~colId is 1 (zero based column numbering, from left to right). ...

## 265. §18.3.1.3, “brk (Break)”, p. 1759, attribute man

[DR 09-0150]

Attributes	Description
man (Manual Page Break)	Manual Break flag. <del>1</del> <u>1</u> means the break is a manually inserted break. ...

## 266. §18.3.1.10, “cfRule (Conditional Formatting Rule)”, pp. 1765–1766, various attributes

[DR 09-0150]

Attributes	Description
aboveAverage (Above Or Below Average)	Indicates whether the rule is an "above average" rule. <u>'1'</u> indicates 'above average'. This attribute is ignored if type is not equal to aboveAverage. ...
bottom (Bottom N)	Indicates whether a "top/bottom n" rule is a "bottom n" rule. <u>'1'</u> indicates 'bottom'. This attribute is ignored if type is not equal to top10. ...
equalAverage (Equal Average)	Flag indicating whether the 'aboveAverage' and 'belowAverage' criteria is inclusive of the average itself, or exclusive of that value. <u>'1'</u> indicates to include the average value in the criteria. This attribute is ignored if type is not equal to aboveAverage. ...
priority (Priority)	The priority of this conditional formatting rule. This value is used to determine which format should be evaluated and rendered. Lower numeric values are higher priority than higher numeric values, where <u>'1'</u> is the highest priority. ...
stopIfTrue (Stop If True)	If this flag is <u>'1'</u> , no rules with lower priority shall be applied over this rule, when this rule evaluates to true. ...

## 267. §18.3.1.11, “cfvo (Conditional Format Value Object)”, p. 1768, attribute gte

[DR 09-0150]

Attributes	Description
gte (Greater Than Or Equal)	For icon sets, determines whether this threshold value uses the greater than or equal to operator. <u>'0'</u> indicates 'greater than' is used instead of 'greater than or equal to'. ...

## 268. §18.3.1.25, “customSheetView (Custom Sheet View)”, p. 1786

[DR 09-0097]

Attributes	Description
------------	-------------

<u>Attributes</u>	<u>Description</u>
showAutoFilter (Show AutoFilter Drop Down Controls)	...

## 269. §18.3.1.29, “dataConsolidate (Data Consolidate)”, p. 1790, new attribute

[DR 09-0026]

<u>Attributes</u>	<u>Description</u>
<a href="#">xml:space (Content Contains Significant Whitespace)</a>  <a href="#">Namespace: http://www.w3.org/XML/1998/namespace</a>	<a href="#">Specifies how white space should be handled for the contents of this element using the W3C space preservation rules.</a>  <a href="#">The possible values for this attribute are defined by §2.10 of the XML 1.0 specification.</a>

## 270. §18.3.1.32, “dataValidation (Data Validation)”, p. 1791, attribute allowBlank

[DR 09-0150]

<u>Attributes</u>	<u>Description</u>
allowBlank (Allow Blank)	A boolean value indicating whether the data validation allows the use of empty or blank entries. <a href="#">‘1’</a> means empty entries are OK and do not violate the validation constraints. ...

## 271. §18.3.1.38, “evenFooter (Even Page Footer)”, p. 1802, new attribute

[DR 09-0026]

<u>Attributes</u>	<u>Description</u>
<a href="#">xml:space (Content Contains Significant Whitespace)</a>  <a href="#">Namespace: http://www.w3.org/XML/1998/namespace</a>	<a href="#">Specifies how white space should be handled for the contents of this element using the W3C space preservation rules.</a>  <a href="#">The possible values for this attribute are defined by §2.10 of the XML 1.0 specification.</a>

## 272. §18.3.1.39, “evenHeader”, p. 1804

[DR 09-0050]

*&"font name,font type"* - code for "text font name" and "text font type", where *font name* and *font type* are strings specifying the name and type of the font, separated by a comma. When a hyphen appears in *font name*, it means "none specified". Both of *font name* and *font type* can be localized values. [Although ISO/IEC 14496-22 permits commas in font family/subfamily/full names, name and font type, the lexically first comma in the string is the one recognized as the separating comma.](#)

### 273. §18.3.1.40, “f (Formula)”, p. 1806, attribute aca

[DR 09-0080]

Change “... needed.The ...” to “... needed. The ...”

### 274. §18.3.1.40, “f (Formula)”, p. 1807, attribute r2

[DR 09-0150]

Attributes	Description
r2 (Input Cell 2)	Second input cell for data table when <u>dt2D</u> is <u>'1'</u> . Only applies to the data tables array function "TABLE()". Written on master cell of data table formula only. ...

### 275. §18.3.1.40, “f (Formula)”, p. 1808, new attribute

[DR 09-0026]

Attributes	Description
<u>xml:space (Content Contains Significant Whitespace)</u>  <u>Namespace:</u> <a href="http://www.w3.org/XML/1998/namespaces">http://www.w3.org/XML/1998/namespaces</a>	<a href="#">Specifies how white space should be handled for the contents of this element using the W3C space preservation rules.</a>  <a href="#">The possible values for this attribute are defined by §2.10 of the XML 1.0 specification.</a>

### 276. §18.3.1.41, “firstFooter (First Page Footer)”, p. 1808

[DR 09-0150]

First page footer content. Only used when headerFooter@differentFirst is '1'.

### 277. §18.3.1.41, “firstFooter (First Page Footer)”, p. 1808, new attribute

[DR 09-0026]

Attributes	Description
------------	-------------

<u>Attributes</u>	<u>Description</u>
<u><a href="#">xml:space (Content Contains Significant Whitespace)</a></u> <u><a href="#">Namespace: http://www.w3.org/XML/1998/namespace</a></u>	<u><a href="#">Specifies how white space should be handled for the contents of this element using the W3C space preservation rules.</a></u> <u><a href="#">The possible values for this attribute are defined by §2.10 of the XML 1.0 specification.</a></u>

## 278. §18.3.1.42, “firstHeader (First Page Header)”, p. 1808

[DR 09-0150]

First page header content. Only used when headerFooter@differentFirst is !1!.

## 279. §18.3.1.42, “firstHeader (First Page Header)”, p. 1809, new attribute

[DR 09-0026]

<u>Attributes</u>	<u>Description</u>
<u><a href="#">xml:space (Content Contains Significant Whitespace)</a></u> <u><a href="#">Namespace: http://www.w3.org/XML/1998/namespace</a></u>	<u><a href="#">Specifies how white space should be handled for the contents of this element using the W3C space preservation rules.</a></u> <u><a href="#">The possible values for this attribute are defined by §2.10 of the XML 1.0 specification.</a></u>

## 280. §18.3.1.43, “formula (Formula)”, p. 1809, new attribute

[DR 09-0026]

<u>Attributes</u>	<u>Description</u>
<u><a href="#">xml:space (Content Contains Significant Whitespace)</a></u> <u><a href="#">Namespace: http://www.w3.org/XML/1998/namespace</a></u>	<u><a href="#">Specifies how white space should be handled for the contents of this element using the W3C space preservation rules.</a></u> <u><a href="#">The possible values for this attribute are defined by §2.10 of the XML 1.0 specification.</a></u>

## 281. §18.3.1.44, “formula1 (Formula 1)”, p. 1809, new attribute

[DR 09-0026]

<u>Attributes</u>	<u>Description</u>

<u>Attributes</u>	<u>Description</u>
<u>xml:space (Content Contains Significant Whitespace)</u> <u>Namespace:</u> <a href="http://www.w3.org/XML/1998/namespace">http://www.w3.org/XML/1998/namespace</a>	<p><a href="#">Specifies how white space should be handled for the contents of this element using the W3C space preservation rules.</a></p> <p><a href="#">The possible values for this attribute are defined by §2.10 of the XML 1.0 specification.</a></p>

## 282. §18.3.1.45, “formula2 (Formula 2)”, p. 1810, new attribute

[DR 09-0026]

<u>Attributes</u>	<u>Description</u>
<u>xml:space (Content Contains Significant Whitespace)</u> <u>Namespace:</u> <a href="http://www.w3.org/XML/1998/namespace">http://www.w3.org/XML/1998/namespace</a>	<p><a href="#">Specifies how white space should be handled for the contents of this element using the W3C space preservation rules.</a></p> <p><a href="#">The possible values for this attribute are defined by §2.10 of the XML 1.0 specification.</a></p>

## 283. §18.3.1.49, “iconSet (Icon Set)”, p. 1813, attribute reverse

[DR 09-0150]

<u>Attributes</u>	<u>Description</u>
reverse (Reverse Icons)	If <a href="#">!1!</a> , reverses the default order of the icons in this icon set. ...

## 284. §18.3.1.57, “oddFooter (Odd Page Footer)”, p. 1823, new attribute

[DR 09-0026]

<u>Attributes</u>	<u>Description</u>
<u>xml:space (Content Contains Significant Whitespace)</u> <u>Namespace:</u> <a href="http://www.w3.org/XML/1998/namespace">http://www.w3.org/XML/1998/namespace</a>	<p><a href="#">Specifies how white space should be handled for the contents of this element using the W3C space preservation rules.</a></p> <p><a href="#">The possible values for this attribute are defined by §2.10 of the XML 1.0 specification.</a></p>

## 285. §18.3.1.58, “oddHeader (Odd Header)”, p. 1823, new attribute

[DR 09-0026]

<u>Attributes</u>	<u>Description</u>
<u>xml:space (Content Contains Significant Whitespace)</u> <u>Namespace:</u> <a href="http://www.w3.org/XML/1998/namespace">http://www.w3.org/XML/1998/namespace</a>	<p>Specifies how white space should be handled for the contents of this element using the W3C space preservation rules.</p> <p>The possible values for this attribute are defined by §2.10 of the XML 1.0 specification.</p>

## 286. §18.3.1.63, “pageSetup (Page Setup Settings)”, p. 1827

[DR 09-0095]

```
<pageSetup blackAndWhite="true" draft="false" paperHeight="1189mm"
paperWidth="841mm" paperUnits="mm" />
```

## 287. §18.3.1.63, “pageSetup (Page Setup Settings)”, p. 1830

[DR 09-0095]

When paperHeight, and paperWidth, ~~and paperUnits~~ are specified, paperSize should be ignored.

## 288. §18.3.1.63, “pageSetup (Page Setup Settings)”, p. 1830, attribute paperSize

[DR 09-0232]

<u>Attributes</u>	<u>Description</u>
paperSize (Paper Size)	<p>Paper size</p> <p>1 = Letter paper (8.5 in. by 11 in.)</p> <p>...</p> <p>68 = A3 extra transverse paper (322 mm by 445 mm)</p> <p><a href="#">69 = Japanese Double Postcard (200 mm x 148 mm)</a></p> <p><a href="#">70 = A6 (105 mm x 148 mm)</a></p> <p><a href="#">71 = Japanese Envelope Kaku #2</a></p> <p><a href="#">72 = Japanese Envelope Kaku #3</a></p> <p><a href="#">73 = Japanese Envelope Chou #3</a></p> <p><a href="#">74 = Japanese Envelope Chou #4</a></p>

<u>75 = Letter Rotated (11in x 8 1/2 11 in)</u>
<u>76 = A3 Rotated (420 mm x 297 mm)</u>
<u>77 = A4 Rotated (297 mm x 210 mm)</u>
<u>78 = A5 Rotated (210 mm x 148 mm)</u>
<u>79 = B4 (JIS) Rotated (364 mm x 257 mm)</u>
<u>80 = B5 (JIS) Rotated (257 mm x 182 mm)</u>
<u>81 = Japanese Postcard Rotated (148 mm x 100 mm)</u>
<u>82 = Double Japanese Postcard Rotated (148 mm x 200 mm)</u>
<u>83 = A6 Rotated (148 mm x 105 mm)</u>
<u>84 = Japanese Envelope Kaku #2 Rotated</u>
<u>85 = Japanese Envelope Kaku #3 Rotated</u>
<u>86 = Japanese Envelope Chou #3 Rotated</u>
<u>87 = Japanese Envelope Chou #4 Rotated</u>
<u>88 = B6 (JIS) (128 mm x 182 mm)</u>
<u>89 = B6 (JIS) Rotated (182 mm x 128 mm)</u>
<u>90 = (12 in x 11 in)</u>
<u>91 = Japanese Envelope You #4</u>
<u>92 = Japanese Envelope You #4 Rotated</u>
<u>93 = PRC 16K (146 mm x 215 mm)</u>
<u>94 = PRC 32K (97 mm x 151 mm)</u>
<u>95 = PRC 32K(Big) (97 mm x 151 mm)</u>
<u>96 = PRC Envelope #1 (102 mm x 165 mm)</u>
<u>97 = PRC Envelope #2 (102 mm x 176 mm)</u>
<u>98 = PRC Envelope #3 (125 mm x 176 mm)</u>
<u>99 = PRC Envelope #4 (110 mm x 208 mm)</u>

<p><a href="#"><u>100 = PRC Envelope #5 (110 mm x 220 mm)</u></a></p> <p><a href="#"><u>101 = PRC Envelope #6 (120 mm x 230 mm)</u></a></p> <p><a href="#"><u>102 = PRC Envelope #7 (160 mm x 230 mm)</u></a></p> <p><a href="#"><u>103 = PRC Envelope #8 (120 mm x 309 mm)</u></a></p> <p><a href="#"><u>104 = PRC Envelope #9 (229 mm x 324 mm)</u></a></p> <p><a href="#"><u>105 = PRC Envelope #10 (324 mm x 458 mm)</u></a></p> <p><a href="#"><u>106 = PRC 16K Rotated</u></a></p> <p><a href="#"><u>107 = PRC 32K Rotated</u></a></p> <p><a href="#"><u>108 = PRC 32K(Big) Rotated</u></a></p> <p><a href="#"><u>109 = PRC Envelope #1 Rotated (165 mm x 102 mm)</u></a></p> <p><a href="#"><u>110 = PRC Envelope #2 Rotated (176 mm x 102 mm)</u></a></p> <p><a href="#"><u>111 = PRC Envelope #3 Rotated (176 mm x 125 mm)</u></a></p> <p><a href="#"><u>112 = PRC Envelope #4 Rotated (208 mm x 110 mm)</u></a></p> <p><a href="#"><u>113 = PRC Envelope #5 Rotated (220 mm x 110 mm)</u></a></p> <p><a href="#"><u>114 = PRC Envelope #6 Rotated (230 mm x 120 mm)</u></a></p> <p><a href="#"><u>115 = PRC Envelope #7 Rotated (230 mm x 160 mm)</u></a></p> <p><a href="#"><u>116 = PRC Envelope #8 Rotated (309 mm x 120 mm)</u></a></p> <p><a href="#"><u>117 = PRC Envelope #9 Rotated (324 mm x 229 mm)</u></a></p> <p><a href="#"><u>118 = PRC Envelope #10 Rotated (458 mm x 324 mm)</u></a></p>
--

When paperHeight, paperWidth, and paperUnits are specified, paperSize should be ignored.

The possible values for this attribute are defined by the W3C XML Schema unsignedInt datatype.

## 289. §18.3.1.64, “pageSetup (Chart Sheet Page Setup)”, p. 1832

[DR 09-0095]

```
<pageSetup blackAndWhite="true" draft="false" paperHeight="1189mm"
paperWidth="841mm" paperUnits="mm" />
```

## 290. §18.3.1.64, “pageSetup (Chart Sheet Page Setup)”, p. 1834

[DR 09-0095]

When paperHeight, and paperWidth, ~~and paperUnits~~ are specified, paperSize should be ignored.

## 291. §18.3.1.73, “row (Row)”, p. 1848, various attributes

[DR 09-0150]

Attributes	Description
collapsed (Collapsed)	'1-' if the rows 1 level of outlining deeper than the current row are in the collapsed outline state. It means that the rows which are 1 outline level deeper (numerically higher value) than the current row are currently hidden due to a collapsed outline state. ...
customFormat (Custom Format)	'1-' if the row style should be applied. ....
customHeight (Custom Height)	'1-' if the row height has been manually set. ...
hidden (Hidden)	'1-' if the row is hidden, e.g., due to a collapsed outline or by manually selecting and hiding a row. ...
ph (Show Phonetic)	'1-' if the row should show phonetic. ...
thickBot (Thick Bottom)	'1-' if any cell in the row has a medium or thick bottom border, or if any cell in the row directly below the current row has a thick top border. ...

## 292. §18.3.1.75, “scenario (Scenario)”, p. 1854

[DR 09-0020]

Attributes	Description
name (Scenario Name)	Scenario's name (user input). Shall be unique for the <a href="#">workbookworksheet</a> . The possible values for this attribute are defined by the ST_Xstring simple type (§xx).

## 293. §18.3.1.85, “sheetProtection (Sheet Protection Options)”, p. 1870, attribute scenarios

[DR 09-0080]

Change “... Scenarios should ...” to “... Scenarios should ...”

**294. §18.3.1.96, “v (Cell Value)”, p. 1884, new attribute**

[DR 09-0026]

<u>Attributes</u>	<u>Description</u>
<u>xml:space (Content Contains Significant Whitespace)</u>  <u>Namespace:</u> <a href="http://www.w3.org/XML/1998/namespaces">http://www.w3.org/XML/1998/namespaces</a>	<u>Specifies how white space should be handled for the contents of this element using the W3C space preservation rules.</u>  <u>The possible values for this attribute are defined by §2.10 of the XML 1.0 specification.</u>

**295. §18.3.2.1, “colorFilter (Color Filter Criteria)”, p. 1888, attribute cellColor**

[DR 09-0150]

<u>Attributes</u>	<u>Description</u>
cellColor (Filter By Cell Color)	Flag indicating whether or not to filter by the cell's fill color. <u>!1!</u> indicates to filter by cell fill. <u>!0!</u> indicates to filter by the cell's font color. ...

**296. §18.3.2.2, “customFilter (Custom Filter Criteria)”, p. 1888**

[DR 09-0097]

A custom AutoFilter ... when the filter is applied.**297. §18.3.2.3, “customFilters (Custom Filters)”, p. 1889, attribute and**

[DR 09-0150]

<u>Attributes</u>	<u>Description</u>
and (And)	Flag indicating whether the two criteria have an "and" relationship. <u>!1!</u> indicates "and", <u>!0!</u> indicates "or". ...

**298. §18.3.2.5, “dynamicFilter (Dynamic Filter)”, pp. 1891–1892, attribute various**

[DR 09-0233]

<u>Attributes</u>	<u>Description</u>
-------------------	--------------------

<u>Attributes</u>	<u>Description</u>
<a href="#"><u>val (Value)</u></a>	<p><a href="#">A minimum numeric value for dynamic filter. (See description of valIso to understand when val is required.)</a></p> <p><a href="#">The possible values for this attribute are defined by the W3C XML Schema double datatype.</a></p>
<a href="#"><u>valIso (ISO Value)</u></a>	<p>A minimum date value for dynamic filter. (See description of maxValIso to understand when <a href="#">val</a>/<a href="#">valIso</a> is required.)</p> <p><a href="#">Only these types of dynamic filters use numeric data, and therefore shall use val and shall not use valiso:</a></p> <ul style="list-style-type: none"> <li>• <a href="#">aboveAverage and belowAverage</a></li> </ul> <p>The possible values for this attribute are defined by the W3C XML Schema dateTime datatype.</p>

## 299. §18.4.12 , “t (Text)”, p. 1906, new attribute

[DR 09-0026]

<u>Attributes</u>	<u>Description</u>
<a href="#"><u>xml:space (Content Contains Significant Whitespace)</u></a>  <a href="#"><u>Namespace: http://www.w3.org/XML/1998/namespace</u></a>	<p><a href="#">Specifies how white space should be handled for the contents of this element using the W3C space preservation rules.</a></p> <p><a href="#">The possible values for this attribute are defined by §2.10 of the XML 1.0 specification.</a></p>

## 300. §18.5.1.1, “calculatedColumnFormula (Calculated Column Formula)”, p. 1909, new attribute

[DR 09-0026]

<u>Attributes</u>	<u>Description</u>
<a href="#"><u>xml:space (Content Contains Significant Whitespace)</u></a>  <a href="#"><u>Namespace: http://www.w3.org/XML/1998/namespace</u></a>	<p><a href="#">Specifies how white space should be handled for the contents of this element using the W3C space preservation rules.</a></p> <p><a href="#">The possible values for this attribute are defined by §2.10 of the XML 1.0 specification.</a></p>

## 301. §18.7.1, “author (Author)”, p. 1929, new attribute

[DR 09-0026]

<u>Attributes</u>	<u>Description</u>
<u>xml:space (Content Contains Significant Whitespace)</u>  <u>Namespace:</u> <a href="http://www.w3.org/XML/1998/namespaces">http://www.w3.org/XML/1998/namespaces</a>	<p>Specifies how white space should be handled for the contents of this element using the W3C space preservation rules.</p> <p>The possible values for this attribute are defined by §2.10 of the XML 1.0 specification.</p>

### 302. §18.8.1, “alignment (Alignment)”, p. 1936, attribute indent

[DR 09-0150]

<u>Attributes</u>	<u>Description</u>
indent (Indent)	<p>...</p> <p><i>[Example: For example, an indent value of '1' means that the text begins 3 space widths (of the normal style font) from the edge of the cell.]</i></p> <p><i>end example</i></p> <p>...</p>

### 303. §18.8.29, “name (Font Name)”, p. 1965

[DR 09-0068]

<u>Attributes</u>	<u>Description</u>
val (String Value)	<p>...</p> <p>The string length for this attribute shall be 0 to 31 <a href="#">Unicode scalar values</a> characters.</p> <p>...</p>

### 304. §18.8.31, “numFmts (Number Formats)”, p. 1974

[DR 09-0022]

<u>Format symbol</u>	<u>Description and result</u>
\$- +/#():space	Displays the symbol. If it is desired to display a character that differs from one of these symbols, precede the character with a backslash (\). Alternatively, enclose the character in quotation marks. <i>[Example: If the number format is (000), and the value 12 is in the cell, the number (012) is displayed.]</i>
/	<a href="#">If this symbol is preceded and followed by a number symbol (0, #, and ?), it is interpreted as the fraction format symbol and will display the number in the format of a fraction.</a> <a href="#">Otherwise, it is interpreted as the forward slash character and is displayed as such.</a>

### 305. §18.10.1.10, “calculatedMember (Calculated Member)”, p. 2030

[DR 09-0009]

~~Represents a calculated OLAP hierarchy. A calculated member is a member of an OLAP-based PivotTable whose value is calculated on the OLAP server. For PivotTables that are created from OLAP cubes the summarized values are precalculated on the OLAP server before the SpreadsheetML application displays the results. These fields appear in the PivotTable field list but cannot be changed from within the PivotTable. You cannot change the summary function used to calculate data fields or subtotals, or add calculated items.~~

A calculated member is a member in an OLAP hierarchy for which the value is calculated by an OLAP server using a Multidimensional Expressions (MDX) expression. For PivotTables that are created from OLAP cubes the summarized values are calculated by an OLAP server before the SpreadsheetML application displays the results. In OLAP PivotTables, the consuming application cannot change the summary function used to calculate totals and subtotals.

### 306. §18.10.1.45, “item (PivotTable Field Item)”, p. 2071

[DR 09-0021]

Attributes	Description
x (Item Index)	Specifies the item index in pivotFields collection in the PivotCache. <del>Applies only non-OLAP PivotTables.</del> ...

### 307. §18.10.1.46, “items (Field Items)”, p. 2072

[DR 09-0097]

*[Example: In the ... <item x="66"/>, which ... Therefore, if you added ...*

### 308. §18.10.1.67, “pivotCacheDefinition (PivotCache Definition)”, pp. 2093-2094

[DR 09-0087]

```
<pivotCacheDefinition xmlns="..." xmlns:r="..." r:id="rId1" refreshedBy="AnonUser"
    refreshedDateIso="2006-05-22T10:07:16" createdVersion="3" refreshedVersion="3"
    minRefreshableVersion="3" recordCount="182">
    ...
</pivotCacheDefinition>
```

### 309. §18.10.1.67, “pivotCacheDefinition (PivotCache Definition)”, p. 2096, attribute refreshedDateIso

[DR 09-0087]

~~If refreshedDateIso and refreshedDate are both present, refreshedDateIso shall take precedence.”~~

### 310. §18.10.1.73, “pivotTableDefinition (PivotTable Definition)”, p. 2142, attribute printDrill

[DR 09-0080]

Change “... indicates that ...” to “... indicates that ...”

### 311. §18.10.1.73, “pivotTableDefinition (PivotTable Definition)”, p. 2146, attribute useAutoFormatting

[DR 09-0080]

Change “... indicates that ...” to “... indicates that ...”

### 312. §18.10.1.90, “sharedItems (Shared Items)”, p. 2167

[DR 09-0069]

Attributes	Description
longText (Long Text)	<p>Specifies a boolean value that indicates whether this field contains a long text value. A string is considered long if it is over 255 <a href="#">Unicode scalar values</a><del>characters</del>.</p> <p>A value of 1 or true indicates the value contains more than 255 <a href="#">Unicode scalar values</a><del>characters</del> of text.</p> <p>A value of 0 or false indicates the value contains less than 255 <a href="#">Unicode scalar values</a><del>characters</del>.</p> <p><i>[Note: This is used as many legacy spreadsheet application support a limit of <a href="#">Unicode scalar values</a><del>characters</del> for text values. end note]</i></p> <p>The possible values for this attribute are defined by the W3C XML Schema boolean datatype.</p>

### 313. §18.14.11, “oleLink (Generic Object Link Connection)”, p. 2251, attribute progId

[DR 09-0080]

Change “... connection. [Example: ...” to “... connection. [Example: ...”

### 314. §18.17.2.1, “Constants”, p. 2276

[DR 09-0015]

```
error-constant=
 "#DIV/0! " | "#N/A" | "#NAME? " | "#NULL! " |
```

"#NUM! " | "#REF! " | "#VALUE! " "#GETTING DATA" ;

### 315. §18.17.2.1, “Constants”, p. 2276

[DR 09-0171]

```
error-constant=
  "#DIV/0!-" | "#N/A" | "#NAME?-" | "#NULL!-"
  "#NUM!- " | "#REF!- " | "#VALUE!- " ;
```

### 316. §18.17.2.1, “Constants”, p. 2277

[DR 09-0171]

```
double-quote=
  ' -' ; (* one double-quote character*)

string-char=
  ' -" -' | (* consecutive double-quotes, with no space between them *) character -
  double-quote ; (* any character except double-quote *)
```

### 317. §18.17.2.3, “Cell References”, p. 2281

[DR 09-0171]

```
apostrophe=
  " -" ; (* one apostrophe character *)
```

### 318. §18.17.2.3.1, “A1-Style Cell References”, p. 2285.

[DR 09-0102]

```
letter=
  "a" | "b" | "c" | "d" | "e" | "f" | "g" | "h" | "i" | "j" | "k" | "l" | "m" |
  "n" | "o" | "p" | "q" | "r" | "s" | "t" | "u" | "v" | "w" | "x" | "y" | "z" |
  "a" | "b" | "c" | "d" | "e" | "f" | "g" | "h" | "i" | "j" | "k" | "l" | "m" |
  "n" | "o" | "p" | "q" | "r" | "s" | "t" | "u" | "v" | "w" | "x" | "y" | "z" |
  "A" | "B" | "C" | "D" | "E" | "F" | "G" | "H" | "I" | "J" | "K" | "L" | "M" |
  "n" | "o" | "p" | "q" | "r" | "s" | "t" | "u" | "v" | "w" | "x" | "y" | "z" | ;
  "N" | "O" | "P" | "Q" | "R" | "S" | "T" | "U" | "V" | "W" | "X" | "Y" | "Z" | ;
```

### 319. §18.17.3, “Error values”, p. 2292

[DR 09-0015]

Error Value	Reason for Occurrence
-------------	-----------------------

Error Value	Reason for Occurrence
#GETTING_DATA	<p>Intended to indicate when a cell reference cannot be evaluated because the value for the cell has not been retrieved or calculated. [Note: This can happen when connected to an OLAP cube. <i>end note</i>]</p> <p>This error constant differs from #N/A in that #GETTING_DATA is used when there is an expectation that the value for the cell will eventually be available, whereas #N/A is used when there is no such expectation.</p>

### 320. §18.17.5.2, “Precision”, p. 2296

[DR 09-0007]

The *value space* consists of the values  $(-1)^s \times m \times 2^n$ , where  $s$  is 0 or 1, where  $m$  is an integer greater than or equal to 0 and whose absolute value is less than  $2^{53}$ , and  $n$  is an integer between -10745 and 9710, inclusive.

### 321. §18.17.5.4, “Interpretation”, p. 2297

[DR 09-0231]

Strings that are permitted according to the lexical definition in §18.17.5.3 shall be interpreted as values in the value space as follows:

4. If the raw absolute value is larger than the largest value in the value space ( $2^{1023}1024$  minus  $-12^{971}$ , by default), or smaller than the smallest value in the value space ( $-2^{1023}+1$ , by default), then a consuming application shall treat this as equivalent to the error value #NUM! (\$xx). Otherwise, the value in the value space that is closest to the raw value is chosen as the interpretation. In the case that two values are equally close, the one with the smaller absolute value is chosen.

### 322. §18.17.6.5, “Name Representation”, p. 2300

[DR 09-0014]

A formula can contain one or more names. These names shall be defined in the *Worksheet**Workbook* part's XML with each being the subject of a *definedName* element, inside a *definedNames* element. ...

### 323. §18.17.7.2, “ACCRINT”, p. 2306, value 0 or omitted

[DR 09-0080]

Change “... 30/360. Assumes ...” to “... 30/360. Assumes ...”

### 324. §18.17.7.2, “ACCRINT”, p. 2307, value 4

[DR 09-0080]

Change "... 30/360. The ..." to "... 30/360. The ..."

### 325. §18.17.7.28, "BETAINV", p. 2333

[DR 09-0144]

**Syntax:**

BETAINV ( *probability* , *alpha* , *beta* [ , [ *A* ] , [ *B* ] ] )

**Description:** Computes the inverse of the cumulative distribution function for a specified beta distribution. Given a value for *probability*, BETAINV is used to seek for the value *x* such that BETADIST(*x, alpha, beta, A, B*) = *probability*. Thus, precision of BETAINV depends on precision of BETADIST. ~~BETAINV uses an iterative search technique.~~

### 326. §18.17.7.37, "CHIINV", p. 2347

[DR 09-0144]

**Return Type and Value:** number – The inverse of the one-tailed probability of the chi-squared distribution.

However, if

- ...
- ~~An implementation uses an iterative search technique, and the search has not converged after some implementation-defined number of iterations the implementation determines that a return value cannot be computed,~~ #N/A is returned

### 327. §18.17.7.49, "CORREL", p. 2360

[DR 09-0098]

- ~~$\bar{y}$~~  = the sample mean AVERAGE(*array-2*)

### 328. §18.17.7.63, "COVAR", p. 2382

[DR 09-0145]

- ~~$\bar{x}$~~  = the sample mean AVERAGE(*array-1*)

### 329. §18.17.7.66, "CUBEMEMBER", p. 2385, name member-expression

[DR 09-0080]

Change "... constant. [Note: ..." to "... constant. [Note: ..."

**330. §18.17.7.74, “DATE”, p. 2393, name year**

[DR 09-0080]

Change “... integer representing ...” to “... integer representing ...”**331. §18.17.7.76, “DATEVALUE”, pp. 2396-2397**

[DR 09-0143]

**Arguments:**

Name	Type	Description
<i>date-time-string</i>	text	The date and/or time whose <u>date component</u> serial value is to be computed. ... Any time information in <i>date-time-string</i> shall be ignored. ...

**332. §18.17.7.76, “DATEVALUE”, p. 2397, name date-time-string**

[DR 09-0080]

Change “... ignored. When ...” to “... ignored. When ...”**333. §18.17.7.89, “DEVSQ”, p. 2410**

[DR 09-0098]

- $\bar{x}$  = the mean of the elements in *argument-list*

**334. §18.17.7.110, “ERROR.TYPE”, p. 2429**

[DR 09-0015]

value	Return Value
#N/A	7
<u>#GETTING DATA</u>	<u>8</u>
Anything else	#N/A

**335. §18.17.7.121, “FINV”, p. 2438**

[DR 09-0144]

**Return Type and Value:** number – The inverse of the F probability distribution.

However, if

- ...

- ~~An implementation uses an iterative search technique, and the search has not converged after some implementation-defined number of iterations~~the implementation determines that a return value cannot be computed, #N/A is returned

### 336. §18.17.7.126, “FORECAST”, p. 2442

[DR 09-0098]

- $x$  = a sample value
- $\bar{x}$  is the sample mean AVERAGE(*known-xs*)
- $y$  = a sample value
- $\bar{y}$  is the sample mean AVERAGE(*known-ys*)

### 337. §18.17.7.132, “GAMMAINV”, p. 2447

[DR 09-0144]

**Return Type and Value:** number – The inverse of the gamma distribution.

However, if

- ...
- ~~An implementation uses an iterative search technique, and the search has not converged after some implementation-defined number of iterations~~the implementation determines that a return value cannot be computed, #N/A is returned.

### 338. §18.17.7.170, “INTERCEPT”, p. 2482

[DR 09-0098]

- $x$  = a sample value
- $\bar{x}$  is the sample mean AVERAGE(*known-xs*)
- $y$  = a sample value
- $\bar{y}$  is the sample mean AVERAGE(*known-ys*)

### 339. §18.17.7.173, “IRR”, p. 2487

[DR 09-0144]

**Return Type and Value:** number – The internal rate of return for a series of cash flows.

However, if ~~an implementation uses an iterative search technique, and the calculation has not converged after an implementation-defined number of iterations~~the implementation determines that a return value cannot be computed, #NUM! is returned.

**340. §18.17.7.195, “LINEST”, p. 2500**

[DR 09-0098]

- $x$  = a sample value
- $\bar{x}$  is the sample mean AVERAGE(*known-xs*)
- $y$  = a sample value
- $\bar{y}$  is the sample mean AVERAGE(*known-ys*)

**341. §18.17.7.230, “NORMINV”, p. 2534**

[DR 09-0144]

**Return Type and Value:** number – The inverse of the normal distribution for the specified mean and standard deviation.

However, if

- ...
- ~~An implementation uses an iterative search technique, and the search has not converged after some implementation-defined number of iterations; the implementation determines that a return value cannot be computed~~, #N/A is returned.

**342. §18.17.7.232, “NORMSINV”, p. 2535**

[DR 09-0144]

**Return Type and Value:** number – The inverse of the standard normal distribution.

However, if

- ...
- ~~An implementation uses an iterative search technique, and the search has not converged after some implementation-defined number of iterations; the implementation determines that a return value cannot be computed~~, #N/A is returned.

**343. §18.17.7.247, “PEARSON”, p. 2557**

[DR 09-0098]

- $x$  = a sample value
- $\bar{x}$  = the sample mean AVERAGE(*array-1*)
- $y$  = a sample value
- $\bar{y}$  = the sample mean AVERAGE(*array-2*)

**344. §18.17.7.283, “RSQ”, p. 2593**

[DR 09-0098]

- $x$  = a sample value
- $\bar{x}$  is the sample mean AVERAGE(*known-xs*)
- $y$  = a sample value
- $\bar{y}$  is the sample mean AVERAGE(*known-ys*)

**345. §18.17.7.292, “SKEW”, p. 2600**

[DR 09-0098]

- $\bar{x}$  = the mean of the elements in *argument-list*

**346. §18.17.7.294, “STDEVA”, p. 2602**

[DR 09-0098]

- $x$  = a sample value
- $\bar{x}$  is the sample mean AVERAGE(*known-xs*)
- $y$  = a sample value
- $\bar{y}$  is the sample mean AVERAGE(*known-ys*)

**347. §18.17.7.298, “STANDARDIZE”, p. 2605, name mean**

[DR 09-0080]

Change “... distribution. Represented ...” to “... distribution. Represented ...”

**348. §18.17.7.298, “STANDARDIZE”, p. 2605, name standard-dev**

[DR 09-0080]

Change “... distribution. Represented ...” to “... distribution. Represented ...”

**349. §18.17.7.299, “STDEV”, p. 2605**

[DR 09-0145]

- $\bar{x}$  = the sample mean AVERAGE(*argument-1, argument-1, ..., argument-n*)

**350. §18.17.7.300, “STDEVA”, p. 2606**

[DR 09-0145]

- $\bar{x}$  = the sample mean AVERAGE(*argument-1, argument-1, ..., argument-n*)

**351. §18.17.7.301, “STDEV”, p. 2607**

[DR 09-0145]

- $\bar{x}$  = the sample mean  $\text{AVERAGE}(\text{argument-1}, \text{argument-1}, \dots, \text{argument-n})$

**352. §18.17.7.302, “STDEVPA”, p. 2608**

[DR 09-0145]

- $\bar{x}$  = the sample mean  $\text{AVERAGE}(\text{argument-1}, \text{argument-1}, \dots, \text{argument-n})$

**353. §18.17.7.303, “STEYX”, p. 2609**

[DR 09-0098]

- $x$  = a sample value
- $\bar{x}$  is the sample mean  $\text{AVERAGE}(\text{known-xs})$
- $y$  = a sample value
- $\bar{y}$  is the sample mean  $\text{AVERAGE}(\text{known-ys})$

**354. §18.17.7.324, “TIMEVALUE”, p. 2627**

[DR 09-0143]

**Description:** Computes the serial value of the **date and/or time** represented by the string *date-time-string*.

**Arguments:**

Name	Type	Description
<i>date-time-string</i>	text	The date and/or time whose <a href="#">time component</a> serial value is to be computed. <i>date-time-string</i> can have any date and/or time format. Any date information in <i>date-time-string</i> shall be ignored.

**Return Type and Value:** number – The serial value of the **date and/or time** represented by the string *date-time-string*, [as a value greater than or equal to 0 and less than or equal to 1](#).

**355. §18.17.7.338, “VAR”, p. 2636**

[DR 09-0145]

- $\bar{x}$  = the sample mean  $\text{AVERAGE}(\text{argument-1}, \text{argument-1}, \dots, \text{argument-n})$

**356. §18.17.7.339, "VARA", p. 2637**

[DR 09-0145]

- $\bar{x}$  = the sample mean  $\text{AVERAGE}(\text{argument-1}, \text{argument-1}, \dots, \text{argument-n})$

**357. §18.17.7.340, "VARP", p. 2638**

[DR 09-0145]

- $\bar{x}$  = the sample mean  $\text{AVERAGE}(\text{argument-1}, \text{argument-1}, \dots, \text{argument-n})$

**358. §18.17.7.341, "VARPA", p. 2639**

[DR 09-0145]

- $\bar{x}$  = the sample mean  $\text{AVERAGE}(\text{argument-1}, \text{argument-1}, \dots, \text{argument-n})$

**359. §18.17.7.356, "ZTEST", p. 2663**

[DR 09-0145]

- $\bar{x}$  = the sample mean  $\text{AVERAGE}(\text{array})$

**360. §18.18.26, "ST\_DynamicFilterType (Dynamic Filter)", p. 2682–2683, enumeration values**

[DR 09-0233]

Enumeration Value	Description
lastQuarter (Last Quarter)	Shows last <a href="#">calendar</a> quarter's dates.
lastWeek (Last Week)	Shows last week's dates, <a href="#">using Sunday as the first weekday</a> .
M2 (2nd Month)	Shows the dates that are in <a href="#">Februaray</a> <a href="#">February</a> , regardless of year.
nextQuarter (Next Quarter)	Shows next <a href="#">calendar</a> quarter's dates.
nextWeek (Next Week)	Shows next week's dates, <a href="#">using Sunday as the first weekday</a> .
Q1 (1st Quarter)	Shows the dates that are in the 1st <a href="#">calendar</a> quarter, regardless of year.
Q2 (2nd Quarter)	Shows the dates that are in the 2nd <a href="#">calendar</a> quarter, regardless of year.
Q3 (3rd Quarter)	Shows the dates that are in the 3rd <a href="#">calendar</a> quarter, regardless of year.
Q4 (4th Quarter)	Shows the dates that are in the 4th <a href="#">calendar</a> quarter, regardless of year.
thisQuarter (This Quarter)	Shows this <a href="#">calendar</a> quarter's dates.
thisWeek (This Week)	Shows this week's dates, <a href="#">using Sunday as the first weekday</a> .

### 361. §19.2.1.13, “font (Embedded Font Name)”, p. 2769

[DR 09-0053]

Attributes	Description
<p>pitchFamily (Similar Font Family)</p> <p>Namespace: .../drawingml/2006/main</p>	<p>Specifies the font pitch as well as the font family for the corresponding font. Because the value of this attribute is determined by an octet value <del>byte variable</del> this value shall be interpreted as follows:</p> <p>...</p> <p>This information is determined by querying the font when present and shall not be modified when the font is not available. This information can be used in font substitution logic to locate an appropriate substitute font when this font is not available.</p> <p><a href="#">[Note: Although the attribute name is pitchFamily, the integer value of this attribute specifies the font family with higher 4 bits and the font pitch with lower 4 bits. end note]</a></p> <p>The possible values for this attribute are defined by the W3C XML Schema byte datatype.</p>

### 362. §19.2.1.19, “modifyVerifier (Modification Verifier)”, p. 2774

[DR 09-0070]

The password supplied to the algorithm is to be a UTF-16LE encoded string; strings longer than [510 octets](#)~~255 characters~~ are truncated to [510 octets](#)~~255 characters~~. If there is a leading BOM character (U+FEFF) in the encoded password it is removed before hash calculation.

### 363. §19.3.1.21, “graphicFrame (Graphic Frame)”, p. 2829, attribute bwMode

[DR 09-0242]

Attributes	Description
<p><a href="#">bwMode (Black and White Mode)</a></p> <p>Namespace: .../drawingml/2006/main</p>	<p><a href="#">Specifies how the graphical object should be rendered, using color, black or white, or grayscale.</a></p> <p><a href="#">[Note: This does not mean that the graphical object itself is stored with only black and white or grayscale information. This attribute instead sets the rendering mode that the graphical object uses. end note]</a></p>

Attributes	Description
	<a href="#">The possible values for this attribute are defined by the ST_BlackWhiteMode simple type (\$xx).</a>

### 364. §19.3.2.4, “oleObj (Global Element for Embedded objects and Controls)”, p. 2859

[DR 09-0243]

This element specifies a global element to be used for an Embedded object and Control.

[When the oleObject element contains a pic child element, the identifier specified by the pic/nvPicPr/cNvPr@id attribute shall be ignored and the identifier specified by the graphicFrame/nvGraphicFramePr/cNvPr@id attribute shall be used when deciding which identifier to use for the OLE object.](#)

### 365. §19.5.9, “audio (Audio)”, p. 2882

[DR 09-0140]

```
<p:cMediaNode vol="50%11000">...
  <p:tgtEl>
    <p:sndTgt r:embed="rId2" />
  </p:tgtEl>
</p:cMediaNode>
```

### 366. §19.5.44, “from (From)”, p. 2919

[DR 09-0106]

```
<p:animScale>
  ...
  <p:from x="100%000" y="100%000" />
  <p:to x="80%000" y="100%000" />
</p:animScale>
```

### 367. §19.5.46, “hsl (HSL)”, p. 2921, attributes l and s

[DR 08-0005]

Attributes	Description
l (Lightness)	Specifies a lightness <del>as fixed percentage in 1000ths of a percent when no percent sign is included in the value or as percent when a percent sign is present as a percentage</del> . The values range from [-100%, 100%].  The possible values for this attribute are defined by the ST_FixedPercentage simple type (\$xx).

Attributes	Description
s (Saturation)	Specifies a saturation <del>as fixed percentage in 1000ths of a percent when no percent sign is included in the value or as percent when a percent sign is present as a percentage</del> . The values range from [-100%, 100%].  The possible values for this attribute are defined by the ST_FixedPercentage simple type (\$xx).

### 368. §19.5.46, “hsl (HSL)”, p. 2921, attribute l

[DR 09-0080]

Change “... percent when ...” to “... percent when ...”

### 369. §19.5.46, “hsl (HSL)”, p. 2921, attribute s

[DR 09-0080]

Change “... percent when ...” to “... percent when ...”

### 370. §19.5.62, “rCtr (Rotation Center)”, p. 2935

[DR 08-0141]

```
<p:animMotion origin="layout" path="M 0 0 L 0.25 0.33333 E"
    pathEditMode="relative" rAng="0" ptsTypes="">
    ...
    <p:rCtr x="56.7%457200" y="83.4%274638" />
</p:animMotion>
```

### 371. §19.5.63, “rgb (RGB)”, pp. 2936–2937, attributes b, g, and r

[DR 08-0006]

Attributes	Description
b (Blue)	This attribute specifies a blue <del>as fixed percentage in 1000ths of a percent when no percent sign is included in the value or as percent when a percent sign is present as a percentage</del> . Values range from [-100%, 100%].  The possible values for this attribute are defined by the ST_FixedPercentage simple type (\$xx).
g (Green)	This attribute specifies a green <del>as fixed percentage in 1000ths of a percent when no percent sign is included in the value or as percent when a percent sign is present as a percentage</del> . Values range from [-100%, 100%].  The possible values for this attribute are defined by the ST_FixedPercentage simple type (\$xx).

Attributes	Description
r (Red)	This attribute specifies a red <del>as fixed percentage in 1000ths of a percent when no percent sign is included in the value or as percent when a percent sign is present as a percentage</del> . Values range from [-100%, 100%].  The possible values for this attribute are defined by the ST_FixedPercentage simple type (\$xx).

### 372. §19.5.63, “rgb (RGB)”, p. 2936, attribute b

[DR 09-0080]

Change “... percent\_when ...” to “... percent when ...”

### 373. §19.5.63, “rgb (RGB)”, p. 2937, attribute g

[DR 09-0080]

Change “... percent\_when ...” to “... percent when ...”

### 374. §19.5.63, “rgb (RGB)”, p. 2937, attribute r

[DR 09-0080]

Change “... percent\_when ...” to “... percent when ...”

### 375. §19.5.68, “snd (Sound)”, p. 2941

[DR 09-0118]

```
<p:stSnd>
  <p:snd r:embed="rId2" r:link="rId3"/>
</p:stSnd>
```

### 376. §19.5.68, “snd (Sound)”, p. 2942, attribute embed

[DR 09-0080]

Change “... file.\_[Note: ...]” to “... file. [Note: ...]”

### 377. §19.5.69, “sndAc (Sound Action)”, p. 2942

[DR 09-0118]

```
<p:stSnd>
  <p:snd r:embed="rId2" r:link="rId3"/>
</p:stSnd>
```

**378. §19.5.70, “sndTgt (Sound Target)”, p. 2943, attribute embed**

[DR 09-0080]

Change “... file. [Note: ...]” to “... file. [Note: ...]”**379. §19.5.76, “stSnd (Start Sound Action)”, p. 2949**

[DR 09-0118]

```
<p:stSnd>
  <p: snd r:embed="rId2" r:link="rId3"/>
</p:stSnd>
```

**380. §19.5.79, “tav (Time Animate Value)”, p. 2952**

[DR 09-0120]

```
<p:tavLst>
  <p:tav tm="0%">
    ...
  </p:tav>
  <p:tav tm="100000%">
    ...
  </p:tav>
</p:tavLst>
```

**381. §19.5.79, “tav (Time Animate Value)”, p. 2955, attribute fmla**

[DR 09-0120]

```
<p:tavLst>
  <p:tav tm="0%" fmla="#ppt_y-sin(pi*$)/3">
    ...
  </p:tav>
  <p:tav tm="100000%">
    ...
  </p:tav>
</p:tavLst>
```

**382. §19.5.80, “tavLst (Time Animated Value List)”, p. 2956**

[DR 09-0120]

```
<p:tavLst>
  <p:tav tm="0%">
```

```

...
</p:tav>
...
</p:tavLst>
```

### 383. §19.5.83, “tmPct (Time Percentage)”, p. 2958

[DR 08-0002]

*[Example: ...*

```

<p:par>
  <p:cTn id="5" >
    <p:stCondLst> ... </p:stCondLst>
    <p:iterate type="lt">
      <p:tmPct val="1000010%" />
    </p:iterate>
    <p:childTnLst> ... </p:childTnLst>
  </p:cTn>
</p:par>
```

*end example]*

### 384. §19.5.88, “to (To)”, p. 2962

[DR 09-0106]

```

<p:animScale>
  ...
  <p:from x="100%000" y="100%000" />
  <p:to x="80%000" y="100%000" />
</p:animScale>
```

### 385. §19.5.88, “to (To)”, p. 2962

[DR 09-0142]

```

<p:cBhvr>
  <p:cTn id="9" dur="200" decel="10.5%0000" autoRev="1" fill="hold">
    <p:stCondLst>
      ...
    </p:stCondLst>
  </p:cTn>
  ...
</p:cBhvr>
```

**386. §19.5.90, “to (To)”, p. 2964**

[DR 09-0131]

```
<p:animClr clrSpc="rg$b">
  ...
</p:animClr>
```

**387. §19.5.92, “tavLst val (Value)”, p. 2965–2966**

[DR 09-0120]

```
<p:tavLst>
  <p:tav tm="0%">
    ...
  </p:tav>
  <p:tav tm="100000000%">
    ...
  </p:tav>
</p:tavLst>
```

**388. §19.7.53, “ST\_TransitionSideDirectionType (Transition Slide Direction Type)”, p. 3004, enumeration value r**

[DR 09-0226]

Enumeration Value	Description
r (Transition Slide Direction <a href="#">Enum</a> ( Right ))	Specifies that the transition direction is right

**389. §20.1.2.2.32, “snd (Hyperlink Sound)”, p. 3044, attribute embed**

[DR 09-0080]

Change “... file. [Note: ...]” to “... file. [Note: ...]”**390. §20.1.2.3.3, “alphaOff (Alpha Offset)”, p. 3053, attribute val**

[DR 09-0250]

Attributes	Description
val (Value)	Specifies the opacity as expressed by a percentage offset increase or decrease <a href="#">relative</a> to the input color. Increases never increase the opacity beyond 100%, decreases never decrease the opacity below 0%.

## 391. §20.1.2.3.5, “blueMod (Blue Modification Modulation)”, p. 3055, attribute val

[DR 09-0264]

Attributes	Description
val (Value)	<p><b>Specifies the value of the blue component. The assigned value is specified as a percentage with 0% indicating minimal blue and 100% indicating maximum blue.</b> <u>Specifies the blue component as expressed by a percentage relative to the input color component. Increases never increase the blue component beyond 100%, decreases never decrease the blue component below 0%.</u></p> <p><i>[Example: The following manipulates the fill from having RGB value RRGGBB = (00, FF, 0000, 00, FF) to value RRGGBB= (00, FF, FF00, 00, 80)</i></p> <pre>&lt;a:solidFill&gt;   &lt;a:srgbClr val="00FF000000FF"&gt;     &lt;a:blue blueMod val="100.000%50.000%" /&gt;   &lt;/a:srgbClr&gt; &lt;/a:solidFill&gt;</pre> <p><i>end example]</i></p> <p>...</p>

## 392. §20.1.2.3.6, “blueOff (Blue Offset)”, pp. 3055–3056, attribute val

[DR 09-0265]

Attributes	Description
val (Value)	<p><b>Specifies the value of the blue component. The assigned value is specified as a percentage with 0% indicating minimal blue and 100% indicating maximum blue.</b> <u>Specifies the blue component as expressed by a percentage offset increase or decrease to the input color component. Increases never increase the blue component beyond 100%, decreases never decrease the blue component below 0%.</u></p> <p><i>[Example: The following manipulates the fill from having RGB value RRGGBB = (00, FF, 0000, 00, FF) to value RRGGBB= (00, FF, FF00, 00, CC)</i></p> <pre>&lt;a:solidFill&gt;   &lt;a:srgbClr val="00FF00"&gt;     &lt;a:blue blueOff val="100.000%-20.000%" /&gt;   &lt;/a:srgbClr&gt; &lt;/a:solidFill&gt;</pre> <p><i>end example]</i></p> <p>...</p>

### 393. §20.1.2.3.10, “green (Green)”, p. 3057, attribute val

[DR 09-0251]

Attributes	Description
val (Value)	<p>Specifies the value of the <b>bluegreen</b> component. The assigned value is specified as a percentage with 0% indicating minimal <b>bluegreen</b> and 100% indicating maximum <b>bluegreen</b>.</p> <p><i>[Example: The following manipulates the fill from having RGB value RRGGBB = (00, FF, 00, 00, FF) to value RRGGBB= (00, FF, FF)</i></p> <pre>&lt;a:solidFill&gt;   &lt;a:srgbClr val="00FF000000FF"&gt;     &lt;a:bluegreen val="100.000%"/&gt;   &lt;/a:srgbClr&gt; &lt;/a:solidFill&gt;</pre> <p><i>end example]</i></p> <p>...</p>

### 394. §20.1.2.3.11, “greenMod (Green Modification Modulation)”, p. 3058, attribute val

[DR 09-0252]

Attributes	Description
val (Value)	<p><b>Specifies the value of the blue component. The assigned value is specified as a percentage with 0% indicating minimal blue and 100% indicating maximum blue.</b> <b>Specifies the green component as expressed by a percentage relative to the input color component. Increases never increase the green component beyond 100%, decreases never decrease the green component below 0%.</b></p> <p><i>[Example: The following manipulates the fill from having RGB value RRGGBB = (00, FF, 00) to value RRGGBB= (00, FF, FF00, 80, 00)</i></p> <pre>&lt;a:solidFill&gt;   &lt;a:srgbClr val="00FF00"&gt;     &lt;a:bluegreenMod val="100.000%50.000%"/&gt;   &lt;/a:srgbClr&gt; &lt;/a:solidFill&gt;</pre> <p><i>end example]</i></p> <p>...</p>

### 395. §20.1.2.3.12, “greenOff (Green Offset)”, p. 3059, attribute val

[DR 09-0253]

Attributes	Description
------------	-------------

Attributes	Description
val (Value)	<p>Specifies the value of the blue component. The assigned value is specified as a percentage with 0% indicating minimal blue and 100% indicating maximum blue. Specifies the green component as expressed by a percentage offset increase or decrease to the input color component. Increases never increase the green component beyond 100%, decreases never decrease the green component below 0%.</p> <p>[Example: The following manipulates the fill from having RGB value RRGGBB = (00, FF, 00) to value RRGGBB= (00, FF, FF00, CC, 00)</p> <pre data-bbox="414 544 1067 762">&lt;a:solidFill&gt;   &lt;a:srgbClr val="00FF00"&gt;     &lt;a:blueGreenOff val="100.000%-20.000%" /&gt;   &lt;/a:srgbClr&gt; &lt;/a:solidFill&gt;</pre> <p><i>end example]</i></p> <p>...</p>

### 396. §20.1.2.3.19, “lum (Luminance)”, p. 3065, attribute val

[DR 09-0254]

Attributes	Description
val (Value)	<p>Specifies the value of the blue component luminance. The assigned value is specified as a percentage with 0% indicating minimal blue luminance and 100% indicating maximum blue luminance.</p> <p>[Example: The following manipulates the fill from having RGB value RRGGBB = (00, FF, 00) to value RRGGBB= (00, FF, FF00, 66, 00)</p> <pre data-bbox="414 1275 980 1417">&lt;a:solidFill&gt;   &lt;a:srgbClr val="00FF00"&gt;     &lt;a:blueLum val="100.000%20.000%" /&gt;   &lt;/a:srgbClr&gt; &lt;/a:solidFill&gt;</pre> <p><i>end example]</i></p> <p>...</p>

### 397. §20.1.2.3.20, “lumMod (Luminance Modulation)”, p. 3065, attribute val

[DR 09-0255]

Attributes	Description
------------	-------------

Attributes	Description
val (Value)	<p>Specifies the value of the blue component. The assigned value is specified as a percentage with 0% indicating minimal blue and 100% indicating maximum blue. Specifies the luminance as expressed by a percentage relative to the input color. Increases never increase the luminance beyond 100%, decreases never decrease the luminance below 0%.</p> <p>[Example: The following manipulates the fill from having RGB value RRGGBB = (00, FF, 00) to value RRGGBB= (00, FF, FF00, 75, 00)</p> <pre>&lt;a:solidFill&gt;   &lt;a:srgbClr val="00FF00"&gt;     &lt;a:blueLumMod val="100.000%50.000%" /&gt;   &lt;/a:srgbClr&gt; &lt;/a:solidFill&gt;</pre> <p><i>end example]</i></p> <p>...</p>

### 398. §20.1.2.3.21, “lumOff (Luminance Offset)”, p. 3066, attribute val

[DR 09-0256]

Attributes	Description
val (Value)	<p>Specifies the value of the blue component. The assigned value is specified as a percentage with 0% indicating minimal blue and 100% indicating maximum blue. Specifies the luminance as expressed by a percentage offset increase or decrease to the input color. Increases never increase the luminance beyond 100%, decreases never decrease the luminance below 0%.</p> <p>[Example: The following manipulates the fill from having RGB value RRGGBB = (00, FF, 00) to value RRGGBB= (00, FF, FF00, 99, 00)</p> <pre>&lt;a:solidFill&gt;   &lt;a:srgbClr val="00FF00"&gt;     &lt;a:blueLumOff val="100.000%-20.000%" /&gt;   &lt;/a:srgbClr&gt; &lt;/a:solidFill&gt;</pre> <p><i>end example]</i></p> <p>...</p>

### 399. §20.1.2.3.23, “red (Red)”, p. 3068, attribute val

[DR 09-0257]

Attributes	Description
------------	-------------

Attributes	Description
val (Value)	<p>Specifies the value of the <a href="#">blue:red</a> component. The assigned value is specified as a percentage with 0% indicating minimal <a href="#">blue:red</a> and 100% indicating maximum <a href="#">blue:red</a>.</p> <p>[Example: The following manipulates the fill from having RGB value RRGGBB = (00, FF, 00) to value RRGGBB= (<a href="#">00, FF, FF</a>, <a href="#">FF, 00, 00</a>)</p> <pre>&lt;a:solidFill&gt;   &lt;a:srgbClr val="00FF00"&gt;     &lt;a:<a href="#">blue:red</a> val="100.000%" /&gt;   &lt;/a:srgbClr&gt; &lt;/a:solidFill&gt;</pre> <p><i>end example]</i></p> <p>...</p>

#### 400. §20.1.2.3.24, “redMod (Red Modulation)”, p. 3069, attribute val

[DR 09-0258]

Attributes	Description
val (Value)	<p><a href="#">Specifies the value of the blue component. The assigned value is specified as a percentage with 0% indicating minimal blue and 100% indicating maximum blue.</a> <a href="#">Specifies the red component as expressed by a percentage relative to the input color component. Increases never increase the red component beyond 100%, decreases never decrease the red component below 0%.</a></p> <p>[Example: The following manipulates the fill from having RGB value RRGGBB = (<a href="#">00, FF, 00</a>, <a href="#">FF, 00, 00</a>) to value RRGGBB= (<a href="#">00, FF, FF</a>, <a href="#">80, 00, 00</a>)</p> <pre>&lt;a:solidFill&gt;   &lt;a:srgbClr val="<a href="#">00FF00FF0000"blue:redMod</a> val="100.000%50.000%" /&gt;   &lt;/a:srgbClr&gt; &lt;/a:solidFill&gt;</pre> <p><i>end example]</i></p> <p>...</p>

#### 401. §20.1.2.3.25, “redOff (Red Offset)”, p. 3070, attribute val

[DR 09-0259]

Attributes	Description
------------	-------------

Attributes	Description
val (Value)	<p>Specifies the value of the blue component. The assigned value is specified as a percentage with 0% indicating minimal blue and 100% indicating maximum blue. Specifies the red component as expressed by a percentage offset increase or decrease to the input color component. Increases never increase the red component beyond 100%, decreases never decrease the red component below 0%.</p> <p>[Example: The following manipulates the fill from having RGB value RRGGBB = (00, FF, 00, 00) to value RRGGBB= (00, FF, FFCC, 00, 00)]</p> <pre>&lt;a:solidFill&gt;   &lt;a:srgbClr val="00FF00FF0000"&gt;     &lt;a:blue redOff val="100.000%-20.000%" /&gt;   &lt;/a:srgbClr&gt; &lt;/a:solidFill&gt;  <i>end example]</i>  ...</pre>

## 402. §20.1.2.3.26, “sat (Saturation)”, p. 3071, attribute val

[DR 09-0260]

Attributes	Description
val (Value)	<p>Specifies the value of the blue component saturation. The assigned value is specified as a percentage with 0% indicating minimal blue saturation and 100% indicating maximum blue saturation.</p> <p>[Example: The following manipulates the fill from having RGB value RRGGBB = (00, FF, 00) to value RRGGBB= (00, FF, FF40, C0, 40)]</p> <pre>&lt;a:solidFill&gt;   &lt;a:srgbClr val="00FF00"&gt;     &lt;a:blue sat val="100.000%50.000%" /&gt;   &lt;/a:srgbClr&gt; &lt;/a:solidFill&gt;  <i>end example]</i>  ...</pre>

## 403. §20.1.2.3.27, “satMod (Saturation Modulation)”, pp. 3071–3072, attribute val

[DR 09-0261]

Attributes	Description
------------	-------------

Attributes	Description
val (Value)	<p>Specifies the value of the blue component. The assigned value is specified as a percentage with 0% indicating minimal blue and 100% indicating maximum blue. Specifies the saturation as expressed by a percentage relative to the input color. Increases never increase the saturation beyond 100%, decreases never decrease the saturation below 0%.</p> <p>[Example: The following manipulates the fill from having RGB value RRGGBB = (00, FF, 00) to value RRGGBB= (00, FF, FF66, 99, 66)</p> <pre>&lt;a:solidFill&gt;   &lt;a:srgbClr val="00FF00"&gt;     &lt;a:blueSatMod val="100.000%20.000%" /&gt;   &lt;/a:srgbClr&gt; &lt;/a:solidFill&gt;</pre> <p><i>end example]</i></p> <p>...</p>

#### 404. §20.1.2.3.28, “satOff (Saturation Offset)”, p. 3072, attribute val

[DR 09-0262]

Attributes	Description
val (Value)	<p>Specifies the value of the blue component. The assigned value is specified as a percentage with 0% indicating minimal blue and 100% indicating maximum blue. Specifies the saturation as expressed by a percentage offset increase or decrease to the input color. Increases never increase the saturation beyond 100%, decreases never decrease the saturation below 0%.</p> <p>[Example: The following manipulates the fill from having RGB value RRGGBB = (00, FF, 00) to value RRGGBB= (00, FF, FF19, E5, 19)</p> <pre>&lt;a:solidFill&gt;   &lt;a:srgbClr val="00FF00"&gt;     &lt;a:blueSatOff val="100.000%-20.000%" /&gt;   &lt;/a:srgbClr&gt; &lt;/a:solidFill&gt;</pre> <p><i>end example]</i></p> <p>...</p>

#### 405. §20.1.2.3.31, “shade (Shade)”, pp. 3076–3077, attribute val

[DR 09-266]

Attributes	Description
------------	-------------

Attributes	Description
val (Value)	<p>Specifies the opacity as expressed by a percentage value.</p> <p>[Example: <del>The following represents a green solid fill which is 50% opaque</del> The following manipulates the fill from having RGB value RRGGBB = (00, FF, 00) to value RRGGBB= (00, BC, 00)</p> <pre>&lt;a:solidFill&gt;   &lt;a:srgbClr val="00FF00"&gt;     &lt;a:<del>alpha</del><u>shade</u> val="50.000%"/&gt;   &lt;/a:srgbClr&gt; &lt;/a:solidFill&gt;  <i>end example]</i>  ...</pre>

#### 406. §20.1.2.3.34, “tint (Tint)”, p. 3081, attribute val

[DR 09-0263]

Attributes	Description
val (Value)	<p>Specifies the <del>opacity</del><u>tint</u> as expressed by a percentage value.</p> <p>[Example: <del>The following represents a green solid fill which is 50% opaque</del> The following manipulates the fill from having RGB value RRGGBB = (00, FF, 00) to value RRGGBB= (BC, FF, BC)</p> <pre>&lt;a:solidFill&gt;   &lt;a:srgbClr val="00FF00"&gt;     &lt;a:<del>alpha</del><u>tint</u> val="50.000%"/&gt;   &lt;/a:srgbClr&gt; &lt;/a:solidFill&gt;  <i>end example]</i>  ...</pre>

#### 407. §20.1.3.7, “wavAudioFile (Audio from WAV File)”, p. 3089, attribute embed

[DR 09-0080]

Change “... file. [Note: ...” to “... file. [Note: ...”

#### 408. §20.1.5.5, “camera (Camera)”, p. 3153

[DR 08-0003]

Attributes	Description
------------	-------------

Attributes	Description
zoom (Zoom)	<pre>... &lt;a:camera prst="perspectiveContrastingRightFacing"     fov="6900000" zoom="<u>200000200%</u>"&gt;     &lt;a:rot lat="1200000" lon="18000000" rev="1200000"/&gt; &lt;/a:camera&gt; ...</pre>

#### 409. §20.1.10.46, “ST\_PositivePercentage (Positive Percentage Value with Sign)”, p. 3300

[DR 08-0002]

#### 410. §20.4.2.3, “anchor (Anchor for Floating DrawingML Object)”, p. 3462-3467

[DR 09-0104]

Attributes	Description
allowOverlap (Allow Objects to Overlap)	<pre>...</pre> <p>If this element is omitted on a given DrawingML object, then overlap shall not be allowed between a DrawingML object which intersects another DrawingML object displayed at the same location.</p>
behindDoc (Display Behind Document Text)	<pre>...</pre> <p>If this attribute is omitted, then the parent DrawingML object shall be displayed in front of the text content of the document in cases of overlapping.</p>
layoutInCell (Layout In Table Cell)	<pre>...</pre> <p>If this attribute is omitted, then its default value shall be considered to be false.</p>
locked (Lock Anchor)	<pre>...</pre> <p>If this attribute is omitted, then the anchor shall not be locked for the parent DrawingML object (i.e. a default value of false).</p>

#### 411. §21.1.2.2.2, “defPPr (Default Paragraph Style)”, p. 3569-3570, attribute rtl

[DR 09-0080]

Change “[Example: Consider …]” to “[Example: Consider …]”

Change “... <a:t> تجربة </a:t> ...” to “... <a:t> تجربة </a:t> ...”

## 412. §21.1.2.2.7, “pPr (Text Paragraph Properties)”, p. 3587–3570, attribute rtl

[DR 09-0080]

Change “[Example: Consider …]” to “[Example: Consider …]”

Change “... <a:t> تجربة </a:t> ...” to “... <a:t> تجربة </a:t> ...”

## 413. §21.1.2.3.1, “cs (Complex Script Font)”, pp. 3598–3599

[DR 09-0054]

Attributes	Description
pitchFamily (Similar Font Family)	<p>Specifies the font pitch as well as the font family for the corresponding font. Because the value of this attribute is determined by an octet value <del>byte variable</del> this value shall be interpreted as follows:</p> <p>...</p> <p><a href="#">[Note: Although the attribute name is pitchFamily, the integer value of this attribute specifies the font family with higher 4 bits and the font pitch with lower 4 bits. end note]</a></p> <p>The possible values for this attribute are defined by the W3C XML Schema byte datatype.</p>

## 414. §21.1.2.3.3, “ea (East Asian Font)”, pp. 3606–3607

[DR 09-0054]

Attributes	Description
pitchFamily (Similar Font Family)	<p>Specifies the font pitch as well as the font family for the corresponding font. Because the value of this attribute is determined by an octet value <del>byte variable</del> this value shall be interpreted as follows:</p> <p>...</p> <p><a href="#">[Note: Although the attribute name is pitchFamily, the integer value of this attribute specifies the font family with higher</a></p>

[4 bits and the font pitch with lower 4 bits. end note\]](#)

The possible values for this attribute are defined by the W3C XML Schema byte datatype.

#### 415. §21.1.2.3.7, “latin (Latin Font)”, pp. 3614–3615

[DR 09-0054]

Attributes	Description
pitchFamily (Similar Font Family)	<p>Specifies the font pitch as well as the font family for the corresponding font. Because the value of this attribute is determined by an octet value <del>byte variable</del> this value shall be interpreted as follows:</p> <p>...</p> <p><u><a href="#">[Note: Although the attribute name is pitchFamily, the integer value of this attribute specifies the font family with higher 4 bits and the font pitch with lower 4 bits. end note]</a></u></p> <p>The possible values for this attribute are defined by the W3C XML Schema byte datatype.</p>

#### 416. §21.1.2.3.10, “sym (Symbol Font)”, pp. 3623–3624

[DR 09-0054]

Attributes	Description
pitchFamily (Similar Font Family)	<p>Specifies the font pitch as well as the font family for the corresponding font. Because the value of this attribute is determined by an octet value <del>byte variable</del> this value shall be interpreted as follows:</p> <p>...</p> <p><u><a href="#">[Note: Although the attribute name is pitchFamily, the integer value of this attribute specifies the font family with higher 4 bits and the font pitch with lower 4 bits. end note]</a></u></p>

	The possible values for this attribute are defined by the W3C XML Schema byte datatype.
--	---

#### 417. §21.1.2.4.6, “buFont (Specified)”, p. 3638-3639

[DR 09-0054]

Attributes	Description
pitchFamily (Similar Font Family)	<p>Specifies the font pitch as well as the font family for the corresponding font. Because the value of this attribute is determined by an octet value <del>byte-variable</del> this value shall be interpreted as follows:</p> <p>...</p> <p><u>[Note: Although the attribute name is pitchFamily, the integer value of this attribute specifies the font family with higher 4 bits and the font pitch with lower 4 bits. end note]</u></p> <p>The possible values for this attribute are defined by the W3C XML Schema byte datatype.</p>

#### 418. §21.1.2.4.9, “buSzPct (Bullet Size Percentage)”, pp. 3640-3641

[DR 08-0008]

This element specifies the size in percentage of the surrounding text to be used on bullet characters within a given paragraph. ~~The size is specified using a percentage where 1000 is equal to 1 percent of the font size and 100000 is equal to 100 percent font of the font size.~~

[Example: Consider the DrawingML shown below.

```

<p:txBody>
  ...
  <a:p>
    <a:pPr ...>
      <a:buSzPct val="111000111%" />
    </a:pPr>
    ...
    <a:t>Bullet 1</a:t>
    ...
  </a:p>
  ...
</p:txBody>
```

The size of the above bullet follows the text size in that it is always rendered at 111% the size of the text within the given text run. This is specified by val="111000111%", with a restriction on the values not being less than 25% or more than 400%. ~~A value of 100000 is equal to 100%, similarly a value of 1000 is equal to 1%.~~ This percentage size should only apply to the actual bullet character and not to the text within the bullet. *end example]*

...

Attributes	Description
val (Value)	<p>Specifies the percentage of the text size that this bullet should be. <del>It is specified here in terms of 100% being equal to 100000 and 1% being specified in increments of 1000.</del> This attribute should not be lower than 25%, <del>or 25000</del> and not be higher than 400%, <del>or 400000</del>.</p> <p>The possible values for this attribute are defined by the ST_TextBulletSizePercent simple type (\$xx).</p>

#### 419. §21.1.2.4.13, “lvl1pPr (List Level 1 Text Style)”, p. 3651–3652, attribute rtl

[DR 09-0080]

Change “[Example: Consider …]” to “[Example: Consider …]”

Change “... <a:t> تجربة </a:t> ...” to “... <a:t> تجربة </a:t> ...”

#### 420. §21.1.2.4.14, “lvl2pPr (List Level 2 Text Style)”, p. 3660–3661, attribute rtl

[DR 09-0080]

Change “[Example: Consider …]” to “[Example: Consider …]”

Change “... <a:t> تجربة </a:t> ...” to “... <a:t> تجربة </a:t> ...”

#### 421. §21.1.2.4.15, “lvl3pPr (List Level 3 Text Style)”, p. 3669, attribute rtl

[DR 09-0080]

Change “[Example: Consider …]” to “[Example: Consider …]”

Change “... <a:t> تجربة </a:t> ...” to “... <a:t> تجربة </a:t> ...”

#### 422. §21.1.2.4.16, “lvl4pPr (List Level 4 Text Style)”, p. 3677–3678, attribute rtl

[DR 09-0080]

Change “[Example: Consider …]” to “[Example: Consider …]”

Change “... <a:t> تجربة </a:t> ...” to “... <a:t> تجربة </a:t> ...”

#### 423. §21.1.2.4.17, “lvl5pPr (List Level 5 Text Style)”, p. 3686, attribute rtl

[DR 09-0080]

Change “[Example: Consider …]” to “[Example: Consider …]”

Change “... <a:t> تجربة </a:t> ...” to “... <a:t> تجربة </a:t> ...”

#### 424. §21.1.2.4.18, “lvl6pPr (List Level 6 Text Style)”, p. 3694–3695, attribute rtl

[DR 09-0080]

Change “[Example: Consider …]” to “[Example: Consider …]”

Change “... <a:t> تجربة </a:t> ...” to “... <a:t> تجربة </a:t> ...”

#### 425. §21.1.2.4.19, “lvl7pPr (List Level 7 Text Style)”, p. 3703, attribute rtl

[DR 09-0080]

Change “[Example: Consider …]” to “[Example: Consider …]”

Change “... <a:t> تجربة </a:t> ...” to “... <a:t> تجربة </a:t> ...”

#### 426. §21.1.2.4.20, “lvl8pPr (List Level 8 Text Style)”, p. 3711–3712, attribute rtl

[DR 09-0080]

Change “[Example: Consider …]” to “[Example: Consider …]”

Change “... <a:t> تجربة </a:t> ...” to “... <a:t> تجربة </a:t> ...”

#### 427. §21.1.2.4.21, “lvl9pPr (List Level 9 Text Style)”, p. 3720, attribute rtl

[DR 09-0080]

Change “[Example: Consider …]” to “[Example: Consider …]”

Change “... <a:t> تجربة </a:t> ...” to “... <a:t> تجربة </a:t> ...”

**428. §21.2.2.12, “backward (Backward)”, p. 3763**

[DR 09-0001]

This element specifies the number of categories (or units on a scatter chart) that the trend line extends before the data for the series that is being trended. On [scatter and](#) non-scatter charts, the value shall be [any non-negative value 0 or 0.5](#).

**429. §21.2.2.59, “evenFooter (Even Footer)”, p. 3789, new attribute**

[DR 09-0026]

<u>Attributes</u>	<u>Description</u>
<a href="#">xml:space (Content Contains Significant Whitespace)</a>  <u>Namespace:</u> <a href="http://www.w3.org/XML/1998/namespace">http://www.w3.org/XML/1998/namespace</a>	<a href="#">Specifies how white space should be handled for the contents of this element using the W3C space preservation rules.</a>  <a href="#">The possible values for this attribute are defined by §2.10 of the XML 1.0 specification.</a>

**430. §21.2.2.60, “evenHeader (Even Header)”, p. 3789, new attribute**

[DR 09-0026]

<u>Attributes</u>	<u>Description</u>
<a href="#">xml:space (Content Contains Significant Whitespace)</a>  <u>Namespace:</u> <a href="http://www.w3.org/XML/1998/namespace">http://www.w3.org/XML/1998/namespace</a>	<a href="#">Specifies how white space should be handled for the contents of this element using the W3C space preservation rules.</a>  <a href="#">The possible values for this attribute are defined by §2.10 of the XML 1.0 specification.</a>

**431. §21.2.2.63, “externalData (External Data Relationship)”, p. 3790**

[DR 09-0013]

Attributes	Description
id (Relationship Reference)  Namespace: .../officeDocument/2006/relationships	Specifies the relationship ID for the relationship for this chart. The relationship explicitly targeted by this attribute shall <u>either</u> be of type <a href="http://schemas.openxmlformats.org/officeDocument/2006/relationships/package">http://schemas.openxmlformats.org/officeDocument/2006/relationships/package</a> <u>or</u> <a href="http://schemas.openxmlformats.org/officeDocument/2006/relationships/oleObject">http://schemas.openxmlformats.org/officeDocument/2006/relationships/oleObject</a> .  The possible values for this attribute are defined by the ST_RelationshipId simple type (§xx).

#### 432. §21.2.2.66, “firstFooter (First Footer)”, p. 3792, new attribute

[DR 09-0026]

Attributes	Description
<a href="#">xml:space (Content Contains Significant Whitespace)</a>  Namespace: <a href="http://www.w3.org/XML/1998/namespaces">http://www.w3.org/XML/1998/namespaces</a>	<u>Specifies how white space should be handled for the contents of this element using the W3C space preservation rules.</u>  <u>The possible values for this attribute are defined by §2.10 of the XML 1.0 specification.</u>

#### 433. §21.2.2.67, “firstHeader (First Header)”, p. 3792, new attribute

[DR 09-0026]

Attributes	Description
<a href="#">xml:space (Content Contains Significant Whitespace)</a>  Namespace: <a href="http://www.w3.org/XML/1998/namespaces">http://www.w3.org/XML/1998/namespaces</a>	<u>Specifies how white space should be handled for the contents of this element using the W3C space preservation rules.</u>  <u>The possible values for this attribute are defined by §2.10 of the XML 1.0 specification.</u>

#### 434. §21.2.2.73, “forward (Forward)”, p. 3795

[DR 09-0001]

This element specifies the number of categories (or units on a scatter chart) that the trend line extends after the data for the series that is being trended. On scatter and non-scatter charts, the value shall be any non-negative value~~a multiple of 0.5~~.

**435. §21.2.2.124, “oddFooter (Odd Footer)”, p. 3818, new attribute**

[DR 09-0026]

<u>Attributes</u>	<u>Description</u>
<u>xml:space (Content Contains Significant Whitespace)</u> <u>Namespace:</u> <a href="http://www.w3.org/XML/1998/namespaces">http://www.w3.org/XML/1998/namespaces</a>	<u>Specifies how white space should be handled for the contents of this element using the W3C space preservation rules.</u> <u>The possible values for this attribute are defined by §2.10 of the XML 1.0 specification.</u>

**436. §21.2.2.125, “oddHeader (Odd Header)”, p. 3818, new attribute**

[DR 09-0026]

<u>Attributes</u>	<u>Description</u>
<u>xml:space (Content Contains Significant Whitespace)</u> <u>Namespace:</u> <a href="http://www.w3.org/XML/1998/namespaces">http://www.w3.org/XML/1998/namespaces</a>	<u>Specifies how white space should be handled for the contents of this element using the W3C space preservation rules.</u> <u>The possible values for this attribute are defined by §2.10 of the XML 1.0 specification.</u>

**437. §21.2.2.134, “pageSetup (Page Setup)”, p. 3822**

[DR 09-0095]

```
<pageSetup blackAndWhite="true" draft="false" paperHeight="1189mm"
paperWidth="841mm" paperUnits="mm"/>
```

**438. §21.2.2.134, “pageSetup (Page Setup)”, p. 3823, attribute paperSize**

[DR 09-0096]

<u>Attributes</u>	<u>Description</u>
<u>paperSize (Page Paper Size)</u>	Specifies the paper size according to the following table. ...

**439. §21.2.2.134, “pageSetup (Page Setup)”, p. 3825**

[DR 09-0095]

When paperHeight, and paperWidth, ~~and paperUnits~~ are specified, paperSize should be ignored.

**440. §21.2.2.220, “userShapes (User Shapes)”, p. 3867**

[DR 09-0083]

This element shall specify the shapes drawn on top of the chart

<a href="#"><u>Parent Elements</u></a>
<a href="#"><u>Root element of Chart Drawing Part</u></a>

**441. §21.2.3.18, “ST\_HoleSize (Hole Size)”, p. 3884**

[DR 09-0002]

This simple type specifies that its contents contain an integer between 10 and 90, whose contents are a percentage.

...

- This simple type has a minimum value of greater than or equal to 10.

**442. §21.2.3.33, “ST\_Period (Period)”, p. 3892**

[DR 09-0003]

This simple type specifies that its contents contain an integer greater than or equal to 2~~between 2 and 255~~.

This simple type's contents are a restriction of the W3C XML Schema unsignedIntByte datatype.

This simple type also specifies the following restrictions:

- This simple type has a minimum value of greater than or equal to 2.
- ~~This simple type has a maximum value of less than or equal to 255.~~

**443. §21.2.3.33, “ST\_Period (Period)”, p. 3892, enumeration value auto**

[DR 09-0004]

Enumeration Value	Description
<a href="#"><u>auto (Auto)</u></a>	<a href="#"><u>Specifies an application-specific marker shall be drawn at each data point.</u></a>

**444. §21.2.3.34, “ST\_Perspective (Perspective)”, p. 3892**

[DR 09-0005]

This simple type specifies that its contents contain an integer between 0 and 240~~100~~, whose unit is one-half degrees~~contents are a percentage~~.

**445. §21.2.3.44, “ST\_Skip (Skip)”, p. 3897**

[DR 09-0006]

This simple type's contents are a restriction of the W3C XML Schema unsignedIntShort datatype.

**446. §22.1.2.3, “aln (Alignment)”, p. 4074**

[DR 09-0148]

This element ... emulator. When 1 or true, this operator ...

**447. §22.1.2.5, “argPr (Argument Properties)”, p. 4078**

[DR 09-0149]

*{In the next reprint or revision, no page breaks will be allowed within this table (and the editor will try to inhibit them for any given row of any table, as appropriate).}*

**448. §22.1.2.18, “cGp (Matrix Column Gap)”, p. 4094**

[DR 09-0148]

This element ... default value is 0 (which ...)

**449. §22.1.2.19, “cGpRule (Matrix Column Gap Rule)”, p. 4095 and many others**

[DR 09-0150]

This element specifies the type of gap (horizontal spacing) between columns of a matrix; the default is 0. Horizontal spacing units can be ems or points (stored as twips).

**450. §22.1.2.22, “cSp (Minimum Matrix Column Width)”, p. 4099**

[DR 09-0150]

... If this element is omitted, the default minimum column width is 0. ... Therefore, a spacing of 1 point will be set by a cSp value of 20. ...

**451. §22.1.2.22, “cSp (Minimum Matrix Column Width)”, p. 4100**

[DR 09-0151]

[Example: The following XML specifies that there should never be fewer than 6 pts. (120 twips) between adjacent column edges of the matrix:

**452. §22.1.2.26, “deg (Degree)”, pp. 4104–4107**

[DR 09-0011]

Child Elements	Subclause
<a href="#">customXml (Inline-Level Custom XML Element)</a>	<a href="#">§17.5.1.3</a>
<a href="#">fldSimple (Simple Field)</a>	<a href="#">§17.16.19</a>
<a href="#">hyperlink (Hyperlink)</a>	<a href="#">§17.16.22</a>
<a href="#">sdt (Inline-Level Structured Document Tag)</a>	<a href="#">§17.5.2.31</a>
<a href="#">smartTag (Inline-Level Smart Tag)</a>	<a href="#">§17.5.1.9</a>

**453. §22.1.2.28, “den (Denominator)”, pp. 4108–4110**

[DR 09-0011]

Child Elements	Subclause
<a href="#">customXml (Inline-Level Custom XML Element)</a>	<a href="#">§17.5.1.3</a>
<a href="#">fldSimple (Simple Field)</a>	<a href="#">§17.16.19</a>
<a href="#">hyperlink (Hyperlink)</a>	<a href="#">§17.16.22</a>
<a href="#">sdt (Inline-Level Structured Document Tag)</a>	<a href="#">§17.5.2.31</a>
<a href="#">smartTag (Inline-Level Smart Tag)</a>	<a href="#">§17.5.1.9</a>

**454. §22.1.2.32, “e (Element (Argument))”, p. 4114**

[DR 09-0152]

[Example: For example, the func  $\lim_{n \rightarrow \infty} \frac{x_n}{x_{\bar{n}}}$  has fName  $\lim$  and e  $x_n$ :

**455. §22.1.2.32, “e (Element)”, pp. 4115–4117**

[DR 09-0011]

Child Elements	Subclause
<a href="#">customXml (Inline-Level Custom XML Element)</a>	<a href="#">§17.5.1.3</a>
<a href="#">fldSimple (Simple Field)</a>	<a href="#">§17.16.19</a>
<a href="#">hyperlink (Hyperlink)</a>	<a href="#">§17.16.22</a>
<a href="#">sdt (Inline-Level Structured Document Tag)</a>	<a href="#">§17.5.2.31</a>
<a href="#">smartTag (Inline-Level Smart Tag)</a>	<a href="#">§17.5.1.9</a>

**456. §22.1.2.37, “fName (Function Name)”, p. 4122**

[DR 09-0152]

[Example: As an example, the func  $\lim_{n \rightarrow \infty} \underline{x_n} - \overline{x_n}$  has fName lim and e  $x_n$ :

#### 457. §22.1.2.37, “fName (Function Name)”, pp. 4123–4125

[DR 09-0011]

Child Elements	Subclause
<a href="#">customXml (Inline-Level Custom XML Element)</a>	<a href="#">§17.5.1.3</a>
<a href="#">fldSimple (Simple Field)</a>	<a href="#">§17.16.19</a>
<a href="#">hyperlink (Hyperlink)</a>	<a href="#">§17.16.22</a>
<a href="#">sdt (Inline-Level Structured Document Tag)</a>	<a href="#">§17.5.2.31</a>
<a href="#">smartTag (Inline-Level Smart Tag)</a>	<a href="#">§17.5.1.9</a>

#### 458. §22.1.2.39, “func (Function Apply Object)”, p. 4126

[DR 09-0152]

As an example, the func  $\lim_{n \rightarrow \infty} \underline{x_n} - \overline{x_n}$  has fName lim and e  $x_n$ :

#### 459. §22.1.2.52, “lim (Limit)”, pp. 4138–4139

[DR 09-0011]

Child Elements	Subclause
<a href="#">customXml (Inline-Level Custom XML Element)</a>	<a href="#">§17.5.1.3</a>
<a href="#">fldSimple (Simple Field)</a>	<a href="#">§17.16.19</a>
<a href="#">hyperlink (Hyperlink)</a>	<a href="#">§17.16.22</a>
<a href="#">sdt (Inline-Level Structured Document Tag)</a>	<a href="#">§17.5.2.31</a>
<a href="#">smartTag (Inline-Level Smart Tag)</a>	<a href="#">§17.5.1.9</a>

#### 460. §22.1.2.75, “num (Numerator)”, pp. 4171–4172

[DR 09-0011]

Child Elements	Subclause
<a href="#">customXml (Inline-Level Custom XML Element)</a>	<a href="#">§17.5.1.3</a>
<a href="#">fldSimple (Simple Field)</a>	<a href="#">§17.16.19</a>
<a href="#">hyperlink (Hyperlink)</a>	<a href="#">§17.16.22</a>
<a href="#">sdt (Inline-Level Structured Document Tag)</a>	<a href="#">§17.5.2.31</a>
<a href="#">smartTag (Inline-Level Smart Tag)</a>	<a href="#">§17.5.1.9</a>

**461. §22.1.2.77, “oMath (Office Math)”, pp. 4174–4176**

[DR 09-0011]

Child Elements	Subclause
<a href="#">customXml (Inline-Level Custom XML Element)</a>	<a href="#">§17.5.1.3</a>
<a href="#">fldSimple (Simple Field)</a>	<a href="#">§17.16.19</a>
<a href="#">hyperlink (Hyperlink)</a>	<a href="#">§17.16.22</a>
<a href="#">sdt (Inline-Level Structured Document Tag)</a>	<a href="#">§17.5.2.31</a>
<a href="#">smartTag (Inline-Level Smart Tag)</a>	<a href="#">§17.5.1.9</a>

**462. §22.1.2.83, “plcHide (Hide Placeholders (Matrix))”, p. 4181**

[DR 09-0154]

{The six placeholders in the left matrix are now visible, as follows:}

$$\begin{pmatrix} 1 & \square & \square \\ \square & 1 & \square \\ \square & \square & 1 \end{pmatrix} \begin{pmatrix} 1 & & \\ & 1 & \\ & & 1 \end{pmatrix}$$

**463. §22.1.2.95, “sepChr (Delimiter Separator Character)”, p. 4193**

[DR 09-0153]

[Example: Examples of d, each with a different sepChr, are:  $(a_1|a_2)(a_1:a_2)(a_1;a_2)$ . The following example sets describes the COLON (:) as the separator character:  
if ::

```
<m:dPr>
  <m:sepChr val="&#0058;" />
</m:dPr>
```

[end example]

**464. §22.1.2.105, “sSup (Superscript Object)”, p. 4202**

[DR 09-0148]

This element ... scr placed above and ...

**465. §22.1.2.112, “sub (Subscript (Pre-Sub-Superscript))”, pp. 4209–4210**

[DR 09-0011]

Child Elements	Subclause
<a href="#">customXml (Inline-Level Custom XML Element)</a>	<a href="#">§17.5.1.3</a>

Child Elements	Subclause
<a href="#">fldSimple (Simple Field)</a>	<a href="#">§17.16.19</a>
<a href="#">hyperlink (Hyperlink)</a>	<a href="#">§17.16.22</a>
<a href="#">sdt (Inline-Level Structured Document Tag)</a>	<a href="#">§17.5.2.31</a>
<a href="#">smartTag (Inline-Level Smart Tag)</a>	<a href="#">§17.5.1.9</a>

#### 466. §22.1.2.114, “**sup** (Superscript (Superscript object))”, pp. 4212–4213

[DR 09-0011]

Child Elements	Subclause
<a href="#">customXml (Inline-Level Custom XML Element)</a>	<a href="#">§17.5.1.3</a>
<a href="#">fldSimple (Simple Field)</a>	<a href="#">§17.16.19</a>
<a href="#">hyperlink (Hyperlink)</a>	<a href="#">§17.16.22</a>
<a href="#">sdt (Inline-Level Structured Document Tag)</a>	<a href="#">§17.5.2.31</a>
<a href="#">smartTag (Inline-Level Smart Tag)</a>	<a href="#">§17.5.1.9</a>

#### 467. §22.5.2.2, “**schemaRef** (Associated XML Schema)”, p. 4262, attribute **uri**

[DR 09-0147]

Attributes	Description
uri (Target Namespace of Associated XML Schema)	<p>...</p> <p>The uri attribute specifies the target namespace of each XML schema reference:</p> <ul style="list-style-type: none"> <li>• <a href="http://www.example.com/schema1">http://www.example.com/schema1</a></li> <li>• <a href="http://www.example.com/schema2">http://www.example.com/schema2</a></li> </ul> <p>...</p>

#### 468. §22.6.2.5, “**Author** (**Author**)”, p. 4269, new attribute

[DR 09-0026]

Attributes	Description
<a href="#">xml:space (Content Contains Significant Whitespace)</a>  <u>Namespace:</u> <a href="http://www.w3.org/XML/1998/namespace">http://www.w3.org/XML/1998/namespace</a>	<p><a href="#">Specifies how white space should be handled for the contents of this element using the W3C space preservation rules.</a></p> <p><a href="#">The possible values for this attribute are defined by §2.10 of the XML 1.0 specification.</a></p>

## 469. §22.9.2.1, “ST\_CalendarType (Calendar Types)”, p. 4319, attribute hebrew

[DR 09-0088]

Enumeration Value	Description
hebrew (Hebrew)	Specifies that the Hebrew lunar calendar, as described by the Gauss formula for Passover [ <a href="#">Har'El</a> , <a href="#">Zvi CITATION</a> ] and The Complete Restatement of Oral Law (Mishneh Torah), shall be used.

## 470. §22.9.2.13, “ST\_String (String)”, p. 4329

[DR 08-0014]

This simple type specifies that its contents contains a string. ~~The contents of this string are interpreted based on the context of the parent XML element.~~

*[Example: Consider the following WordprocessingML fragment:*

```
<w:pPr>
  <w:pStyle w:val="heading1" />
</w:pPr>
```

~~The value of the val attribute is the ID of the associated paragraph style's styleId. However, consider the following fragment:~~

```
<w:sdtPr>
  <w:alias w:val="SDT_Title_Example" />
  ...
</w:sdtPr>
```

~~In this case, the decimal number in the val attribute is the caption of the parent structured document tag. In each case, the value is of type ST\_String, and therefore must be interpreted in the context of the parent element. end example}~~

This simple type's contents are a restriction of the W3C XML Schema string datatype.

## 471. §22.9.2.13, “ST\_String (String)”, p. 4329

[DR 09-0227]

*[Example: Consider the following WordprocessingML fragment:*

```
<w:pPr>
  <w:pStyle w:val="Heading1heading1" />
</w:pPr>
```

**472. §22.9.2.15, “ST\_UniversalMeasure (Universal Measurement)”, p. 4332**

[DR 09-0158]

Unit Identifier	Definition
cm	As defined in ISO 31.
mm	As defined in ISO 31.
in	1_in = 2.54_cm (informative)
pt	1_pt = 1/72_in (informative)
pc	1_pc = 12_pt (informative)
pi	1_pi = 12_pt (informative)

**473. §A.1, “WordprocessingML”, p. 4345**

[DR 09-0276]

[This schema is available in the file wml.xsd.](#)**474. §A.1, “WordprocessingML”, p. 4378, lines 1780–1786**

[DR 09-0017, DR 09-0018]

```

<xsd:group name="EG_RPrMath">
  <xsd:choice>
    <xsd:group ref="EG_RPr"/>
    <xsd:element name="ins" type="CT_RPrChangeCT_MathCtrlIns"/>
    <xsd:element name="del" type="CT_RPrChangeCT_MathCtrlDel"/>
  </xsd:choice>
</xsd:group>
<xsd:complexType name="CT_MathCtrlIns">
  <xsd:complexContent>
    <xsd:extension base="CT_TrackChange">
      <xsd:choice minOccurs="0">
        <xsd:element name="del" type="CT_RPrChange" minOccurs="1"/>
        <xsd:element name="rPr" type="CT_RPr" minOccurs="1"/>
      </xsd:choice>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
<xsd:complexType name="CT_MathCtrlDel">
  <xsd:complexContent>
    <xsd:extension base="CT_TrackChange">
      <xsd:choice minOccurs="0">
        <xsd:element name="rPr" type="CT_RPr" minOccurs="1"/>
      </xsd:choice>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>

```

## 475. §A.1, “WordprocessingML”, new type

[DR 09-0011]

```

<xsd:group name="EG_PContentMath">
  <xsd:choice>
    <xsd:group ref="EG_PContentBase" minOccurs="0" maxOccurs="unbounded" />
    <xsd:group ref="EG_ContentRunContentBase" minOccurs="0"
      maxOccurs="unbounded" />
  </xsd:choice>
</xsd:group>
<xsd:group name="EG_PContentBase">
  <xsd:choice>
    <xsd:element name="customXml" type="CT_CustomXmlRun"/>
    <xsd:element name="fldSimple" type="CT_SimpleField" minOccurs="0"
      maxOccurs="unbounded"/>
    <xsd:element name="hyperlink" type="CT_Hyperlink"/>
  </xsd:choice>
</xsd:group>
<xsd:group name="EG_ContentRunContentBase">
  <xsd:choice>
    <xsd:element name="smartTag" type="CT_SmartTagRun"/>
    <xsd:element name="sdt" type="CT_SdtRun"/>
    <xsd:group ref="EG_RunLevelElts" minOccurs="0" maxOccurs="unbounded" />
  </xsd:choice>
</xsd:group>

```

## 476. §A.2, “SpreadsheetML”, p. 4410

[DR 09-0276]

This schema is available in the file sml.xsd.

## 477. §A.2, “SpreadsheetML”, p. 4411, lines 84–88

[DR 09-0233]

```

<xsd:complexType name="CT_DynamicFilter">
  <xsd:attribute name="type" type="ST_DynamicFilterType" use="required"/>
  <xsd:attribute name="val" type="xsd:double" use="optional"/>
  <xsd:attribute name="valIso" type="xsd:dateTime" use="optional"/>
  <xsd:attribute name="maxValIso" type="xsd:dateTime" use="optional"/>
</xsd:complexType>

```

## 478. §A.2, “SpreadsheetML”, p. 4482, lines 3822–3829

[DR 09-0010]

```

<xsd:complexType name="CT_ExternalLink">
  <xsd:choice>
    ...
    <xsd:element name="oleLink" type="CT_OleLink" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="extLst" minOccurs="0" type="CT_ExtensionList"/>
  </xsd:choice>
  <xsd:element name="extLst" minOccurs="0" type="CT_ExtensionList"/>
</xsd:complexType>

```

#### 479. §A.3, “PresentationML”, p. 3394

[DR 09-0276]

[This schema is available in the file pml.xsd.](#)

#### 480. §A.3, “PresentationML”, p. 4518, lines 1278-1286

[DR 09-0242]

```

<xsd:complexType name="CT_GraphicalObjectFrame">
  <xsd:sequence>
    ...
  </xsd:sequence>
  <xsd:attribute name="bwMode" type="a:ST_BlackWhiteMode" use="optional"/>
</xsd:complexType>

```

#### 481. §A.4.1, “DrawingML - Main”, p. 4525

[DR 09-0276]

[This schema is available in the file dml-main.xsd.](#)

#### 482. §A.4.1, “DrawingML - Main”, p. 4525, lines 17-18

[DR 09-0277]

```

<xsd:import
  namespace="http://schemas.openxmlformats.org/drawingml/2006/compatibility"
  schemaLocation="dml-compatibility.xsd"/>

```

#### 483. §A.4.1, “DrawingML - Main”, p. 4546, lines 1103-1110

[DR 08-0002]

```
<xsd:complexType name="CT_Camera">
  ...
  <xsd:attribute name="zoom" type="ST_PositivePercentage"
    use="optional" default="100000100%" />
</xsd:complexType>
```

#### 484. §A.4.2, “DrawingML – Picture”, p. 4582

[DR 09-0276]

This schema is available in the file dml-picture.xsd.

#### 485. §A.4.3, “DrawingML - Locked Canvas”, p. 4583

[DR 09-0276]

This schema is available in the file dml-lockedCanvas.xsd.

#### 486. §A.4.4, “DrawingML - WordprocessingML Drawing”, p. 4583

[DR 09-0276]

This schema is available in the file dml-spreadsheetDrawing.xsd.

#### 487. §A.4.5, “DrawingML - SpreadsheetML Drawing”, p. 4586

[DR 09-0276]

This schema is available in the file dml-wordprocessingDrawing.xsd.

#### 488. §A.5.1, “DrawingML – Charts”, p. 4590

[DR 09-0276]

This schema is available in the file dml-chart.xsd.

#### 489. §A.5.1, “DrawingML - Charts”, p. 4596, lines 309–317

[DR 09-0002]

```
<xsd:simpleType name="ST_HoleSize">
  <xsd:restriction base="xsd:unsignedByte">
    <xsd:minInclusive value="10"/>
    <xsd:maxInclusive value="90"/>
  </xsd:restriction>
</xsd:simpleType>
```

## 490. §A.5.1, “Drawing ML - Charts”, p. 4598, lines 424–438

[DR 09-0004]

```
<xsd:simpleType name="ST_MarkerStyle">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="circle"/>
    ...
    <xsd:enumeration value="x"/>
    <xsd:enumeration value="auto"/>
  </xsd:restriction>
</xsd:simpleType>
```

## 491. §A.5.1, “Drawing ML - Charts”, p. 4599, lines 493–498

[DR 09-0003]

```
<xsd:simpleType name="ST_Period">
  <xsd:restriction base="xsd:unsignedByte">
    <xsd:minInclusive value="2"/>
    <xsd:maxInclusive value="255"/>
  </xsd:restriction>
</xsd:simpleType>
```

## 492. §A.5.1, “Drawing ML - Charts”, p. 4609, lines 1024–1028

[DR 09-0006]

```
<xsd:simpleType name="ST_Skip">
  <xsd:restriction base="xsd:unsignedInt">
    <xsd:minInclusive value="1"/>
  </xsd:restriction>
</xsd:simpleType>
```

## 493. §A.5.2, “DrawingML - Chart Drawing”, p. 4617

[DR 09-0276]

[This schema is available in the file dml-chartDrawing.xsd.](#)

#### 494. §A.5.3, “DrawingML – Diagrams”, p. 4620

[DR 09-0276]

[This schema is available in the file dml-diagram.xsd.](#)

#### 495. §A.6.1, “Math”, p. 4641

[DR 09-0276]

[This schema is available in the file shared-math.xsd.](#)

#### 496. §A.6.1, “Math”, p. 4650, lines 488–493

[DR 09-0011]

```
<xsd:group name="EG_0MathElements">
  <xsd:choice>
    <xsd:group ref="EG_0MathMathElements"/>
    <xsd:group ref="w:EG_RunLevelElts w:EG_PContentMath"/>
  </xsd:choice>
</xsd:group>
```

#### 497. §A.6.2, “Extended Properties”, p. 4652

[DR 09-0276]

[This schema is available in the file shared-documentPropertiesExtended.xsd.](#)

#### 498. §A.6.3, “Custom Properties”, p. 4653

[DR 09-0276]

[This schema is available in the file shared-documentPropertiesCustom.xsd.](#)

#### 499. §A.6.4, “Variant Types”, p. 4654

[DR 09-0276]

[This schema is available in the file shared-documentPropertiesVariantTypes.xsd.](#)

#### 500. §A.6.5, “Custom XML Data Properties”, p. 4658

[DR 09-0276]

[This schema is available in the file shared-customXmlDataProperties.xsd.](#)

## 501. §A.6.6, “Bibliography”, p. 4658

[DR 09-0276]

[This schema is available in the file shared-bibliography.xsd.](#)

## 502. §A.6.7, “Additional Characteristics”, p. 4661

[DR 09-0276]

[This schema is available in the file shared-additionalCharacteristics.xsd.](#)

## 503. §A.6.8, “Office Document Relationships”, p. 4662

[DR 09-0276]

[This schema is available in the file shared-relationshipReference.xsd.](#)

## 504. §A.6.9, “Shared Simple Types”, p. 4662

[DR 09-0276]

[This schema is available in the file shared-commonSimpleTypes.xsd.](#)

## 505. §A.7, “Custom XML Schema References”, p. 4665

[DR 09-0276]

[This schema is available in the file shared-customXmlSchemaProperties.xsd.](#)

## 506. §B.1, “WordprocessingML”, p. 4667

[DR 09-0276]

[This schema is available in the file wml.rnc.](#)

## 507. §B.1, “WordprocessingML”, p. 4688, lines 1134–1137

[DR 09-0017]

<<Relax NG schema change description goes here>>

## 508. §B.1, “WordprocessingML”, p. 4688, lines 1134–1137

[DR 09-0018]

<<Relax NG schema change description goes here>>

## 509. §B.1, “WordprocessingML”, new type

[DR 09-0011]

<<Relax NG schema change description goes here>>

## 510. §B.1.1.1, “Comments Part”, p. 4708

[DR 09-0276]

[This schema is available in the file WordprocessingML\\_Comments.rnc.](#)

## 511. §B.1.1.2, “Document Settings Part”, p. 4708

[DR 09-0276]

[This schema is available in the file WordprocessingML\\_Document\\_Settings.rnc.](#)

## 512. §B.1.1.3, “Endnotes Part”, p. 4708

[DR 09-0276]

[This schema is available in the file WordprocessingML\\_Endnotes.rnc.](#)

## 513. §B.1.1.4, “Font Table Part”, p. 4709

[DR 09-0276]

[This schema is available in the file WordprocessingML\\_Font\\_Table.rnc.](#)

## 514. §B.1.1.5, “Footer Part”, p. 4709

[DR 09-0276]

[This schema is available in the file WordprocessingML\\_Footer.rnc.](#)

## 515. §B.1.1.6, “Footnotes Part”, p. 4709

[DR 09-0276]

[This schema is available in the file WordprocessingML\\_Footnotes.rnc.](#)

## 516. §B.1.1.7, “Glossary Document Part”, p. 4710

[DR 09-0276]

[This schema is available in the file WordprocessingML\\_Glossary\\_Document.rnc.](#)

## 517. §B.1.1.8, “Header Part”, p. 4710

[DR 09-0276]

[This schema is available in the file WordprocessingML\\_Header.rnc.](#)

## 518. §B.1.1.9, “Mail Merge Recipient Data Part”, p. 4710

[DR 09-0276]

[This schema is available in the file WordprocessingML\\_Mail\\_Merge\\_Recipient\\_Data.rnc.](#)

## 519. §B.1.1.10, “Main Document Part”, p. 4711

[DR 09-0276]

[This schema is available in the file WordprocessingML\\_Main\\_Document.rnc.](#)

## 520. §B.1.1.11, “Numbering Definitions Part”, p. 4711

[DR 09-0276]

[This schema is available in the file WordprocessingML\\_Numbering\\_Definitions.rnc.](#)

## 521. §B.1.1.12, “Style Definitions Part”, p. 4711

[DR 09-0276]

[This schema is available in the file WordprocessingML\\_Style\\_Definitions.rnc.](#)

## 522. §B.1.1.13, “Web Settings Part”, p. 4712

[DR 09-0276]

[This schema is available in the file WordprocessingML\\_Web\\_Settings.rnc.](#)

## 523. §B.2, “SpreadsheetML”, p. 4712

[DR 09-0276]

[This schema is available in the file sml.rnc.](#)

## 524. §B.2, “SpreadsheetML”, p. 4714, lines 78-81

[DR 09-0233]

```
sml_CT_DynamicFilter =  
    attribute type { sml_ST_DynamicFilterType },  
    attribute val { xsd:double }?,  
    attribute valIso { xsd:dateTime }?,  
    attribute maxValIso { xsd:dateTime }?
```

## 525. §B.2, “SpreadsheetML”, p. 4789, lines 4056–4060

[DR 09-0010]

<<Relax NG schema change description goes here>>

## 526. §B.2.1.1, “Calculation Chain Part”, p. 4800

[DR 09-0276]

[This schema is available in the file SpreadsheetML\\_Calculation\\_Chain.rnc.](#)

## 527. §B.2.1.2, “Chartsheet Part”, p. 4800

[DR 09-0276]

[This schema is available in the file SpreadsheetML\\_Chartsheet.rnc.](#)

## 528. §B.2.1.3, “Comments Part”, p. 4800

[DR 09-0276]

[This schema is available in the file SpreadsheetML\\_Comments.rnc.](#)

## 529. §B.2.1.4, “Connections Part”, p. 4801

[DR 09-0276]

[This schema is available in the file SpreadsheetML\\_Connections.rnc.](#)

## 530. §B.2.1.5, “Custom XML Mappings Part”, p. 4801

[DR 09-0276]

[This schema is available in the file SpreadsheetML\\_Custom\\_XML\\_Mappings.rnc.](#)

## 531. §B.2.1.6, “Dialogsheet Part”, p. 4801

[DR 09-0276]

[This schema is available in the file SpreadsheetML\\_Dialogsheet.rnc.](#)

## 532. §B.2.1.7, “Drawing Part”, p. 4801

[DR 09-0276]

[This schema is available in the file SpreadsheetML\\_Drawing.rnc.](#)

## 533. §B.2.1.8, “External Workbook References Part”, p. 4802

[DR 09-0276]

[This schema is available in the file SpreadsheetML\\_External\\_Workbook\\_References.rnc.](#)

## 534. §B.2.1.9, “Metadata Part”, p. 4802

[DR 09-0276]

[This schema is available in the file SpreadsheetML\\_Metadata.rnc.](#)

## 535. §B.2.1.10, “Pivot Table Part”, p. 4802

[DR 09-0276]

[This schema is available in the file SpreadsheetML\\_Pivot\\_Table.rnc.](#)

## 536. §B.2.1.11, “Pivot Table Cache Definition Part”, p. 4803

[DR 09-0276]

[This schema is available in the file SpreadsheetML\\_Pivot\\_Table\\_Cache\\_Definition.rnc.](#)

## 537. §B.2.1.12, “Pivot Table Cache Records Part”, p. 4803

[DR 09-0276]

[This schema is available in the file SpreadsheetML\\_Pivot\\_Table\\_Cache\\_Records.rnc.](#)

## 538. §B.2.1.13, “Query Table Part”, p. 4803

[DR 09-0276]

[This schema is available in the file SpreadsheetML\\_Query\\_Table.rnc.](#)

## 539. §B.2.1.14, “Shared String Table Part”, p. 4803

[DR 09-0276]

[This schema is available in the file SpreadsheetML\\_Shared\\_String\\_Table.rnc.](#)

## 540. §B.2.1.15, “Shared Workbook Revision Headers Part”, p. 4804

[DR 09-0276]

[This schema is available in the file SpreadsheetML Shared Workbook Revision Headers.rnc.](#)

## 541. §B.2.1.16, “Shared Workbook Revision Log Part”, p. 4804

[DR 09-0276]

[This schema is available in the file SpreadsheetML Shared Workbook Revision Log.rnc.](#)

## 542. §B.2.1.17, “Shared Workbook User Data Part”, p. 4804

[DR 09-0276]

[This schema is available in the file SpreadsheetML Shared Workbook User Data.rnc.](#)

## 543. §B.2.1.18, “Single Cell Table Definitions Part”, p. 4804

[DR 09-0276]

[This schema is available in the file SpreadsheetML Single Cell Table Definitions.rnc.](#)

## 544. §B.2.1.19, “Styles Part”, p. 4805

[DR 09-0276]

[This schema is available in the file SpreadsheetML Styles.rnc.](#)

## 545. §B.2.1.20, “Table Definitions Part”, p. 4805

[DR 09-0276]

[This schema is available in the file SpreadsheetML Table Definitions.rnc.](#)

## 546. §B.2.1.21, “Volatile Dependencies Part”, p. 4805

[DR 09-0276]

[This schema is available in the file SpreadsheetML Volatile Dependencies.rnc.](#)

## 547. §B.2.1.22, “Workbook Part”, p. 4806

[DR 09-0276]

[This schema is available in the file SpreadsheetML Workbook.rnc.](#)

**548. §B.2.1.23, “Worksheet Part”, p. 4806**

[DR 09-0276]

[This schema is available in the file SpreadsheetML\\_Worksheet.rnc.](#)**549. §B.3, “PresentationML”, p. 4828**

[DR 09-0276]

[This schema is available in the file pml.rnc.](#)**550. §B.3, “PresentationML”, p. 4818, line 606**

[DR 09-0079]

```
p_ST_SlideSizeCoordinate =
  xsd:int {
    minInclusive = "0"
    minInclusive = "914400"
    maxInclusive = "51206400"
  }
```

**551. §B.3, “PresentationML”, pp. 4822–4823, lines 864–868**

[DR 09-0242]

```
p_CT_GraphicalObjectFrame =
  ...
  attribute bwMode { a\_ST\_BlackWhiteMode }?
```

**552. §B.3.1.1, “Comment Authors Part”, p. 4828**

[DR 09-0276]

[This schema is available in the file PresentationML\\_Comments.rnc.](#)**553. §B.3.1.2, “Comments Part”, p. 4828**

[DR 09-0276]

[This schema is available in the file PresentationML\\_Comment\\_Authors.rnc.](#)**554. §B.3.1.3, “Handout Master Part”, p. 4828**

[DR 09-0276]

[This schema is available in the file PresentationML\\_Handout\\_Master.rnc.](#)

**555. §B.3.1.4, “Notes Master Part”, p. 4828**

[DR 09-0276]

[This schema is available in the file PresentationML\\_Notes\\_Master.rnc.](#)

**556. §B.3.1.5, “Notes Slide Part”, p. 4829**

[DR 09-0276]

[This schema is available in the file PresentationML\\_Notes\\_Slide.rnc.](#)

**557. §B.3.1.6, “Presentation Part”, p. 4829**

[DR 09-0276]

[This schema is available in the file PresentationML\\_Presentation.rnc.](#)

**558. §B.3.1.7, “Presentation Properties Part”, p. 4829**

[DR 09-0276]

[This schema is available in the file PresentationML\\_Presentation\\_Properties.rnc.](#)

**559. §B.3.1.8, “Slide Part”, p. 4829**

[DR 09-0276]

[This schema is available in the file PresentationML\\_Slide.rnc.](#)

**560. §B.3.1.9, “Slide Layout Part”, p. 4830**

[DR 09-0276]

[This schema is available in the file PresentationML\\_Slide\\_Layout.rnc.](#)

**561. §B.3.1.10, “Slide Master Part”, p. 4830**

[DR 09-0276]

[This schema is available in the file PresentationML\\_Slide\\_Master.rnc.](#)

**562. §B.3.1.11, “Slide Synchronization Data Part”, p. 4830**

[DR 09-0276]

[This schema is available in the file PresentationML\\_Slide\\_Synchronization\\_Data.rnc.](#)

### 563. §B.3.1.12, “User Defined Tags Part”, p. 4831

[DR 09-0276]

[This schema is available in the file PresentationML\\_Presentation.rnc.](#)

### 564. §B.3.1.13, “View Properties Part”, p. 4831

[DR 09-0276]

[This schema is available in the file PresentationML\\_Presentation\\_Properties.rnc.](#)

### 565. §B.4.1, “DrawingML - Main”, p. 4831

[DR 09-0276]

[This schema is available in the file dml-main.rnc.](#)

### 566. §B.4.1.1.1, “Table Styles Part”, p. 4874

[DR 09-0276]

[This schema is available in the file DrawingML\\_Table\\_Styles.rnc.](#)

### 567. §B.4.1.1.2, “Theme Part”, p. 4875

[DR 09-0276]

[This schema is available in the file DrawingML\\_Theme.rnc.](#)

### 568. §B.4.1.1.3, “Theme Override Part”, p. 4875

[DR 09-0276]

[This schema is available in the file DrawingML\\_Theme\\_Override.rnc.](#)

### 569. §B.4.1.1.3, “Theme Override Part”, p. 4875, line 10

[DR 09-0077]

```
start = a_themeOverride
```

### 570. §B.4.2, “DrawingML - Picture”, p. 4875

[DR 09-0276]

[This schema is available in the file dml-picture.rnc.](#)

## 571. §B.4.3, “DrawingML - Locked Canvas”, p. 4876

[DR 09-0276]

[This schema is available in the file dml-lockedCanvas.rnc.](#)

## 572. §B.4.4, “DrawingML - WordprocessingML Drawing”, p. 4876

[DR 09-0276]

[This schema is available in the file dml-wordprocessingDrawing.rnc.](#)

## 573. §B.4.5, “DrawingML - SpreadsheetML Drawing”, p. 4878

[DR 09-0276]

[This schema is available in the file dml-spreadsheetDrawing.rnc.](#)

## 574. §B.5.1, “DrawingML - Charts”, p. 4880

[DR 09-0276]

[This schema is available in the file dml-chart.rnc.](#)

## 575. §B.5.1, “Drawing ML - Charts”, p. 4884, lines 192–193

[DR 09-0002]

```
dchrt_ST_HoleSize =  
xsd:unsignedByte { minInclusive = "10" maxInclusive = "90" }
```

## 576. §B.5.1, “Drawing ML - Charts”, pp. 4885–4886, lines 261–272

[DR 09-0004]

```
dchrt_ST_MarkerStyle =  
string "circle"  
...  
| string "x"  
| string "auto"
```

## 577. §B.5.1, “Drawing ML - Charts”, p. 4886, lines 311–312

[DR 09-0003]

<<Relax NG schema change description goes here>>

## 578. §B.5.1, “Drawing ML - Charts”, p. 4892, lines 652

[DR 09-0006]

```
dchrt_ST_Skip = xsd:unsignedInt { minInclusive = "1" }
```

## 579. §B.5.1.1.1, “Chart Part”, p. 4898

[DR 09-0276]

[This schema is available in the file DrawingML\\_Chart.rnc.](#)

## 580. §B.5.1.1.2, “Chart Drawing Part”, p. 4898

[DR 09-0276]

[This schema is available in the file DrawingML\\_Chart\\_Drawing.rnc.](#)

## 581. §B.5.2, “DrawingML - Chart Drawing”, p. 4898

[DR 09-0276]

[This schema is available in the file dml-chartDrawing.rnc.](#)

## 582. §B.5.3, “DrawingML - Diagrams”, p. 4900

[DR 09-0276]

[This schema is available in the file dml-diagram.rnc.](#)

## 583. §B.5.3.1.1, “Diagram Colors Part”, p. 4915

[DR 09-0276]

[This schema is available in the file DrawingML\\_Diagram\\_Colors.rnc.](#)

## 584. §B.5.3.1.2, “Diagram Data Part”, p. 4915

[DR 09-0276]

[This schema is available in the file DrawingML\\_Diagram\\_Data.rnc.](#)

## 585. §B.5.3.1.3, “Diagram Layout Definitions Part”, p. 4915

[DR 09-0276]

[This schema is available in the file DrawingML\\_Diagram\\_Layout\\_Definition.rnc.](#)

## 586. §B.5.3.1.4, “Diagram Style Part”, p. 4915

[DR 09-0276]

[This schema is available in the file DrawingML\\_Diagram\\_Style.rnc.](#)

## 587. §B.6.1, “Math”, p. 4916

[DR 09-0276]

[This schema is available in the file shared-math.rnc.](#)

## 588. §B.6.1, “Math”, p. 4920, line 240

[DR 09-0011]

```
m_EG_OMathElements = m_EG_OMathMathElements | w_EG_RunLevelElts w_EG_PContentMath
```

## 589. §B.6.2, “Extended Properties”, p. 4921

[DR 09-0276]

[This schema is available in the file shared-documentPropertiesExtended.rnc.](#)

## 590. §B.6.2.1.1, “Extended File Properties Part”, p. 4922

[DR 09-0276]

[This schema is available in the file Shared\\_Extended\\_File\\_Properties.rnc.](#)

## 591. §B.6.3, “Custom Properties”, p. 4922

[DR 09-0276]

[This schema is available in the file shared-documentPropertiesCustom.rnc.](#)

## 592. §B.6.3.1.1, “Custom File Properties Part”, p. 4923

[DR 09-0276]

[This schema is available in the file Shared\\_Custom\\_File\\_Properties.rnc.](#)

## 593. §B.6.4, “Variant Types”, p. 4923

[DR 09-0276]

[This schema is available in the file shared-documentPropertiesVariantTypes.rnc.](#)

**594. §B.6.5, “Custom XML Data Properties”, p. 4927**

[DR 09-0276]

[This schema is available in the file shared-customXmlDataProperties.rnc.](#)

**595. §B.6.5.1.1, “Custom XML Data Properties Part”, p. 4927**

[DR 09-0276]

[This schema is available in the file Shared\\_Custom\\_XML\\_Data\\_Storage\\_Properties.rnc.](#)

**596. §B.6.6, “Bibliography”, p. 4927**

[DR 09-0276]

[This schema is available in the file shared-bibliography.rnc.](#)

**597. §B.6.6.1.1, “Bibliography Part”, p. 4929**

[DR 09-0276]

[This schema is available in the file Shared\\_Bibliography.rnc.](#)

**598. §B.6.7, “Additional Characteristics”, p. 4929**

[DR 09-0276]

[This schema is available in the file shared-additionalCharacteristics.rnc.](#)

**599. §B.6.7.1.1, “Additional Characteristics Part”, p. 4930**

[DR 09-0276]

[This schema is available in the file Shared\\_Additional\\_Characteristics.rnc.](#)

**600. §B.6.8, “Office Document Relationships”, p. 4930**

[DR 09-0276]

[This schema is available in the file shared-relationshipReference.rnc.](#)

**601. §B.6.9, “Shared Simple Types”, p. 4930**

[This schema is available in the file shared-commonSimpleTypes.rnc.](#)

**602. §B.7, “Custom XML Schema References”, p. 4932**

[DR 09-0276]

This schema is available in the file shared-customXmlSchemaProperties.rnc.**603. §B.8.1, “Any”, p. 4932**

[DR 09-0276]

This schema is available in the file any.rnc.**604. §B.8.2, “XML”, p. 4932**

[DR 09-0276]

This schema is available in the file xml.rnc.**605. §E, “Processing Bitfields with XSLT”, pp. 4937–4939**

[DR 09-0100]

{Delete this annex.}

**606. §F, “WordprocessingML Custom XML Data Extraction”, p. 4940–4941**

[DR 09-0156]

```

<?xml version="1.0" encoding="UTF-8" ?>
<xsl:stylesheet version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
    xmlns:w="http://schemas.openxmlformats.org/wordprocessingml/2006/main">

    <!-- This parameter should have the same value as
        ignoreMixedContent settings (see 17.15.1.54 in Part 1) -->
    <xsl:param name="ignoreMixedContent" select="false()"/>

    <!-- Some document structure checks -->
    <xsl:template match="/">
        <xsl:if test="count(/w:customXml/ancestor-or-self::w:customXml) > 1">
            <xsl:if test="count(/w:customXml/ancestor-or-self::w:customXml[last()]) >
1">
                <xsl:message>Output will not be well formed and will have more than one
root element.</xsl:message>
                <xsl:message>Produced XML document will not be WF and will have more
than one root element.</xsl:message>
            </xsl:if>
        </xsl:if>
    </xsl:template>

```

```

<!-- Process content of document -->
<xsl:apply-templates/>
</xsl:template>

...
<!-- copy over only text inside custom XML -->
<xsl:template match="text()[ancestor::w:customXml]" priority="10">
<xsl:template match="text()[ancestor::w:customXml[not(.//w:customXml)]]"
priority="10">
    <xsl:value-of select="."/>
</xsl:template>

<!-- warn about mixed content -->
<xsl:template match="text()[ancestor::w:customXml]" priority="5">
    <xsl:choose>
        <xsl:when test="$ignoreMixedContent">
            <xsl:message>Stripping "<xsl:value-of select="."/>" from
output.</xsl:message>
            <xsl:message>This text is part of mixed content and would cause non-
valid result.</xsl:message>
        </xsl:when>
        <xsl:otherwise>
            <xsl:value-of select="."/>
        </xsl:otherwise>
    </xsl:choose>
</xsl:template>

<!-- warn about text which is not tagged -->
<xsl:template match="text()">
    <xsl:message>Stripping "<xsl:value-of select="."/>" from
output.</xsl:message>
    <xsl:message>This text is not enclosed by root element and will result in
well-formed output.</xsl:message>
    <xsl:message>This text is not enclosed by root element and would cause non-
WF result.</xsl:message>
</xsl:template>

<!-- do not pick up deleted content -->
<xsl:template match="w:del|w:moveFrom"/>
</xsl:stylesheet>

```

## 607. §F, “WordprocessingML Custom XML Data Extraction”, p. 4941

[DR 09-0029]

Once this custom markup is extracted, the resulting XML document can be validated separately from the WordprocessingML document.

For example, the custom XML for the example on p. 530, once extracted, would be:

```
<invoice xmlns="http://www.example.com/2006/invoice">
    <customerName>Tristan Davis</customerName>
</invoice>
```

An application can employ any desired method to find the appropriate schema(s) for validation. As an example, one such approach using information defined by this Standard might be:

- Locate the schema element (§23.2.1) in the Document Settings part whose uri attribute matches the namespace of the root element in the XML document extracted from custom XML markup
- If that element also specifies a schemaLocation attribute, the resulting path is used to locate the schema used for validation.
- Once this schema is located, validation should be triggered based on the value of doNotValidateAgainstSchema (§17.15.1.43).

## 608. §K.5.8.1, “Using Captions and Long Descriptions in WordprocessingML Tables”, pp. 5061–5062

[DR 08-0010]

```
<w:body>
    <w:tbl>
        <w:tblPr>
            ...
            <w:tblLook w:val="04A0" w:firstRow="true" w:firstColumn="true"
                        w:noVBand="true"/>
        <w:tblCaption w:val="2004 Figures"/>
        <w:tblDescription w:val="This table shows that sales figure have been
rising for the past five quarters."/>
    </w:tblPr>
    ...
</w:tbl>
...
</w:body>
```

## 609. §M.1.5.9, “Vertically Merged Cells”, p. 5085

[DR 09-0115]

Although the previous examples might have implied that tables have strict definition of rows, table cells can also be merged vertically. The tcPr element can contain the vMerge element that defines the extent of vertically merged grid columns within a table. A vMerge element with its val attribute set to restart marks the start of a vertically merged cell range. A vMerge element with the val attribute set to continue (the default value) marks the continuation of a vertically merged grid column. Cells between the first and last merged cell that are part of the vertical merge each must have a vMerge element to continue the vertical merge.

## 610. §M.1.5.9, “Vertically Merged Cells”, pp. 5086–5087

[DR 09-0115]

```
<w:tcPr>
  <w:vMerge w:val="restart"/>
</w:tcPr>
...
<w:tcPr>
  <w:vMerge/>
</w:tcPr>
```

As shown, the vMerge with a value of restart begins (or restarts) a merged region, and the cell with no value is merged with the one above.

## 611. §M.1.8.2, “Style Definitions”, p. 5097

[DR 09-0121]

```
<w:style w:type="paragraph" w:styleId="Heading1">
  ...
  <w:qFormat/>
  ...
</w:style>
```

## 612. §M.1.8.3, “Paragraph Styles”, p. 5098

[DR 09-0121]

```
<w:style w:type="paragraph" w:styleId="TestParagraphStyle">
  ...
  <w:qFormat/>
  ...
</w:style>
```

## 613. §M.1.8.4, “Character Styles”, p. 5099

[DR 09-0121]

```
<w:style w:type="character" w:styleId="TestCharacterStyle">
  ...
  <w:qFformat/>
  ...
</w:style>
```

## 614. §M.1.8.5, “Linked Styles”, p. 5100

[DR 09-0121]

```
<w:style w:type="paragraph" w:styleId="TestLinkedStyle">
  ...
  <w:qFformat/>
  ...
</w:style>
```

## 615. §M.1.8.5, “Linked Styles”, p. 5100

[DR 09-0081]

... indent is 1\_inch left.

## 616. §M.1.8.7, “Table Styles”, p. 5105

[DR 08-0010]

The use or omission conditional formats are specified using the `tblLook` element, which contains a  ~~bitmask representing number of attributes that indicate~~  which properties are applied and omitted.

## 617. §M.1.8.7, “Table Styles”, p. 5106

[DR 08-0010]

```
<w:tbl>
  <w:tblPr>
    <w:tblStyle w:val="Style2"/>
    <w:tblW w:w="0" w:type="auto"/>
    <w:tblLook w:val="0660" w:firstRow="true" w:lastRow="true"
      w:noHBand="true" w:noVBand="true"/>
  </w:tblPr>
  ...
</w:tbl>
```

```

...
<w:tbl>
  <w:tblPr>
    <w:tblStyle w:val="Style2"/>
    <w:tblW w:w="0" w:type="auto"/>
    <w:tblLook w:val="0460" w:firstRow="true" w:lastRow="true"
      w:noVBand="true"/>
  </w:tblPr>
  ...
</w:tbl>
```

## 618. §M.1.8.11, “Latent Styles”, p. 5109

[DR 09-0121]

```

<w:latentStyles w:defLockedState="0" w:defUIPriority="99"
  w:defSemiHidden="1" w:defUnhideWhenUsed="1" w:defQFormat="0"
  w:count="180">
  <w:lsdException w:name="Normal" w:unhideWhenUsed="0"
    w:qFormat="1"/>
  <w:lsdException w:name="heading 1" w:semiHidden="0" w:uiPriority="1"/>
  <w:lsdException w:name="heading 2" w:uiPriority="1"
    w:unhideWhenUsed="1"/>
  <w:lsdException w:name="heading 3" w:semiHidden="0"/>
  <w:lsdException w:name="heading 4" w:uiPriority="1" w:qFormat="1"/>
  <w:lsdException w:name="heading 5" w:uiPriority="1" w:qFormat="1"/>
  <w:lsdException w:name="heading 6" w:uiPriority="1" w:qFormat="1"/>
  <w:lsdException w:name="heading 7" w:uiPriority="1" w:qFormat="1"/>
  <w:lsdException w:name="heading 8" w:uiPriority="1" w:qFormat="1"/>
  <w:lsdException w:name="heading 9" w:uiPriority="1" w:qFormat="1"/>
  <w:lsdException w:name="Normal Indent" w:uiPriority="6" w:qFormat="1"/>
</w:latentStyles>
```

## 619. §M.1.10.3, “Abstract Numbering Definitions”, p. 5116

[DR 09-0108]

```

<w:lvl w:ilvl="1">
  <w:start w:val="4"/>
  <w:nfc w:val="3"/>
  <w:pStyle w:val="Heading1"/>
  <w:lvlText w:val="BEFORE %2 AFTER %1 END"/>
  <w:lvlJc w:val="startLeft"/>
  ...
</w:lvl>
```

**620. §M.1.10.4, “Numbering Definition Instances”, p. 5118**

[DR 09-0108]

```
<w:lvl w:ilvl="0">
  <w:start w:val="4" />
  <w:lvlText w:val="%1)" />
  <w:lvlJc w:val="startLeft" />
  <w:pPr>
    <w:ind w:left="360" w:hanging="360" />
  </w:pPr>
</w:lvl>
```

**621. §M.1.10.6, “The Complete Story”, p. 5122**

[DR 09-0108]

```
<w:lvl w:ilvl="0">
  <w:start w:val="1" />
  <w:lvlText w:val="%1." />
  <w:lvlJc w:val="startLeft" />
  ...
</w:lvl>
```

**622. §M.1.10.8, “Referencing Numbering Styles”, p. 5125**

[DR 09-0108]

```
<w:lvl w:ilvl="0">
  <w:lvlText w:val="%1 %1 %1" />
  <w:lvlJc w:val="startLeft" />
  ...
</w:lvl>
```

**623. §M.1.10.8, “Referencing Numbering Styles”, p. 5126**

[DR 09-0108]

```
<w:lvl w:ilvl="0">
  <w:lvlText w:val="%1 %1 %1" />
  <w:lvlJc w:val="startLeft" />
  ...
</w:lvl>
```

**624. §M.2.8.3.2.2, “Metadata Behaviors”, p. 5225**

[DR 09-0150]

The metadata type expresses operations on cells that allow the metadata to remain associated with the cell. Operations not listed or set to ~~10~~<sup>1</sup> would cause the metadata to no longer be associated with the cell.

**625. §M.2.9.3.2, “XML - pivotCacheDefinition part”, p. 5239**

[DR 09-0087]

```
<pivotCacheDefinition xmlns:r="..." r:id="rId1" refreshedBy="AnonUser"
    refreshedDateIso="2006-05-22T10:07:16" createdVersion="3"
    refreshedVersion="3" minRefreshableVersion="3" recordCount="182">
    ...
</pivotCacheDefinition>
```

**626. §M.2.9.3.2, “XML - pivotCacheDefinition part”, p. 5242**

[DR 09-0087]

- refreshedDateIso indicates when the PivotCache was last refreshed.

**627. §M.2.9.3.4.5, “Row Items”, pp. 5251–5252**

[DR 09-0150]

Note that the first item has no r explicitly written. Since a default of ~~10~~<sup>1</sup> is specified in the schema, for any item whose r is missing, a default value of ~~10~~<sup>1</sup> is implied.

Note that the first instance of x has no attribute value v associated with it, so v's default value of ~~10~~<sup>1</sup> is implied.

... The first item value "Bikes" is expressed implicitly, because the value of r on the second i element is ~~10~~<sup>1</sup>, indicating that the first item value from the previous row is reused again as the first item value for the current row. ...

**628. §M.2.9.3.4.7, “Column Items”, p. 5254**

[DR 09-0150]

Note that the first item has no r explicitly written so the default value of ~~10~~<sup>1</sup> is implied.

...

Note that the first instance of x has no attribute value v associated with it, so v's default value of ~~10~~<sup>1</sup> is implied.

## 629. §M.2.12.3, “Pivot XML fragment”, p. 5269

[DR 09-0087]

```
<pivotCacheDefinition ... saveData="0" refreshedBy="Chad Rothschilder"
    refreshedDateIso="2006-04-13T16:02:14" backgroundQuery="1"
    createdVersion="3"
    refreshedVersion="3" minRefreshableVersion="3" recordCount="0">
    ...
</pivotCacheDefinition>
```

## 630. §M.4.6.2.2, “Camera”, p. 5374

[DR 08-0002]

The only complex type contained in the camera, CT\_SphereCoords, is a complex type defined elsewhere within the DrawingML. There are three simple types associated with a camera:

- ST\_FOVAngle (field of view angle), which is a positive angle between 0 and 180 in 60,000th of a degree.
- ST\_PositivePercentage (zoom), which is defined as a percentage ~~in 1,000th of a percent~~.
- ST\_PresentCameraType (preset camera)

## 631. §M.6.1, “Math”, p. 5507

[DR 09-0086]

*{The right-most of each pair of figures is to be removed, as shown below.}*

... That is,  $\overrightarrow{abc}$  and  $\overbrace{abc}^{\overrightarrow{abc}}$  are represented ... Similarly,  $\frac{n}{k}$  and  $\frac{n}{\cancel{k}}$  are both ...

## 632. §N.1, “WordprocessingML”, p. 5554

[DR 09-0111]

- The following enumeration values were added to the ST\_TextDirection simple type (§xx): ~~bt~~, tb, r1, lr, tbV, r1V, and lrV.